

Appendix B

**Mobility Analysis Report
University of the Nations Kona
Master Plan Update
Kona, Hawai'i
Fehr & Peers, Inc., February 2020**

**Mobility Analysis Report for the
University of the Nations Kona
Master Plan Update
Kona, HI**

Prepared for:
University of the Nations Kona

FINAL February 18, 2020

SD19-0323

FEHR  PEERS

Table of Contents

1.0	EXECUTIVE SUMMARY	4
1.1	Intersection Operations.....	4
1.2	Future Phase 2 and Phase 3 Assessment.....	5
1.3	Vehicular Access and Circulation.....	6
1.4	Multimodal Assessment.....	8
2.0	INTRODUCTION	10
2.1	Project Description.....	10
2.2	Project Study Area.....	14
2.3	Study Scenarios.....	14
2.4	Traffic Analysis Methods.....	15
2.4.1	Signalized Intersections.....	15
2.4.2	Unsignalized Intersections.....	16
2.4.3	Significant Impact Criteria	17
3.0	EXISTING CONDITIONS.....	19
3.1	Existing Site	19
3.2	Existing Transportation Facilities.....	19
3.2.1	Existing Roadway System.....	19
3.2.2	Existing Transit Facilities and Services	20
3.2.3	Existing Bicycle Activity.....	20
3.2.4	Existing Pedestrian Activity	21
3.3	Existing Traffic Volumes/Lane Configurations.....	21
3.4	Field Observations.....	22
3.5	Existing Intersection Levels of Service	22
4.0	PHASE 1 (2030) NO PROJECT CONDITIONS.....	25
4.1	Phase 1 (2030) No Project Traffic Estimates.....	25
4.1.1	Areawide or Ambient Traffic Growth	25
4.1.2	Future Transportation Improvements.....	25
4.2	Phase 1 (2030) No Project Levels of Service.....	27



5.0 PROJECT TRAFFIC ESTIMATES..... 29

5.1 Project Trip Generation Estimates..... 29

5.2 Project Trip Distribution and Assignment..... 30

6.0 PHASE 1 (2030) PLUS PROJECT CONDITIONS..... 34

6.1 Phase 1 (2030) Plus Project Intersection Level of Service 34

6.2 Signal Warrant Analysis..... 38

6.3 Potential Intersection Impacts 38

6.4 Special Events..... 38

7.0 FUTURE PHASE 2 AND PHASE 3 ASSESSMENT 40

7.1 Phase 2 “Hot Spot” Assessment..... 40

7.2 Phase 3 Development Beyond 2040..... 42

8.0 VEHICLE ACCESS, CIRCULATION, AND PARKING 43

8.1 Vehicular Site Access 43

8.2 On-Site Vehicle Circulation 43

8.3 Parking..... 44

9.0 MULTIMODAL ASSESSMENT 45

9.1 Pedestrian and Bicycle Access and Circulation 45

9.1.1 Off-Site Pedestrian and Bicycle Access 45

9.1.2 On-Site Pedestrian and Bicycle Circulation 46

9.2 Transit Access 46

9.3 Recommended Improvements..... 46

9.3.1 Off-Site Pedestrian and Bicycle Improvements..... 46

9.3.2 On-Site Pedestrian and Bicycle Improvements..... 47

Appendices

- Appendix A: Traffic Count Data
- Appendix B: LOS Worksheets
- Appendix C: 4-Hour signal Warrant Worksheets
- Appendix D: 8-Hour signal Warrant Worksheets



List of Figures

Figure 2-1. Project Site & Study Intersections..... 12
 Figure 2-2. Proposed Site Plan..... 13
 Figure 3-1. Peak Hour Traffic Volumes and Lane Configurations – Existing (2019) Conditions 24
 Figure 4-1. Peak Hour Traffic Volumes and Lane Configurations – Phase 1 (2030) No Project Conditions . 26
 Figure 5-1. Project Trip Distribution 32
 Figure 5-2. Project Trip Assignment 33
 Figure 6-1. Peak Hour Traffic Volumes and Lane Configurations – Phase 1 Plus Project Conditions..... 37
 Figure 9-1. Recommended On-Site Pedestrian and Bicycle Improvements..... 48

List of Tables

Table 2-1. Signalized Intersection Level of Service Definitions..... 16
 Table 2-2. Unsignalized Intersection Level of Service Definitions 17
 Table 3-1. Existing Peak Hour Intersection Level of Service..... 23
 Table 4-1. Phase 1 (2030) No Project Peak Hour Intersection Level of Service..... 27
 Table 5-1. Project Future Growth Factor Estimates 30
 Table 5-2. Project Trip Generation Estimates..... 30
 Table 6-1. Phase 1 (2030) With and Without Project Peak Hour Intersection Level of Service 35

1.0 EXECUTIVE SUMMARY

This report documents the assessment of traffic, mobility, and access for an update to the 2003 University of the Nations (UOFN) Kona Master Plan. The project site is on tax map key parcels TMK (3) 7-5-010: 085 and (3) 7-5-017: 006, between Kuakini Highway and Hualalai Road on the Island of Hawai'i. The project site is within the Kona Community Plan area. The existing site includes residential, religious, educational, recreational, and commercial uses.

Impacts of the proposed Master Plan Update were evaluated following guidelines established by the County of Hawai'i Department of Public Works-Engineering Division and the State of Hawai'i Department of Transportation (HDOT), which has jurisdiction over Hawai'i Belt Road/Queen Kaahumanu Highway (Highway 11). The operations of eight (8) intersections [seven (7) existing and one (1) future location] were evaluated during the weekday morning (AM) and evening (PM) peak hour for Existing (2019) and Master Plan Phase 1 (2030) conditions. Master Plan Phase 1 conditions were evaluated without and with the project.

To estimate project trip generation, multimodal counts of vehicles, bicyclists, and pedestrians were collected at the existing University of the Nations site driveway during October 2019. Vehicular counts were collected for a continuous 72-hour period, and bicycle/pedestrian counts were collected during the peak AM and PM commute periods. These counts were used to develop a per-student trip rate, which was applied to future university enrollment and employment forecasts to estimate future project trips. Using this approach, it was anticipated that 215 new peak hour trips (154 inbound/62 outbound) would occur during the AM peak hour and 161 new peak hour trips (64 inbound/97 outbound) would occur during the PM peak hour.

Project trip distribution was estimated using the location of complementary land uses and existing travel patterns, and trips were subsequently assigned to the adjacent streets. Proposed trip distribution is shown below on **Figure 5-1**. Key findings of the mobility analysis are summarized below.

1.1 INTERSECTION OPERATIONS

Under Phase 1 (2030) Plus Project conditions, all study intersections are anticipated to continue to operate at LOS D or better during the AM and PM peak hours with the addition of project-generated traffic except for the following unsignalized intersections:

- Kuakini Highway and University of the Nations Kona Driveway (LOS F, AM and PM peaks)
- Queen Kaahumanu Highway and Hualalai Road (LOS F, AM peak; LOS E, PM peak)
- Queen Kaahumanu Highway and Kuakini Highway (LOS F, AM and PM peaks)

The project is expected to cause an impact at the intersection of Kuakini Highway and University of the Nations Kona Driveway as intersection operations would degrade to undesirable LOS, and signal warrants would be met. However, the impact at this intersection can be mitigated by adding a refuge lane along Kuakini Highway to receive westbound left-turn movements from the University of Nations Kona Driveway. The addition of a refuge lane can could likely be accomplished within the existing highway right-of way with re-stripping minor pavement modifications, though additional design analysis is needed to determine construction needs for this improvement. With a refuge lane, intersection operations would improve to LOS C in both AM and PM peak hours.

The intersections of Queen Kaahumanu Highway and Hualalai Road, and Queen Kaahumanu Highway and Kuakini Highway intersections would operate at an unacceptable LOS (LOS E or F) during both peak hours under Phase 1 Plus Project conditions. However, neither intersection met any of the signal warrants in this scenario, therefore no impacts are anticipated at these locations.

1.2 FUTURE PHASE 2 AND PHASE 3 ASSESSMENT

A high-level “hot spot” assessment was conducted to identify intersections where campus activities are close to triggering impacts in Phase 1 of the campus buildout, and in which it would be reasonable to expect project impacts to likely occur in Phase 2 (i.e. by 2040) or Phase 3 (beyond 2040) as a result of further anticipated on-campus and ambient traffic growth. The assessment determined that the following intersections could either have project-related impacts during Phase 2 or may require additional attention:

- **Queen Kaahumanu Highway/Hualalai Rd and Queen Kaahumanu Highway/Kuakini Highway:** warrants are not expected to be met, but HDOT may express concern that the project would add traffic to the northbound left-turn movements at both intersections, which would contribute to increased delays for minor street approaches.
- **Kuakini Highway and the University of the Nations Kona Driveway:** a sensitivity test found that the intersection would operate at LOS E in the AM peak and LOS C in the PM peak. Further, it was determined that the intersection would also meet both 4-hour and 8-hour signal warrants with the addition of Phase 2 project trips. As such, it is likely that a signal would be required with Phase 2 of the project to enhance intersection operations, site access, and safety.
- **Queen Kaahumanu Highway and Nani Kailua Drive:** The intersection is projected to operate at acceptable levels of service under Phase 1 conditions, however the intersection would likely operate worse than what is shown because congestion along Queen Kaahumanu Highway limits the number of vehicles that are able to pass through the intersection during the peak hour. Intersection conditions would likely continue to degrade with the addition of ambient and project-related traffic in Phase 2. If it is determined that Phase 2 of the project would create a

significant impact, the project may be required to contribute funding for anticipated roadway improvements (e.g. widening of Queen Kaahumanu Highway) or signal modifications.

- **Kuakini Highway Widening:** The secondary access into the project site (TMK (3) 7-5-010:085) off of Kuakini Highway is scheduled to be a part of Phase 2. In general, the secondary access on Kuakini Highway would help to distribute traffic on that highway; however, with increased through and project traffic after 2030, Kuakini Highway may need to be widened to accommodate a left-turn lane in and a refuge lane for left-turn traffic out of the site. The County of Hawaii has already planned the widening of Kuakini Highway fronting the project site in Federal Aid Project No. STP 01102 (Kuakini Highway Improvements, Phase II, Hualalai Road to the Proposed Alii Highway). If the roadway widening occurs by 2040, the UOFN Kona could be required to contribute funding for select improvements within the widened corridor or if it is determined future on-campus growth would significantly impact intersections along the highway.

Beyond 2040, the potential operational issues noted above would continue to persist and operations would likely degrade further without additional improvements. However, the Kuakini Highway Improvements, Phase II will likely change the LOS on Kuakini Highway and redistribute traffic in the subregion. With planned regional improvements such as the widening of Queen Kaahumanu Highway and Kuakini Highway, the UOFN Kona could be required to contribute funding or select improvements within the widened corridor.

1.3 VEHICULAR ACCESS AND CIRCULATION

Site Access

Direct access to the project site is provided by a driveway located on Kuakini Highway and is controlled by an access gate located approximately 125 feet east of Kuakini Highway. During peak travel periods, or during special events, campus-bound traffic could potentially queue up while waiting to pass through the access gate and spill back onto Kuakini Highway. To reduce the potential for spillback onto Kuakini Highway, it is recommended that the access gate be relocated to a point further east. A second access point would also be provided off of Hualalai Road via a new unsignalized intersection and driveway leading to the project site. No vehicular site access issues are expected as a result of Phase 1.

On-Site Circulation

Under Phase 1, the proposed site plan includes the extension of two on-site internal campus roadways. First, the on-site, east-west roadway located along the northern site boundary is planned to be extended within the site from its existing eastern terminus to a new driveway on Hualalai Road (as noted above in Section 8.1). In addition, the east-west campus roadway located along the southern edge of the developed campus will be extended from its existing eastern terminus to the existing north-south roadway serving

Hualalai Village Apartments. This second campus roadway will effectively be the central spine roadway within the overall campus master plan area. On the eastern side of campus, this roadway will be limited to on-campus circulation only and will not provide a connection to Hualalai Road via Hualalai Village Road.

To manage travel speeds along both of these roadways, it is recommended that stop signs and other traffic calming devices be included at key points along the roadway. Similar treatments should be employed as appropriate on any other future on-campus roadways built as part of Phases 2 and 3 that will include longer, tangent sections of uninterrupted street segments (i.e., of 600 feet or more).

Two-way, north-south drive aisles would intersect the primary east-west roadways, and they will provide access to existing and planned parking lots. Though the drive aisles and parking lots do not provide direct access to all campus facilities, students, faculty/staff, and visitors will be able to access campus facilities via unrestricted pedestrian and bicycle pathways. More information on these facilities is included below in Section 8.3.

Parking

Vehicle parking will be provided via on- and off-street parking throughout campus. Insufficient parking was not noted as an issue by the project development team at the time this report was written. As such, it is assumed that the existing parking inventory is sufficient to accommodate the parking demand generated by current levels of campus students, faculty, staff, and visitors. Therefore, it is recommended that parking supply provided in Phase 1 of the project maintain the same ratio of campus students, faculty, staff, and visitors to parking spaces unless adjustments to the supply are needed.

On the current site plan, several on-site parking lots are shown with multiple aisles that connect directly to the future east-west primary campus roadways, which creates additional vehicle conflicts and requires pedestrians and bicyclists to cross an excessive number of vehicle paths. To enhance safety and to internalize parking movements, it is recommended that all new surface parking lots be limited to one or two access driveways per lot (depending on the number of spaces served), and adequate aisles be provided within each lot to allow for internal vehicle circulation.

1.4 MULTIMODAL ASSESSMENT

Bicycle and Pedestrian Facilities

Implementation of Phase 1 of the project will not conflict with any existing pedestrian or bicycle facilities and will not preclude the implementation of any planned pedestrian or bicycle facilities within the study area.

A proposed bike lane along Kuakini Highway from Lako Street to Hualalai Road is identified as a high-priority project in Bike Plan Hawai'i. When completed, this facility will enhance bicycle connectivity to and from the University of the Nations Kona west entrance. No pedestrian improvements are planned along roadways adjacent to the University of the Nations Kona campus.

While the project-generated pedestrian and bicycle volumes are initially expected to be low, the addition of any active travelers along Kuakini Highway may result in people walking or biking along the roadway, which could result in a potential safety issue and a significant multimodal impact. To address this issue, the following pedestrian improvements are proposed at this location:

- An elevated sidewalk should be installed between the existing sidewalk on the east side of Kuakini Highway from the existing sidewalk's terminus to the existing crosswalk approximately 600 feet north of the University of the Nations Driveway.
- A high-visibility crosswalk, adequate nighttime lighting levels, and crosswalk warning signs should be added on the north and east legs of the intersections.
- The existing striped triangle on the east leg of the intersection should be converted to an elevated area to act as a pedestrian refuge island.
- A Pedestrian Hybrid Beacon (PHB) could also be installed on the north leg of the intersection, however a warrant would need to be conducted to determine whether it would be necessary. If it is not warranted, a Rectangular Rapid-Flashing Beacon (RRFB) could be added.

Direct pedestrian and bicycle connections between campus facilities and parking lots would be provided via unrestricted pedestrian and bicycle pathways throughout campus, however no improvements are planned along on-site campus roadways. As such, the following improvements are recommended:

- A shared-use path should be included on one side of both on-site campus roadways to further enhance pedestrian and bicycle connectivity and safety throughout the campus.
- An enhanced bicycle route (e.g. bike lane or "sharrows") should be included along the makai north-south campus roadway between the northern and central roadways.

- Pedestrian-level lighting is recommended along both the shared-use path and the pedestrian sidewalk.
- Raised crosswalks should be provided at all locations where pedestrian crossings are planned.

It is also recommended that secure bike parking – including bike racks near building entrance(s) – is provided to encourage and support non-motorized travel. Specific locations for bike racks should be determined by the project team in consultation with the University of the Nations Kona staff.

Transit

The Pahala-Kailua-Kona-South Kohala Resorts Route provides daily transit service along Queen Kaahumanu Highway. The nearest bus stop would require passengers to walk or bike at least 2,000 feet from campus to use the transit service. One potential improvement would be to provide a multi-use connection directly to Hualalai Road to reduce the overall distance transit riders would have to walk or bike to access the campus.

The project is anticipated to generate a low amount of transit riders at the completion of Phase 1. As project-related transit ridership is anticipated to be low, no project impacts to transit facilities or services are anticipated, and no modifications to transit stop locations or services would be required.

2.0 INTRODUCTION

This mobility analysis report (MAR) presents the study conducted by Fehr & Peers for the University of the Nations, Kona 2020 Master Plan Update, the proposed update to the 2003 UOFN Kona Master Plan in the Kona Community Plan area of Kailua-Kona on the Island of Hawai'i. The project site is located on tax map key parcels TMK (4) 7-5-010: 085 and (4) 7-5-017: 006, between Kuakini Highway and Hualalai Road. This MAR was conducted in accordance with the guidelines and standards of the affected government agencies, and it addresses the potential impact of the project on vehicular, bicycle, pedestrian, and transit conditions.

2.1 PROJECT DESCRIPTION

The University of the Nations is a Christian university with over 600 locations across 160 countries. With approximately 500 college students, 340 Pre-K-12 students, and 750 staff members, the Kona campus is one of the largest UOFN campuses worldwide. The existing site includes residential, religious, educational, recreational, and commercial uses.

The 2020 Master Plan Update was prepared for UOFN Kona and includes plans for the Existing Campus Site as well as the Petition Area (approximately 62 acres of land adjacent to the Existing Campus). The purpose is to update the Master Plan and to reflect current and upcoming priorities since the 2002-2005 master planning and land use entitlements period. Future buildings and projects planned in 10-year increments, with emphasis given to the next 5-10 years, are projected into the 2020 Master Plan Update.

Projected future buildings and projects fall into three categories:

- Phase 1: Planning Program Projects anticipated for development within the next 5-10 years
 - 500 Pre-K-12 Students
 - 1,000 University Students
 - 900 Faculty/Staff Members
- Phase 2: Planning Program Projects anticipated for development beyond the 10-year period
 - Potentially up to 750 Pre-K-12 Students
 - 1,500 University Students
 - 1,350 Faculty/Staff Members
- Phase 3: Planning Program Projects anticipated for development beyond the 20-year period.
 - Potentially up to 1,000 Pre-K-12 Students
 - 2,000 University Students
 - 1,800 Faculty/Staff Members

The 2020 Master Plan Update focuses on projects in the Phase 1 Planning Program, within the next 5-10 years. Projects beyond the period of 5-10 years are listed and included in the overall conceptual design of the Master Plan, but are not included for detailed description. Proposed buildings and improvements for Phase 1 of the project are as follows:


- Existing Campus Site
 - Student Resident Dormitory Buildings and Parking Area
 - Multi-Purpose Complex Building and Parking Area
- Petition Area
 - Discipleship Learning Center
 - Athletic/Training Complex
 - Lower School
 - Archaeological Preservation Sites
 - Agricultural Exhibit
 - Maintenance and Storage Facilities
 - Roadways/Pathways
 - Open Space: Lawn Areas and Landscaping

Additional facilities are planned on the existing campus site and petition area for Phase 2 and Phase 3. Phase 2 facilities may include additional discipleship learning center space, athletic/training complex space, a theatre, CERT building, and Pre-K-12 facilities, among others. Phase 3 facilities may include additional student resident dormitory buildings, faculty/staff housing, Discipleship Learning Center space, athletic/training complex space, and Pre-K-12 instructional buildings, among others.

Additionally, a second campus access point is planned on the mauka side of campus along Hualalai Village Road. Once this connection is completed, campus students, faculty/staff members, and visitors will be able to access the campus via the intersection of Hualalai Road and Hualalai Village Road.

Though details are not included in the Campus Master Plan Update, the university expects to host four or five higher-attendance community events throughout the course of the year. Each event would last between one and two weeks, and could host up to 3,000 attendees each. Additionally, the university expects to host four or five higher-attendance athletic events throughout the course of the year. Each of these events would last between one and two weeks, and could host up to 500 attendees each. A general overview of potential effects of these events are described in Section 6.4.

The location of the project site and immediate study area is shown on **Figure 2-1**. The proposed site plan showing building locations and campus access is illustrated on **Figure 2-2**.



N:\Projects\2019_P\Projects\0323_University of the Nations Kona_MAR\Graphics\GIS\Study\Intersections.mxd

Legend

- Project Study Area
- X Study Intersections
- X Future Study Intersections

Figure 2-1

Project Site & Study Intersections





Figure 2-2
Proposed Site Plan

2.2 PROJECT STUDY AREA

The project site is located in Kailua-Kona, bounded by Kuakini Highway and Hualalai Road. The campus is currently accessible via one driveway along Kuakini Highway, approximately one-half mile north of the intersection of Kuakini Highway and Walua Road/Oni Oni Street. The University of the Nations Driveway is a two-lane road that provides controlled access to university visitors. Land uses along Kuakini Highway in the vicinity of the project include commercial, single-family residential, and multi-family residential uses. Other surrounding land uses include residential neighborhoods and agricultural uses.

The mobility analysis evaluated the operations at a total of eight (8) intersections [seven (7) existing and one (1) future location] in the vicinity of the proposed project that are listed below and shown on **Figure 2-1**.

1. Kuakini Highway and Hualalai Road
2. Kuakini Highway and the University of the Nations Driveway
3. Hualalai Road and Nani Kailua Drive
4. Hualalai Road and Unnamed Campus Driveway (potential future intersection)
5. Hualalai Road and Hualalai Village Driveway
6. Nani Kailua Drive and Queen Kaahumanu Highway (Hwy 11)
7. Hualalai Road and Queen Kaahumanu Highway (Hwy 11)
8. Kuakini Highway and Queen Kaahumanu Highway (Hwy 11)

The study analyzed the potential project-related traffic impacts under typical weekday AM and PM peak hour traffic conditions. The AM and PM peak hours for each intersection are identified as the highest one-hour totals of traffic at the intersection from 6:00 to 9:00 AM and from 3:00 to 6:00 PM on a weekday.

2.3 STUDY SCENARIOS

This report includes the following types of analysis:

- **Phase 1 Detailed Intersection Operations Analysis:** Phase 1 of the Master Plan buildout was analyzed for the year 2030 using the methods described below in Section 2.4. This analysis includes the evaluation of existing and future intersections, as well as a qualitative assessment of potential impacts to study area transit services and bicycle and pedestrian facilities.
- **Phase 2 “Hot Spot” Assessment:** This analysis uses the findings from the detailed operational analysis to identify potential project impacts. The assessment identifies intersections where campus activities are close to triggering impacts in 2030, and in which it would be reasonable to expect project impacts to occur by 2040 as a result of further anticipated on-campus and ambient traffic growth.

For the Detailed Operational Analysis described above, operations of the study intersections were evaluated during weekday AM and PM peak hours for the following scenarios:

- **Existing Conditions:** The analysis of existing traffic conditions was based on 2019 counts collected for the analyzed peak hour and existing intersection configurations. The existing conditions analysis also includes a description of key area roadways and a review of existing transit facilities and services near the site.
- **Future Phase 1 (2030) No Project Conditions:** Existing peak hour volumes increased to account for approved (but not yet occupied) development projects and forecasted growth in the area at the year of anticipated implementation of Master Plan Phase 1 in 2030. Traffic growth was estimated based on an annual growth factor to account for ambient growth *plus* traffic generated from approved (but not yet constructed) and pending developments in the study area.
- **Future Phase 1 (2030) Plus Project Conditions:** This scenario provides projected traffic volumes and an assessment of operating conditions under Phase 1 Conditions with the addition of forecasted project-generated traffic. This scenario assumes intersection configurations would remain the same as the Future Phase 1 (2030) No Project scenario.

2.4 TRAFFIC ANALYSIS METHODS

The analysis of roadway operations performed for this study is based on procedures presented in the *Highway Capacity Manual 6th Edition* (HCM), published by the Transportation Research Board in 2016. The operations of roadway facilities are described with the term level of service (LOS). LOS is a qualitative description of traffic flow based on such factors as speed, travel time, delay, and freedom to maneuver. Six (6) levels are defined; from LOS A, with the least congested operating conditions, to LOS F, with the most congested operating conditions. LOS E represents “at-capacity” operations. Operations are designated as LOS F when volumes exceed capacity, resulting in stop-and-go conditions. The methodologies for signalized and unsignalized intersections are described below.

2.4.1 SIGNALIZED INTERSECTIONS

Signalized intersection operations were analyzed using the method described in Chapter 19: Signalized Intersections of the HCM. This LOS method analyzes a signalized intersection’s operation based on average control delay per vehicle. Control delay alone is used to characterize LOS for the entire intersection or an approach. Control delay includes the initial deceleration delay, queue move-up time, stopped delay, and final acceleration delay. The average control delay for signalized intersections is calculated using Synchro 10.0 analysis software and is correlated to a LOS designation as shown in **Table 2-1**.

2.4.2 UNSIGNALIZED INTERSECTIONS

Unsignalized intersection operations were evaluated using the method contained in Chapter 20: Two-Way Stop-Controlled Intersections of the HCM. LOS ratings for stop-sign-controlled intersections are based on the average control delay expressed in seconds per vehicle. At two-way or side-street-controlled (SSSC) intersections, the average control delay is calculated for each minor-street-stopped movement and the major street left turns; not for the intersection as a whole. For approaches composed of a single lane, the control delay is computed as the average of all movements in that lane. For approaches with multiple lanes, the control delay is computed for each movement; the movement with the worst (i.e., longest) delay is presented for two-way stop-controlled (TWSC). The average control delay for unsignalized intersections is calculated using Synchro 10.0 analysis software and is correlated to a LOS designation as shown in **Table 2-2**.

Table 2-1. Signalized Intersection Level of Service Definitions

Level of Service	Description	Delay in Seconds
A	Progression is extremely favorable, and most vehicles arrive during the green phase. Most vehicles do not stop at all. Short cycle lengths may also contribute to low delay.	≤ 10.0
B	Progression is good, cycle lengths are short, or both. More vehicles stop than with LOS A, causing higher levels of average delay.	> 10.0 to 20.0
C	Higher congestion may result from fair progression, longer cycle lengths, or both. Individual cycle failures may begin to appear at this level, though many still pass through the intersection without stopping.	> 20.0 to 35.0
D	The influence of congestion becomes more noticeable. Longer delays may result from some combination of unfavorable progression, long cycle lengths, or high V/C ratios. Many vehicles stop, and the proportion of vehicles not stopping declines. Individual cycle failures are noticeable.	> 35.0 to 55.0
E	This level is considered by many agencies to be the limit of desirable delay. These high delay values generally indicate poor progression, long cycle lengths, and high V/C ratios. Individual cycle failures are frequent occurrences.	> 55.0 to 80.0
F	This level is considered undesirable with oversaturation, which is when arrival flow rates exceed the capacity of the intersection. This level may also occur at high V/C ratios below 1.0 with many individual cycle failures. Poor progression and long cycle lengths may also be contributing factors to such delay levels.	> 80.0

Source: *Highway Capacity Manual*, Transportation Research Board, 2016.

Table 2-2. Unsignalized Intersection Level of Service Definitions

Level of Service	Description	Average Control Delay Per Vehicle (Seconds)
A	Little or no delay	≤ 10.0
B	Short traffic delay	> 10.0 to 15.0
C	Average traffic delays	> 15.0 to 25.0
D	Long traffic delays	> 25.0 to 35.0
E	Very long traffic delays	> 35.0 to 50.0
F	Extreme traffic delays with capacity exceeded	> 50.0

Source: *Highway Capacity Manual*, Transportation Research Board, 2016.

2.4.3 SIGNIFICANT IMPACT CRITERIA

The analysis of future conditions compares the Phase 1 or “no project” condition with conditions that include project-generated traffic assuming full development of Phase 1 uses. This is done to determine if the addition of project traffic is expected to result in a significant impact on the surrounding roadways. Based on previous studies conducted for the County of Hawai‘i, the minimum desired operating standard for a signalized intersection is LOS D for the overall intersection. Additionally, the Hawai‘i Department of Transportation (HDOT) strives to universally maintain LOS D intersection operations and in their *Draft HDOT Best Practices for Traffic Impact Report* (June 2012) defines a significant impact when the operations of an intersection, turning movement, or roadway segment change from LOS D or better to LOS E or F. Also, when evaluating intersection approach LOS at any location, other factors should be considered in the analysis, such as traffic volumes and potential secondary impacts to pedestrian, bicycle, and transit travel.

Any identified significant impacts could be further categorized as either a cumulative or direct impact. At a signalized intersection, if the addition of project traffic is expected to degrade acceptable service levels (LOS D or better) to unacceptable service levels (LOS E or F), then the project is considered to have a direct impact.

For unsignalized intersections, the criterion for a direct impact is the same as for signalized intersections regarding LOS as described above, but one or more signal warrants must also be met. The signal warrants used for this evaluation are those described in Chapter 4C of the Manual of Uniform Control Devices (MUTCD, 2009) published by the U.S. Department of Transportation Federal Highway Administration (FHWA). However, the project is determined to have a potentially significant cumulative impact when it adds traffic to a study location that includes a controlled approach operating at an unacceptable level (i.e., LOS E or F) *and* one or more volume-based signal warrants are met.

The County of Hawai'i and HDOT do not publish impact criteria for pedestrian, bicycle, and transit impacts. For this analysis, these impacts are evaluated based on whether a proposed project would: 1) conflict with existing or planned pedestrian, bicycle, or transit facilities and services, or 2) create substantive walking, bicycling, or transit use demand without providing adequate and appropriate facilities for non-motorized mobility. Existing facilities for pedestrians, bicycles, and transit users were inventoried to evaluate the quality and scope of facilities/services currently in place. The assessments of planned pedestrian, bicycle, and transit facilities were conducted using information in planning documents, such as the *Bike Plan Hawai'i Master Plan (2012)*, *Statewide Pedestrian Master Plan (2013)*, and *County of Hawai'i Transit and Multi-Modal Transportation Master Plan (2018)*. For these modes, if the proposed project is expected to conflict with existing or planned improvements to pedestrian and bicycle facilities, or if the project is expected to generate a substantial demand which could warrant additional transit service, then the project would be determined to have a project-specific impact to non-motorized modes of transportation.

3.0 EXISTING CONDITIONS

This chapter describes the existing transportation network and includes a discussion of pedestrian, bicycle, and transit facilities located within the project study area. This chapter also includes a discussion of the existing intersection LOS operation results.

3.1 EXISTING SITE

The University of the Nations campus is located at 75-5952 Kuakini Highway in the community of Kona in Hawai'i County. The project site is on tax map key parcels TMK (4) 7-5-010: 085 and (4) 7-5-017: 006, between Kuakini Highway and Hualalai Road. The existing campus includes the following mix of uses:

- Residential land use (e.g., student and faculty housing)
- Religious land use (i.e., chapel)
- Educational land use (e.g., classrooms, campus services)
- Recreational land use (e.g., sports complex, swimming pool)
- Commercial land use (e.g., coffee shop, convenience store)

3.2 EXISTING TRANSPORTATION FACILITIES

A comprehensive data collection effort was undertaken to identify existing transportation conditions in the vicinity of the proposed project. The assessment of existing conditions relevant to this study includes an inventory of the street system, traffic volumes on these facilities, and operating conditions at key intersections. Existing public transit, bicycle, and pedestrian facilities are also described.

3.2.1 EXISTING ROADWAY SYSTEM

The key roadways providing access to or in the vicinity of the study area are described below.

The University of the Nations Driveway provides direct access from Kuakini Highway to the University of the Nations campus and serves as the primary internal campus roadway providing access to existing campus facilities. The roadway terminates just west of the Aloha Lanai Cafeteria. The unnamed road has speed bumps and is currently two lanes. The posted speed limit is 15 miles per hour (mph).

Kuakini Highway is the primary street that provides access to the project site. Adjacent to the project site, it is a two-lane collector roadway that extends generally from the north end of the town of Kailua-Kona to

Queen Kaahumanu Highway. The posted speed limit is 35 mph. Kuakini Highway is under the jurisdiction of the County of Hawai'i Department of Public Works (DPW). Sidewalks are not provided on either side of Kuakini Highway. No bicycle facilities exist along Kuakini Highway within the study area. Crosswalks are provided at the intersection of Kuakini Highway and Hualalai Road.

Hualalai Road is a two-lane local roadway that is under the jurisdiction of DPW. It runs east-west between Ali'i Drive and Queen Kaahumanu Hwy. The posted speed limit is 25 mph. Sidewalks are provided on both sides of the roadway makai of Kuakini Highway, on the north side of the roadway between Kuakini Highway and the Regency at Hualalai, and on the south side of the roadway just makai of Queen Kaahumanu Hwy. No bicycle facilities exist along Hualalai Road within the study area. On-street parking is not provided.

Queen Kaahumanu Highway is a two-lane highway that is under the jurisdiction of the State of Hawai'i Department of Transportation (HDOT). It is a major component of the Hawai'i Belt Road and runs from Hwy 19 in Kailua-Kona to Hwy 19 in Hilo. The posted speed limit within the study area is 45 mph. Neither sidewalks nor bicycle facilities are provided along the roadway. On-street parking is not provided.

Nani Kailua Drive is a two-lane local roadway that is under the jurisdiction of DPW. It runs east-west and extends from Hualalai Road to just mauka of Pikake Place. The posted speed limit is 25 mph. Neither sidewalks nor bicycle facilities are provided along the roadway. On-street parking is provided on both sides of the roadway.

3.2.2 EXISTING TRANSIT FACILITIES AND SERVICES

The County of Hawai'i Mass Transit Agency provides island-wide commuter and fixed-route service on the Island of Hawai'i, where it served over 800,000 riders in the fiscal year of 2016-2017.¹ Hele-On offers fixed-route transit service in the Hilo and Kona areas Monday through Saturday, and limited commuter services to the South Kohala Resort (SKR) areas seven days a week. Within the project study area, the Pahala-Kailua-Kona-South Kohala Resorts Route provides daily service along Queen Kaahumanu Highway with transit stops both north and south of the project site². Detailed route schedule information, such as operating hours and frequencies, was not available at the time this was written.

3.2.3 EXISTING BICYCLE ACTIVITY

The study area has a low level of bicycle activity. Based on the peak period traffic counts, a range of 0-16 bicyclists were observed at each intersection during the AM peak hour and a range of 0-6 bicyclists were

¹ County of Hawai'i Mass Transit Agency Transit Agency Profile. National Transit Database, 2017. Accessed online at https://www.transit.dot.gov/sites/fta.dot.gov/files/transit_agency_profile_doc/2017/9R03-91080.pdf

² County of Hawai'i Mass Transit Agency. Accessed online at <https://www.hawaiicounty.gov/departments/mass-transit>.

observed at each intersection during the PM peak hour. In general, most bicyclists were traveling mauka-bound along Hualalai Road.

At the intersection of Kuakini Highway and the University of the Nations Driveway, the highest level of morning bicycle activity occurred from 7:15 to 8:15 AM, with a total of two (2) bicyclists traveling through the intersection. In the evening, the highest level of bicycle activity occurred from 4:15 to 5:15 PM with a total of two (2) bicyclists traveling through the intersection.

3.2.4 EXISTING PEDESTRIAN ACTIVITY

The study area generally has a low level of pedestrian activity, except for the intersection of Kuakini Highway and Hualalai Road, where pedestrian activity is high. During the AM peak hour, 46 pedestrians were observed at the intersection of Kuakini Highway and Hualalai Road, and between zero (0) and three (3) pedestrians were observed at the other study intersections. During the PM peak hour, 32 pedestrians were observed at the intersection of Kuakini Highway and Hualalai Road, and between zero (0) and 11 pedestrians were observed at the other study intersections.

At the intersection of Kuakini Highway and the University of the Nations Driveway, the highest levels of pedestrian activity occurred in the morning from 7:15 to 8:15 AM with one (1) pedestrian, and in the evening from 4:15 to 5:15 PM with a total of 11 pedestrians. At the intersection of Kuakini Highway and Hualalai Road: 28 AM and six (6) PM peak hour pedestrian trips crossed the north leg of the intersection, five (5) AM and three (3) PM pedestrian trips crossed the south leg of the intersection, five (5) AM and 22 PM pedestrian trips crossed the mauka leg of the intersection, and a total of eight (8) AM trips and one (1) PM pedestrian trip crossed the makai leg of the intersection.

3.3 EXISTING TRAFFIC VOLUMES/LANE CONFIGURATIONS

Operations of the seven (7) existing study intersections were evaluated for the weekday AM and PM peak hours. Traffic counts were collected during the weekday AM and PM peak periods in October 2019 while university classes were in session. The weekday peak hours of traffic for the study area generally occurred between the hours of 7:15 to 8:15 AM and 4:15 to 5:15 PM.

Existing lane configurations and signal controls were obtained through field observations. **Figure 3-1** presents the existing peak-hour turning movement volumes, corresponding lane configurations, and traffic control devices. Raw traffic count data sheets are provided in **Appendix A**.

3.4 FIELD OBSERVATIONS

As noted, a site visit was conducted by the project team in October 2019. During this visit, the project team observed vehicular traffic conditions (e.g. intersection operations, queuing, and travel speeds) to better understand how the development of Phase 1 of the project could affect future traffic operations. During this visit, the following key observations were made:

- Kuakini Highway/Hualalai Road: Vehicular congestion along Kuakini Highway limits the number of vehicles that can pass through this intersection during the peak hour than would in free-flow conditions. As fewer vehicles pass through the intersection, intersection delay is lower, and LOS is more desirable, than existing field observations indicate.
- Queen Kaahumanu Highway & Nani Kailua: Vehicular congestion along Queen Kaahumanu Highway limits the number of vehicles that can pass through this intersection during the peak hour than would in free-flow conditions. As fewer vehicles pass through the intersection, intersection delay is lower, and LOS is more desirable, than existing field observations indicate.
- Queen Kaahumanu Highway & Lako Street: though not located within the study area, delays at this intersection cause substantive amounts of queuing in the southbound direction along Queen Kaahumanu Highway. This queuing spills back into the intersection of Queen Kaahumanu Highway & Kuakini Highway and can disrupt intersection operations.

3.5 EXISTING INTERSECTION LEVELS OF SERVICE

Peak hour intersection capacity analysis was performed for the study intersections using the methodology described in Section 2.4 and the recently collected peak hour traffic count data. **Table 3-1** summarizes the results of the intersection operations analysis for Existing Conditions. Detailed LOS worksheets are provided in **Appendix B**.

Table 3-1. Existing Peak Hour Intersection Level of Service

Intersection	Traffic Control	Peak Hour	Existing Conditions	
			(sec/veh) ^{1,3}	LOS ^{2,3}
1. Kuakini Hwy & Hualalai Rd	Signalized	AM	17.4	B
		PM	19.2	B
2. Kuakini Hwy & University of the Nations Kona Driveway	SSSC	AM	38.7	E
		PM	33.0	D
3. Hualalai Rd & Nani Kailua Rd	SSSC	AM	10.6	B
		PM	10.5	B
4. Queen Kaahumanu Hwy & Nani Kailua Dr ⁴	Signalized	AM	11.1	B
		PM	11.9	B
5. Hualalai Village Driveway & Hualalai Rd	SSSC	AM	11.3	B
		PM	10.4	B
6. Queen Kaahumanu Hwy & Hualalai Rd ⁴	SSSC	AM	32.9	D
		PM	23.5	C
7. Queen Kaahumanu Hwy & Kuakini Hwy	SSSC	AM	38.4	E
		PM	28.7	D

Source: Fehr & Peers, 2020

Notes:

¹ Whole intersection weighted average stopped delay expressed in seconds per vehicle for signalized intersections. The vehicular delay for the worst movement is reported for the side-street stop-controlled (SSSC) intersection, and traffic along the main roadways typically moves more efficiently.

² LOS calculations performed using the Highway Capacity Manual (HCM) method.

³ Unacceptable seconds of delay per vehicle and LOS highlighted in **bold**.

⁴ Congestion along Queen Kaahumanu Highway limits the number of vehicles that can pass through this intersection. Actual intersection operations operate worse than indicated.

As shown in **Table 3-1**, the following intersections operate at less-than-desirable LOS:

- Kuakini Highway and University of the Nations Kona Driveway: LOS E (AM Peak)
- Queen Kaahumanu Highway and Kuakini Highway: LOS E (AM Peak)

Intersection results are generally consistent with field observations, except for the intersections of Kuakini Highway/Hualalai Road and Nani Kailua/Queen Kaahumanu Highway. These intersections operate worse than what is shown above, primarily because congestion along Kuakini Highway and Queen Kaahumanu Highway limits the number of vehicles that are able to pass through the intersection during the peak hour than would pass in free-flow conditions.



<p>1. Kuakini Hwy/Hualalai Rd</p> <p>163 (313) 382 (632) 131 (179)</p> <p>198 (217) 34 (46) 63 (89)</p> <p>194 (205) 41 (43) 15 (50)</p> <p>19 (28) 606 (568) 50 (89)</p>	<p>2. Kuakini Hwy/Driveway</p> <p>304 (743) 107 (53)</p> <p>54 (88) 10 (33)</p> <p>620 (410) 77 (27)</p>	<p>3. Nani Kalua Rd/Hualalai Rd</p> <p>105 (147) 12 (21)</p> <p>12 (9) 198 (106)</p> <p>72 (123) 73 (98)</p>
<p>4. Queen Kaahumanu Hwy/Nani Kalua Dr</p> <p>70 (68) 671 (964) 69 (126)</p> <p>204 (80) 48 (40) 54 (30)</p> <p>54 (69) 20 (50) 17 (12)</p> <p>24 (31) 952 (866) 32 (38)</p>	<p>5. Driveway/Hualalai Rd</p> <p>3 (2) 0 (0) 0 (3)</p> <p>3 (4) 168 (100) 6 (13)</p> <p>2 (2) 75 (104) 8 (13)</p> <p>41 (13) 0 (0) 5 (4)</p>	<p>6. Queen Kaahumanu Hwy/Hualalai Rd</p> <p>24 (19) 746 (991)</p> <p>33 (14) 50 (105)</p> <p>168 (88) 1,033 (905)</p>
<p>7. Queen Kaahumanu Hwy/Kuakini Hwy</p> <p>74 (52) 690 (829)</p> <p>2 (19)</p> <p>475 (257) 824 (870)</p>		




Figure 3-1
Peak Hour Traffic Volumes and Lane Configurations
Existing (2019) Conditions



4.0 PHASE 1 (2030) NO PROJECT CONDITIONS

To evaluate the potential impacts of traffic generated by the proposed project on the surrounding street system, it was necessary to first develop estimates of future traffic conditions in the area without the project. Future traffic conditions without the project reflect traffic increases due to regional growth and development. This scenario is referred to as Phase 1 or “no project” conditions. The forecasted future traffic volumes were then used as a Phase 1 to identify impacts on the roadway system from the project.

4.1 PHASE 1 (2030) NO PROJECT TRAFFIC ESTIMATES


The following section summarizes growth assumptions used to estimate the amount of traffic that would be added to existing intersection volumes to develop Phase 1 (2030) No Project volume estimates.

4.1.1 AREAWIDE OR AMBIENT TRAFFIC GROWTH

A growth factor was applied to existing traffic volumes to account for future study area growth. This factor was derived using the travel demand forecasting model (TDFM), that was developed for the *Federal-Aid Highways 2035 Transportation Plan for the District of Hawaii (July 2014)* published by HDOT. The TDFM uses land use and socioeconomic data to assign traffic across the planned roadway network for the base and horizon years. Future year (2035) model volumes were compared to base year (2007) model volumes to develop growth factors along study area roadways. A comparison of these daily roadway volumes demonstrated that traffic near the project site would increase annually by 2.5% along Queen Kaahumanu Highway, 1.5% along Kuakini Highway, 2% along Nani Kailua Drive, and 1% along Hualalai Road. Growth rates were compounded over the future-year timeframe (2019 to 2030) and applied to each of the existing intersection turning movement traffic volumes collected in October 2019. Resulting volumes were then rounded to the nearest ten (10) vehicles.

4.1.2 FUTURE TRANSPORTATION IMPROVEMENTS

The project team coordinated with HDOT and the Hawai'i County Department of Public Works (DPW) to identify any transportation improvements within the study area that could affect vehicular traffic operations. Hawai'i County DPW noted that Kuakini Highway is planned to be widened within the study area, but that this improvement likely would not occur until after 2030. No other improvements are planned in the study area by 2030. Therefore, intersection lane configurations and traffic control devices are expected to remain the same in Phase 1 as under Existing Conditions. **Figure 4-1** illustrates the forecasted peak hour traffic volumes for the Phase 1 (2030) No Project Conditions.



LEGEND



Figure 4-1
 Peak Hour Traffic Volumes and Lane Configurations
 Phase 1 (2030) No Project Conditions



4.2 PHASE 1 (2030) NO PROJECT LEVELS OF SERVICE

Peak hour intersection capacity analysis was performed for the study intersections using the volumes generated by the methodology described in Section 4.1. **Table 4-1** summarizes the results of the intersection operations analysis for Existing Conditions. Detailed LOS worksheets are provided in **Appendix B**.

Table 4-1. Phase 1 (2030) No Project Peak Hour Intersection Level of Service

Intersection	Traffic Control	Peak Hour	Phase 1 Conditions	
			(sec/veh) ^{1,3}	LOS ^{2,3}
1. Kuakini Hwy & Hualalai Rd	Signalized	AM	20.8	C
		PM	26.4	C
2. Kuakini Hwy & University of the Nations Kona Driveway	SSSC	AM	54.4	F
		PM	47.4	E
3. Hualalai Rd & Nani Kailua Rd	SSSC	AM	11.5	B
		PM	11.6	B
4. Queen Kaahumanu Hwy & Nani Kailua Dr ⁴	Signalized	AM	23.6	C
		PM	27.1	C
5. Hualalai Village Driveway & Hualalai Rd	SSSC	AM	12.6	B
		PM	11.1	B
6. Queen Kaahumanu Hwy & Hualalai Rd ⁴	SSSC	AM	64.7	F
		PM	36.4	E
7. Queen Kaahumanu Hwy & Kuakini Hwy	SSSC	AM	90.6	F
		PM	51.1	F

Source: Fehr & Peers, 2020

Notes:

¹ Whole intersection weighted average stopped delay expressed in seconds per vehicle for signalized intersections. The vehicular delay for the worst movement is reported for the side-street stop-controlled (SSSC) intersection, and traffic along the main roadways typically moves more efficiently.

² LOS calculations performed using the Highway Capacity Manual (HCM) method.

³ Unacceptable seconds of delay per vehicle and LOS highlighted in **bold**.

⁴ Congestion along Queen Kaahumanu Highway limits the number of vehicles that can pass through this intersection. Actual intersection operations operate worse than indicated.

As shown in **Table 4-1**, the following intersections operate at less-than-desirable LOS:

- Kuakini Highway and University of the Nations Driveway: LOS F in the AM and LOS E in the PM Peak
- Queen Kaahumanu Highway and Hualalai Road : LOS F in the AM and LOS E in the PM Peak
- Queen Kaahumanu Highway and Kuakini Highway: LOS F (AM and PM Peak)



It is important to note that the intersections of Kuakini Highway/Hualalai Road and Nani Kailua/Queen Kaahumanu Highway would likely operate worse than what is shown above, primarily because congestion along Kuakini Highway and Queen Kaahumanu Highway limits the number of vehicles that are able to pass through the intersection during the peak hour than would pass in free-flow conditions.

5.0 PROJECT TRAFFIC ESTIMATES

This section describes the anticipated number of vehicle trips and directionality of those trips that would result from implementation of Phase 1 of the Campus Master Plan. Future traffic added to the roadway system by the project is estimated using a three-step process: (1) project trip generation, (2) trip distribution, and (3) trip assignment. The first step estimates the amount of project-generated traffic that would be added to the roadway network. The second step estimates the direction of travel to and from the project site. The third step assigns trips generated by the project to specific street segments and intersection turning movements. This process is described in more detail in the following sections.

5.1 PROJECT TRIP GENERATION ESTIMATES

Since the existing campus is self-contained, and existing access is limited to one location, it can be assumed that any growth in student and/or faculty/staff levels would directly result in an increase in trips to and from the university campus, and that any trips going in or coming from the University of the Nations Driveway are those generated by the university itself.

To estimate Phase 1 traffic generated by the university, a growth factor was first developed by comparing the total number of students, faculty, and staff projected to be living off campus (487) in Phase 1 to the number of existing students, faculty, and staff living off-campus (870). This growth factor (1.8) was then applied to existing count data taken at the project driveway along Kuakini Highway to derive future peak hour campus-generated vehicle trips. Total peak hour trips were then split into inbound and outbound trips. For this step, the ratio of inbound and outbound trips is assumed to be the same as under existing conditions.

Table 5-1 and **Table 5-2** summarize the forecasted trip generation for the proposed project. As shown, Phase 1 of the Campus Master Plan is estimated to generate up to 215 new AM peak hour trips (154 inbound/62 outbound) and up to 161 PM peak hour trips (64 inbound/97 outbound). These represent vehicle trips that are estimated to be added to the surrounding network with the implementation of Phase 1 as proposed.

Table 5-1. Project Future Growth Factor Estimates

	Existing			Phase 1		
	Total	On campus	Off Campus	Total	On campus	Off Campus
Students	840	90%	10%	1,500	90%	10%
Staff	504	20%	80%	900	20%	80%
Total	1,344	857	487	2,400	1,530	870
Future Growth Factor (Phase 1/Existing)						1.8

Source: Fehr & Peers, 2020

Table 5-2. Project Trip Generation Estimates

	AM			PM		
	Total	In ¹	Out ¹	Total	In ¹	Out ¹
Existing Campus Driveway Trips	269	192	77	201	80	121
Future Growth Factor	1.8			1.8		
Total Future (2030) Campus Trips	484	346	139	362	144	218
Net New Project Trips	215	154	62	161	64	97

Source: Fehr & Peers, 2020

¹ To calculate project In and Out trips, the existing distribution percentages were used.

5.2 PROJECT TRIP DISTRIBUTION AND ASSIGNMENT

The geographic distribution of project trips is primarily dependent on the roadway circulation network and the location of residential, commercial, and other land uses that would either produce trips destined for campus (e.g. faculty/staff housing) or attract trips from campus (e.g. commercial shopping centers).

Project trip distribution was developed using existing travel patterns and anticipated growth areas and assumed no substantive changes to the surrounding roadway circulation network.


The resulting overall trip distribution pattern estimates for project-generated traffic are as follows:

- 65% north of the project site:
 - 59% to/from Kuakini Highway
 - 3% to/from Nani Kailua Drive
 - 3% to/from Hualalai Road
- 35% south of the project site:
 - 30% to/from Queen Kaahumanu Highway
 - 2% to/from Walua Road
 - 1% to/from Nakukui Drive
 - 2% to/from Puapuaanui Street

Figure 5-1 illustrates the project trip distribution pattern in the study area.

Using the estimated trip generation and trip distribution approach discussed above, the traffic forecast to be generated by the proposed project was assigned to the turning movements at each of the study intersections. **Figure 5-2** illustrates the assignment of new project-generated trips for each turning movement at the study intersections.

As noted in Section 2.1, a second access point is planned on the mauka side of campus along Hualalai Village Road. Once this connection is completed, campus students, faculty/staff, and visitors will be able to access campus via the intersection of Hualalai Road and Hualalai Village Road. The provision of a second access point will shift some inbound and outbound traffic to the mauka side of campus. This change in travel patterns was accounted for in the project trip assignment.



N:\Projects\2019_Projects\0323_University of the Nations Kona.MAR\Graphics\GIS\Study\Intersections.mxd

Legend





-  Project Access Points
-  XX% Project Trip Distribution Percentage

Figure 5-1

Phase 1 Project Trip Distribution



<p>1. Kuakini Hwy/Hualalai Rd</p>	<p>2. Kuakini Hwy/Driveway</p>	<p>3. Nani Kalua Rd/Hualalai Rd</p>
<p>4. Queen Kaahumanu Hwy/Nani Kalua Dr</p>	<p>5. Driveway/Hualalai Rd</p>	<p>6. Queen Kaahumanu Hwy/Hualalai Rd</p>
<p>7. Queen Kaahumanu Hwy/Kuakini Hwy</p>		<p>8. Campus Driveway/Hualalai Rd</p>

LEGEND

AM (PM) Peak Hour Traffic Volumes

Lane Configuration

Figure 5-2
Net Project Trip Assignment



6.0 PHASE 1 (2030) PLUS PROJECT CONDITIONS

This section describes the analysis of potential impacts on the roadway system due to projected future increases in traffic, including traffic generated by Phase 1 of the project in 2030. The Phase 1 (2030) Plus Project roadway network is the same network assumed under the Phase 1 No Project scenario. The analysis compares the project levels of service (LOS) at each study intersection with and without the addition of project-generated trips from Phase 1 to determine potential impacts to the transportation network.

6.1 PHASE 1 (2030) PLUS PROJECT INTERSECTION LEVEL OF SERVICE

To forecast the peak hour operating conditions at each study intersection, project trip volumes were added to Phase 1 (2030) No Project traffic volumes to derive Phase 1 (2030) Plus Project volumes.

Figure 6-1 presents the forecasted Phase 1 (2030) Plus Project AM and PM peak hour volumes. The peak hour volumes were used to analyze operations using the LOS methodology described in Section 2.4.

The comparative LOS analysis results for the study intersections under Phase 1 (2030) Without and With Project conditions are presented in **Table 6-1**. Detailed LOS results for intersection movements and corresponding LOS calculation sheets are included in **Appendix B**.

Table 6-1. Phase 1 (2030) With and Without Project Peak Hour Intersection Level of Service

Intersection	Traffic Control	Peak Hour	Phase 1 Conditions		Phase 1 + Project Conditions		Change in Delay ⁴
			(sec/veh) ^{1,3}	LOS ^{2,3}	(sec/veh) ^{1,3}	LOS ^{2,3}	
1. Kuakini Hwy & Hualalai Rd	Signalized	AM	20.8	C	21.1	C	0.3
		PM	26.4	C	26.7	C	0.3
2. Kuakini Hwy & University of the Nations Kona Driveway	SSSC	AM	54.4	F	77.6	F	23.2
		PM	47.4	E	51.2	F	3.8
3. Hualalai Rd & Nani Kailua Rd	SSSC	AM	11.5	B	13.2	B	1.7
		PM	11.6	B	12.4	B	0.8
4. Queen Kaahumanu Hwy & Nani Kailua Dr ⁵	Signalized	AM	23.6	C	24.5	C	0.9
		PM	27.1	C	30.3	C	3.2
5. Hualalai Village Driveway & Hualalai Rd	SSSC	AM	12.6	B	14.2	B	1.6
		PM	11.1	B	11.8	B	0.7
6. Queen Kaahumanu Hwy & Hualalai Rd ⁵	SSSC	AM	64.7	F	84.3	F	19.6
		PM	36.4	E	39.1	E	2.7
7. Queen Kaahumanu Hwy & Kuakini Hwy	SSSC	AM	90.6	F	90.7	F	0.1
		PM	51.1	F	52.4	F	1.3
8. Campus Driveway & Hualalai Rd	SSSC	AM	-	-	10.7	B	-
		PM	-	-	10.3	B	-

Source: Fehr & Peers, 2020

Notes:

¹ Whole intersection weighted average stopped delay expressed in seconds per vehicle for signalized intersections. The vehicular delay for the worst movement is reported for the side-street stop-controlled (SSSC) intersection, and traffic along the main roadways typically moves more efficiently.

² LOS calculations performed using the Highway Capacity Manual (HCM) method.

³ Unacceptable seconds of delay per vehicle and LOS highlighted in **bold**.

⁴ Delay increases of more than five seconds are colored in **red**.

⁵ Congestion along Queen Kaahumanu Highway limits the number of vehicles that can pass through this intersection. Actual intersection operations operate worse than indicated.

The results presented in **Table 6-1** indicate that under Phase 1 (2030) Plus Project conditions, all study intersections are anticipated to continue to operate at LOS D or better during the AM and PM peak hours with the addition of project-generated traffic except for the following unsignalized intersections:

- Kuakini Highway and University of the Nations Kona Driveway (LOS F, AM and PM peaks)
- Queen Kaahumanu Highway and Hualalai Road (LOS F, AM peak; LOS E, PM peak)
- Queen Kaahumanu Highway and Kuakini Highway (LOS F, AM and PM peaks)

The intersections of Kuakini Highway and University of the Nations Kona Driveway (AM and PM peaks) and Queen Kaahumanu Highway and Hualalai Road (AM peak) operate at undesirable LOS, and the addition of project traffic would cause operations at each location to degrade further. However, as noted in Section 2.4.3, one or more signal warrants must also be met at unsignalized intersections for a direct impact to occur. An overview of signal warrant analysis is included in Section 6.2.

It is important to note that the intersections of Kuakini Highway/Hualalai Road and Nani Kailua/Queen Kaahumanu Highway would likely operate worse than what is shown above, primarily because congestion along Kuakini Highway and Queen Kaahumanu Highway limits the number of vehicles that are able to pass through the intersection during the peak hour than would pass in free-flow conditions.



<p>1. Kuakini Hwy/Hualalai Rd</p>	<p>2. Kuakini Hwy/Driveway</p>	<p>3. Nani Kalia Rd/Hualalai Rd</p>
<p>4. Queen Kaahumanu Hwy/Nani Kalia Dr</p>	<p>5. Driveway/Hualalai Rd</p>	<p>6. Queen Kaahumanu Hwy/Hualalai Rd</p>
<p>7. Queen Kaahumanu Hwy/Kuakini Hwy</p>	<p>8. Campus Driveway/Hualalai Rd</p>	




Figure 6-1
Traffic Volumes, Lane Configurations, and Level of Service Phase 1 (2030) Plus Project Conditions



6.2 SIGNAL WARRANT ANALYSIS

As noted in Section 2.4.3, a significant impact would occur at unsignalized intersections if operations change from LOS D or better to LOS E or F, and one or more signal warrants are met.

As noted in Section 6.1, the intersections of Kuakini Highway and the University of the Nations Kona Driveway, Queen Kaahumanu Highway and Hualalai Road, and Queen Kaahumanu Highway and Kuakini Highway intersections operate at an unacceptable LOS (LOS E or F) during both peak hours under Phase 1 Plus Project conditions. To determine whether significant impacts would occur at any of these intersections, four-hour and eight-hour signal warrant analyses were performed. The Queen Kaahumanu Highway and Hualalai Road and Queen Kaahumanu Highway and Kuakini Highway intersections did not meet any of the signal warrants in this scenario. However, the Kuakini Highway and University of the Nations Kona Driveway meets both signal warrants in the Phase 1 Plus Project Scenario. Signal warrant worksheets are included in **Appendix C and Appendix D**.

6.3 POTENTIAL INTERSECTION IMPACTS

Based upon the impact significance criteria and the results of the operations analysis presented, development of Phase 1 of the proposed project is forecast to result in a significant traffic impact at the intersection of Kuakini Highway and the University of the Nations Kona Driveway. However, the impact at this intersection can be mitigated by adding a refuge lane along Kuakini Highway to receive westbound left-turn movements from the University of Nations Kona Driveway. The addition of a refuge lane can likely be accomplished within the existing highway right-of way with re-striping minor pavement modifications, though additional design analysis is needed to determine construction needs for this improvement. With a refuge lane, intersection operations would improve to LOS C in both AM and PM peak hours.

6.4 SPECIAL EVENTS

As noted in Section 2.1, the University of the Nations Kona plans to host four or five higher-attendance community and athletic events throughout the course of the year. Each event would last between one and two weeks. Community events could host up to 3,000 attendees each, whereas athletic events could host up to 500 attendees each. Events of this size and duration would be expected to generate substantial amounts of vehicular traffic traveling to and from the campus if demand was not managed.



It is recommended that the University of the Nations Kona develop a transportation management plan (TMP) – which should include a transportation demand management (TDM) program – to reduce potential temporary impacts to study area intersections during events. Potential TDM strategies include the use of event shuttles/buses, dynamic event parking pricing, remote parking, and incentives to encourage attendees to carpool to and/or from events. In addition to TDM, it is also expected that manual traffic control and focused enforcement will be needed to effectively manage special event traffic and minimize adjacent neighborhood intrusion.

7.0 FUTURE PHASE 2 AND PHASE 3 ASSESSMENT

7.1 Phase 2 “Hot Spot” Assessment

This section provides a high-level overview of intersections where campus development will be close to triggering impacts under Phase 1 of the campus buildout, and identifies locations at which it is reasonable to expect additional project impacts that are likely to occur in Phase 2 (i.e. by 2040). These impacts would be caused by some combination of traffic from anticipated on-campus development and ambient traffic growth.

As noted in Section 6.0, the project is not expected to result in a significant impact at the unsignalized intersections of Queen Kaahumanu Highway/Hualalai Rd and Queen Kaahumanu Highway/Kuakini Highway under Phase 1 conditions. Though the project causes operations for controlled movements at these intersections to change from LOS D or better to LOS E or F, no volume signal warrants are expected to be met. During Phase 2 campus development, two scenarios are possible that would trigger a significant impact at either intersection, including the following:

- **Ambient and Project Traffic Growth:** Ambient growth throughout the study area could result in a signal warrant being met, even without the addition of project traffic from Phase 2. In this scenario, if Phase 2 project traffic causes operations change from LOS D or better to LOS E or F, a significant impact would occur.
- **Project Traffic Growth Only:** If Phase 2 project traffic triggers a signal warrant and causes operations change from LOS D or better to LOS E or F, a significant impact would occur.

The hot spot assessment determined that the intersections below could either have project-related impacts during Phase 2 or may require additional attention for reasons noted.

Queen Kaahumanu Highway/Hualalai Rd and Queen Kaahumanu Highway/Kuakini Highway

Based on a limited amount of traffic expected to use the eastbound left turns at the intersections of Queen Kaahumanu Highway/Hualalai Rd and Queen Kaahumanu Highway/Kuakini Highway, signal warrants are not anticipated to be met. However, HDOT may express concern that Phase 2 campus development will add traffic to the northbound left-turn movements at both intersections, which would contribute to increased delays for the left-turn movement on the minor street approach, therefore exacerbating the need for a traffic signal to enhance traffic operations and safety.

Kuakini Highway and the University of the Nations Kona Driveway

The intersection of Kuakini Highway and the University of the Nations Kona Driveway is expected to operate at LOS C under Phase 1 conditions with the addition of a southbound refuge lane along Kuakini Highway for westbound vehicles that will turn left out of the campus driveway. As part of the hot spot assessment, the project team tested the sensitivity of this intersection to degrading to a less-than-desirable LOS with the addition of Phase 2 project trips. To do so, projected Phase 2 project trips were estimated using the trip generation methodology described in Section 5.1 and informed by campus student, faculty, and staff projections provided by UOFN Kona. Projected Phase 2 project trips were added to the Phase 1 No Project volumes and evaluated using Synchro software. The refuge lane mentioned in Section 6.3 was assumed to be in place, as this would represent mitigated intersection lane configurations under Phase 1.

The sensitivity test found that the intersection would operate at LOS E in the AM peak and LOS C in the PM peak. Further, it was determined that the intersection would also meet both 4-hour and 8-hour signal warrants with the addition of Phase 2 project trips. As such, it is likely that a signal would be required with Phase 2 of the project to enhance intersection operations, site access, and safety.

The UOFN site plan includes an additional access point along Kuakini Highway, south of the University of the National Kona Driveway, which is anticipated to be added during Phase 2. The addition of a second access point along Kuakini Highway would likely relieve some of the congestion at the existing University of the Nations Kona Driveway, although the refuge lane at the existing campus driveway would likely still be required. The County of Hawaii has planned the widening of Kuakini Highway fronting the project site which may impact the type of improvements required at the second access point. If the roadway widening does occur by 2040, the UOFN Kona could be required to contribute funding for select improvements within the widened corridor or if it is determined future on-campus growth would significantly impact intersections along the highway.

Queen Kaahumanu Highway and Nani Kailua Drive

The intersection of Queen Kaahumanu Highway and Nani Kailua Drive is projected to operate at acceptable levels of service under Phase 1 conditions, however it is recognized that the intersection is operating at a worse level than the initial calculated LOS is shown in Section 6.1. This is primarily because of congestion along Queen Kaahumanu Highway that limits the number of vehicles that are able to pass through the intersection during the peak hour. Intersection conditions would likely continue to degrade with the addition of ambient and project-related traffic in Phase 2. If it is determined that Phase 2 of the project would create a significant impact, the project may be required to make a fair-share contribution to funding for anticipated roadway improvements (e.g. widening of Queen Kaahumanu Highway at the intersection including lane and/or signal modifications).

Kuakini Highway Widening

Kuakini Highway could be widened by 2040. The widening of Kuakini Highway would affect the types of improvements which would be required for the secondary access planned for Phase 2. If the roadway widening does occur by 2040, the UOFN Kona could be required to contribute funding for select improvements within the widened corridor or if it is determined future on-campus growth would significantly impact intersections along the highway.

All of the other study intersections are forecast to operate at LOS C or better at the completion of Phase 1, and additional capacity is available to absorb some additional traffic from ambient growth and Phase 2 development expected under the campus master plan. Due to the planned widening of Kuakini Highway, a more detailed analysis may need to be conducted prior to the construction of the Phase 2 access to determine any potential impacts at the study intersections.

7.2 PHASE 3 DEVELOPMENT BEYOND 2040

Beyond 2040, the potential operational issues noted above would continue to persist and operations would likely degrade further without the additional improvements discussed for Phase 1 and Phase 2. Additionally, with the planned regional improvements such as the widening of Queen Kaahumanu Highway and Kuakini Highway, the UOFN Kona could be required to contribute funding or select improvements within the widened corridor if it is determined future on-campus growth would significantly impact intersections along the highway.

8.0 VEHICLE ACCESS, CIRCULATION, AND PARKING

This chapter includes a review of the proposed site plan to evaluate site access and on-site circulation. The site plan was reviewed to determine if adequate vehicle circulation would be provided so that turning vehicles to and from site driveways would not substantially impact operations on adjacent roadways (including the impact of any gated entry points). Additional recommendations are also provided, where applicable. All recommended improvements shall be designed in conformance with policies and principles established and maintained by the County of Hawaii Public Works Department Traffic Division.

8.1 VEHICULAR SITE ACCESS

Direct access to the project site is provided by a driveway located on Kuakini Highway and is controlled by an access gate located approximately 125 feet east of Kuakini Highway. During peak travel periods, or during special events, campus-bound traffic could potentially queue up while waiting to pass through the access gate and spill back onto Kuakini Highway. To reduce the potential for spillback onto Kuakini Highway, it is recommended that the access gate be relocated to a point further east.

As noted previously, the addition of a refuge lane on the south leg of the Kuakini Highway/University of the Nations Kona Driveway intersection will improve egress from campus by providing westbound left turns more space to merge onto Kuakini Highway.

Under Phase 1 conditions, a second access point will be provided off of Hualalai Road via a new unsignalized intersection and driveway leading to the project site. This will provide access to campus from areas mauka to the project site. Due to the relatively low volume of vehicles on this roadway and limited land uses served by it, no vehicular site access issues are expected as a result of implementing Phase 1 development.

8.2 ON-SITE VEHICLE CIRCULATION

Under Phase 1, the proposed site plan includes the extension of two on-site internal campus roadways. First, the on-site, east-west roadway located along the northern site boundary is planned to be extended within the site from its existing eastern terminus to a new driveway on Hualalai Road (as noted above in Section 8.1). In addition, the east-west campus roadway located along the southern edge of the developed campus will be extended from its existing eastern terminus to the existing north-south roadway serving Hualalai Village Apartments. This second campus roadway will effectively be the central spine roadway

within the overall campus master plan area. On the eastern side of campus, this roadway will be limited to on-campus circulation only and will not provide a connection to Hualalai Road via Hualalai Village Road.

To manage travel speeds along both of these roadways, it is recommended that stop signs and other traffic calming devices be included at key points along the roadway. Similar treatments should be employed as appropriate on any other future on-campus roadways built as part of Phases 2 and 3 that will include longer, tangent sections of uninterrupted street segments (i.e., of 600 feet or more).

Two-way, north-south drive aisles would intersect the primary east-west roadways, and they will provide access to existing and planned parking lots. Though the drive aisles and parking lots do not provide direct access to all campus facilities, students, faculty/staff, and visitors will be able to access campus facilities via unrestricted pedestrian and bicycle pathways. More information on these facilities is included below.

8.3 PARKING

As shown on the project site plan, vehicle parking will be provided via on- and off-street parking throughout campus. Insufficient parking was not noted as an issue by the project development team at the time this report was written. As such, it is assumed that the existing parking inventory is sufficient to accommodate the parking demand generated by current levels of campus students, faculty, staff, and visitors. Therefore, it is recommended that parking supply provided in Phase 1 of the project maintain the same ratio of campus students, faculty, staff, and visitors to parking spaces unless adjustments to the supply are needed.

On the current site plan, several on-site parking lots are shown with multiple aisles that connect directly to the future east-west primary campus roadways. This would require drivers looking for available spaces to use the campus roadways to re-circulate through the parking lot. This design will create additional vehicle conflicts and require pedestrians and bicyclists to cross an excessive number of vehicle paths. To enhance safety and to internalize parking movements, it is recommended that all new surface parking lots be limited to one or two access driveways per lot (depending on the number of spaces served), and adequate aisles be provided within each lot to allow for internal vehicle circulation.

9.0 MULTIMODAL ASSESSMENT

This section summarizes potential project impacts from Phase 1 to off- and on-site pedestrian, bicycle, and transit facilities and services, and identifies recommended improvements.

9.1 PEDESTRIAN AND BICYCLE ACCESS AND CIRCULATION

9.1.1 OFF-SITE PEDESTRIAN AND BICYCLE ACCESS

Pedestrians and cyclists can access the university from Kuakini Highway at the existing campus driveway. A pedestrian sidewalk runs along the east side of Kuakini Highway, beginning at the University of the Nations Kona Driveway and terminating approximately 150 feet north of the driveway. A pedestrian crosswalk exists approximately 600 feet north of the University of the Nations Driveway and provides connectivity across Kuakini Highway. On the east side of the project site, a pedestrian sidewalk exists along the south side of Hualalai Road adjacent to the Hualalai Village Apartments. No pedestrian crossings exist along Hualalai Road. Bicycle facilities do not exist along Kuakini Highway or Hualalai Road near the campus.

The following bicycle improvements, identified as high-priority projects in Bike Plan Hawai'i, are proposed within the study area:

- Hualalai Road from Kuakini Highway to Old Mamaloha: Signed Shared Path
- Kuakini Highway from Lako Street to Hualalai Road: Bike Lane
- Queen Kaahumanu Highway from Henry Road to Kuakini Highway: Signed Shared Path

The proposed bike lane along Kuakini Highway will enhance bicycle connectivity to and from the University of the Nations Kona west entrance.

No pedestrian improvements are planned along roadways adjacent to the University of the Nations Kona campus.

Implementation of Phase 1 of the project will not conflict with any existing pedestrian or bicycle facilities and will not preclude the implementation of any planned pedestrian or bicycle facilities within the study area. Phase 1 of the proposed project is expected to generate some bicycle and pedestrian trips to and from the project site. Most of these trips would occur along Kuakini Highway by university students, faculty/staff, or visitors traveling between campus and nearby residential, commercial, and retail land uses. As project-generated pedestrian and bicycle trips are projected to be low, no project impacts are anticipated.

9.1.2 ON-SITE PEDESTRIAN AND BICYCLE CIRCULATION

Direct connections between campus facilities and parking lots would be provided via unrestricted pedestrian and bicycle pathways throughout campus. Pedestrians and bicyclists would travel throughout campus via the shared-use path and crosswalks provided. Bicyclists may also share the on-campus roadway with vehicular traffic. The proposed unrestricted pedestrian and bicycle pathways are expected to provide adequate connectivity between buildings on campus. The project site plan does not identify any pedestrian or bicycle facilities along internal campus roadways.

9.2 TRANSIT ACCESS

As noted in Section 3.2.2, the Pahala-Kailua-Kona-South Kohala Resorts Route provides daily transit service along Queen Kaahumanu Highway. The nearest bus stop is located approximately 1,100 feet south of the intersection of Queen Kaahumanu Highway and Hualalai Road. Based on the site plan provided, transit riders would have to walk at least 2,000 feet to access this bus stop. One potential improvement would be to provide a multi-use connection directly to Hualalai Road to reduce the overall distance transit riders would have to walk or bike to access the campus.

The project is anticipated to generate a low amount of transit riders at the completion of Phase 1. This is primarily due to existing bus stops being located outside of comfortable walking distances from campus, and relatively low service frequencies. As project-related transit ridership is anticipated to be low, no project impacts to transit facilities or services are anticipated, and no modifications to transit stop locations or services would be required.

9.3 RECOMMENDED IMPROVEMENTS

9.3.1 OFF-SITE PEDESTRIAN AND BICYCLE IMPROVEMENTS

Using Federal Highway Administration (FHWA) guidelines and the Fehr & Peers proprietary Crosswalk+ tool, the project team identified potential pedestrian improvements that can be considered at the intersection of Kuakini Highway and the University of the Nations Driveway. The following improvements are proposed at this location:

- Addition of a high-visibility crosswalk, adequate nighttime lighting levels, and crosswalk warning signs on the north and east legs of the intersections.

- The existing striped triangle on the east leg of the intersection should be converted to an elevated area to act as a pedestrian refuge island.
- A Pedestrian Hybrid Beacon (PHB) could also be installed on the north leg of the intersection, however a warrant would need to be conducted to determine whether it would be necessary. If it is not warranted, a Rectangular Rapid-Flashing Beacon (RRFB) could be added.

While the project-generated pedestrian and bicycle volumes are initially expected to be low, the addition of any active travelers along Kuakini Highway may result in people walking or biking along the roadway, which could result in a potential safety issue and a significant multimodal impact. To address this issue and to encourage non-automobile travel and provide greater connectivity to nearby land uses, it is recommended that an elevated sidewalk be installed between the existing sidewalk on the east side of Kuakini Highway from the existing sidewalk's terminus to the existing crosswalk approximately 600 feet north of the University of the Nations Driveway. This ADA-compliant path would be a minimum of four (4) feet wide plus a two-foot buffer between the roadway edge and the path. The buffer could include a guardrail, asphalt berm, or landscaping to help separate pedestrians from vehicle traffic.

9.3.2 ON-SITE PEDESTRIAN AND BICYCLE IMPROVEMENTS

As noted, the project site plan does not include any pedestrian or bicycle facilities along the on-site campus roadways. As such, the following recommendations are recommended:

- A shared-use path should be included on one side of both on-site campus roadways to further enhance pedestrian and bicycle connectivity and safety throughout the campus.
- An enhanced bicycle route (e.g. bike lane or "sharrows") should be included along the makai north-south campus roadway between the northern and central roadways.
- Pedestrian-level lighting is recommended along both the shared-use path and the pedestrian sidewalk.
- Raised crosswalks should be provided at all locations where pedestrian crossings are planned.

It is also recommended that secure bike parking – including bike racks near building entrance(s) – is provided to encourage and support non-motorized travel. Specific locations for bike racks should be determined by the project team in consultation with the University of the Nations Kona staff.

A summary of recommended on-site pedestrian and bicycle improvements are shown on **Figure 9-1**.

LEGEND:

- PHASE I
- PHASE II
- PHASE III



Legend

- Recommended Shared Use Paths
- Potential Bicycle Route Enhancement
- Potential Raised Crosswalk Locations
- Recommended Parking Lot Access Modifications

Figure 9-1

On-site Improvements











APPENDIX A: TRAFFIC COUNT DATA



LOCATION: Kuakini Hwy -- Hualalai Rd
CITY/STATE: Kailua, HI

QC JOB #: 15036003
DATE: Tue, Oct 1 2019

Peak-Hour: 7:15 AM -- 8:15 AM
Peak 15-Min: 7:45 AM -- 8:00 AM











15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				Hualalai Rd (Eastbound)				Hualalai Rd (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
6:00 AM	1	40	2	0	6	26	11	0	21	3	0	0	3	3	9	0	125	
6:15 AM	2	72	3	0	3	24	18	0	20	2	2	0	5	4	16	0	171	
6:30 AM	3	73	4	0	15	34	16	0	19	2	2	0	2	6	21	0	197	
6:45 AM	3	106	9	0	20	50	40	0	38	1	3	0	5	4	19	0	298	791
7:00 AM	4	105	8	0	18	58	18	0	40	2	6	0	2	11	12	0	284	950
7:15 AM	1	133	7	0	14	81	34	0	40	15	4	0	6	5	31	0	371	1150
7:30 AM	6	145	10	0	36	74	39	0	50	8	5	0	14	9	48	0	444	1397
7:45 AM	8	162	17	0	36	108	56	0	49	7	5	0	26	7	56	0	537	1636
8:00 AM	4	166	16	0	45	99	34	0	45	11	1	0	17	13	63	0	514	1866
8:15 AM	9	146	13	0	37	73	41	0	36	9	6	0	12	14	45	0	441	1936
8:30 AM	5	124	13	0	27	66	36	0	58	9	8	0	10	12	56	0	424	1916
8:45 AM	5	124	16	0	35	103	45	0	46	9	5	0	17	21	73	0	499	1878
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	32	648	68	0	144	432	224	0	196	28	20	0	104	28	224	0	2148	
Heavy Trucks	0	8	0	0	0	8	4	0	0	0	0	0	0	0	0	0	20	
Pedestrians		12				32				4				0			48	
Bicycles	0	0	0		0	0	1		1	0	0		0	0	0		2	
Railroad																		
Stopped Buses																		

Comments: Conduct TMC on 10/1 and 2/2019

LOCATION: Kuakini Hwy -- Hualalai Rd
CITY/STATE: Kailua, HI

QC JOB #: 15036004
DATE: Tue, Oct 1 2019

Peak-Hour: 3:15 PM -- 4:15 PM
Peak 15-Min: 4:00 PM -- 4:15 PM











15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				Hualalai Rd (Eastbound)				Hualalai Rd (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
3:00 PM	4	138	20	0	51	133	65	0	40	7	7	0	16	14	44	0	539	
3:15 PM	7	136	19	0	49	164	70	0	55	15	17	0	7	13	56	0	608	
3:30 PM	7	128	22	0	39	151	70	0	54	1	9	0	20	8	49	0	558	
3:45 PM	9	161	26	0	43	147	79	2	45	14	14	0	21	10	48	0	619	2324
4:00 PM	5	143	22	0	45	170	94	1	51	13	10	0	21	12	64	0	651	2436
4:15 PM	5	143	18	0	31	176	79	0	54	16	16	0	21	6	60	0	625	2453
4:30 PM	9	118	12	0	27	161	70	1	45	10	6	0	20	5	45	0	529	2424
4:45 PM	4	121	20	0	32	182	97	0	42	11	17	0	24	18	32	0	600	2405
5:00 PM	8	130	20	0	33	178	84	1	45	16	22	0	17	8	43	0	605	2359
5:15 PM	12	124	19	0	40	170	76	0	49	15	18	0	14	2	39	0	578	2312
5:30 PM	8	85	14	0	29	188	104	1	53	10	12	0	13	2	27	0	546	2329
5:45 PM	7	96	10	0	36	178	83	0	26	11	14	0	20	8	20	0	509	2238
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	20	572	88	0	180	680	376	4	204	52	40	0	84	48	256	0	2604	
Heavy Trucks	0	12	0	0	0	0	4	0	0	0	4	0	0	0	0	0	20	
Pedestrians		0				16				4				0			20	
Bicycles	0	2	0		0	0	0		0	0	0		0	0	0		2	
Railroad																		
Stopped Buses																		

Comments: Conduct TMC on 10/1 and 2/2019

LOCATION: Kuakini Hwy -- YWAM Driveway
CITY/STATE: Kailua, HI

QC JOB #: 15036059
DATE: Tue, Oct 1 2019

Peak-Hour: 7:15 AM -- 8:15 AM
Peak 15-Min: 7:45 AM -- 8:00 AM



15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				YWAM Driveway (Eastbound)				YWAM Driveway (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
12:00 AM	0	6	0	0	0	11	0	0	0	0	0	0	0	0	0	0	17	
12:15 AM	0	4	0	0	0	8	0	0	0	0	0	0	0	0	0	0	12	
12:30 AM	0	1	0	0	0	6	0	0	0	0	0	0	0	0	0	0	7	
12:45 AM	0	5	0	0	0	7	0	0	0	0	0	0	0	0	0	0	12	48
1:00 AM	0	1	0	0	0	7	0	0	0	0	0	0	0	0	0	0	8	39
1:15 AM	0	3	0	0	0	4	0	1	0	0	0	0	0	0	0	0	8	35
1:30 AM	0	2	0	0	0	8	0	0	0	0	0	0	0	0	0	0	10	38
1:45 AM	0	2	0	0	1	2	0	0	0	0	0	0	1	0	0	0	6	32
2:00 AM	0	5	0	0	0	6	0	0	0	0	0	0	0	0	0	0	11	35
2:15 AM	0	2	0	0	0	2	0	0	0	0	0	0	0	0	0	0	4	31
2:30 AM	0	3	0	0	0	11	0	0	0	0	0	0	0	0	0	0	14	35
2:45 AM	0	3	0	0	0	6	0	0	0	0	0	0	0	0	1	0	10	39
3:00 AM	0	1	0	0	0	4	0	0	0	0	0	0	0	0	0	0	5	33
3:15 AM	0	4	0	0	1	1	0	0	0	0	0	0	0	0	0	0	6	35
3:30 AM	0	7	1	0	0	3	0	0	0	0	0	0	0	0	0	0	11	32
3:45 AM	0	5	0	0	0	2	0	0	0	0	0	0	0	0	0	0	7	29
4:00 AM	0	7	0	0	0	4	0	0	0	0	0	0	0	0	0	0	12	36
4:15 AM	0	9	0	0	0	3	0	0	0	0	0	0	0	0	1	0	13	43
4:30 AM	0	7	0	0	0	1	0	0	0	0	0	0	0	0	0	0	8	40
4:45 AM	0	17	0	0	2	4	0	1	0	0	0	0	0	0	0	0	24	57
5:00 AM	0	14	1	0	1	7	0	0	0	0	0	0	0	0	0	0	23	68
5:15 AM	0	18	3	0	7	4	0	0	0	0	0	0	0	0	1	0	33	88
5:30 AM	0	39	5	0	1	8	0	0	0	0	0	0	0	0	1	0	54	134
5:45 AM	0	57	1	0	5	13	0	0	0	0	0	0	0	0	0	0	76	186
6:00 AM	0	39	1	0	2	24	0	0	0	0	0	0	0	0	1	0	67	230
6:15 AM	0	77	3	0	3	22	0	0	0	0	0	0	0	0	2	0	107	304
6:30 AM	0	86	4	0	5	39	0	0	0	0	0	0	1	0	1	0	136	386
6:45 AM	0	104	4	0	5	60	0	0	0	0	0	0	2	0	3	0	178	488
7:00 AM	0	115	2	0	5	56	0	0	0	0	0	0	2	0	11	0	191	612
7:15 AM	0	146	5	0	10	83	0	0	0	0	0	0	0	0	3	0	247	752
7:30 AM	0	148	7	0	16	66	0	0	0	0	0	0	2	0	11	0	250	866
7:45 AM	0	165	48	0	52	81	0	0	0	0	0	0	5	0	12	0	363	1051
8:00 AM	0	161	17	0	29	74	0	0	0	0	0	0	3	0	28	0	312	1172
8:15 AM	0	156	8	0	15	70	0	0	0	0	0	0	5	0	11	1	266	1191
8:30 AM	0	117	3	0	18	107	0	0	0	0	0	0	0	0	6	0	251	1192
8:45 AM	0	101	6	0	18	85	0	0	0	0	0	0	4	0	13	0	227	1056
9:00 AM	0	122	3	1	12	70	0	0	0	0	0	0	6	0	10	0	224	968
9:15 AM	0	96	3	0	10	75	0	0	0	0	0	0	7	0	14	0	205	907

15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				YWAM Driveway (Eastbound)				YWAM Driveway (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
9:30 AM	0	111	3	0	8	100	0	0	0	0	0	0	2	0	8	0	232	888
9:45 AM	0	119	6	0	6	80	0	0	0	0	0	0	2	0	9	0	222	883
10:00 AM	0	101	2	1	15	80	0	0	0	0	0	0	1	0	17	0	217	876
10:15 AM	0	95	0	0	6	96	0	0	0	0	0	0	2	0	9	0	208	879
10:30 AM	0	94	1	0	10	76	0	0	0	0	0	0	1	0	4	0	186	833
10:45 AM	0	125	3	0	10	94	0	1	0	0	0	0	5	0	8	0	246	857
11:00 AM	0	100	3	0	9	100	0	0	0	0	0	0	1	0	9	0	222	862
11:15 AM	0	101	3	0	12	112	0	0	0	0	0	0	0	0	14	0	242	896
11:30 AM	0	102	4	0	12	102	0	0	0	0	0	0	3	0	5	0	228	938
11:45 AM	0	93	10	0	15	105	0	0	0	0	0	0	2	0	7	0	232	924
12:00 PM	0	104	6	0	9	118	0	0	0	0	0	0	5	0	17	0	259	961
12:15 PM	0	97	4	0	8	125	0	0	0	0	0	0	4	0	30	0	268	987
12:30 PM	0	98	5	0	10	109	0	0	0	0	0	0	7	0	21	0	250	1009
12:45 PM	0	112	7	0	18	123	0	0	0	0	0	0	7	0	10	0	277	1054
1:00 PM	0	88	5	0	16	104	0	0	0	0	0	0	3	0	9	0	225	1020
1:15 PM	0	83	7	0	20	98	0	0	0	0	0	0	5	0	22	0	235	987
1:30 PM	0	110	6	0	9	124	0	0	0	0	0	0	5	0	15	0	269	1006
1:45 PM	0	103	5	0	10	122	0	0	0	0	0	0	2	0	17	0	259	988
2:00 PM	0	86	2	0	8	124	0	0	0	0	0	0	5	0	21	0	246	1009
2:15 PM	0	114	2	0	15	125	0	0	0	0	0	0	2	0	16	0	274	1048
2:30 PM	0	112	11	0	16	123	0	0	0	0	0	0	7	0	16	0	285	1064
2:45 PM	0	101	9	0	15	125	0	0	0	0	0	0	6	0	21	0	277	1082
3:00 PM	0	103	5	0	15	134	0	0	0	0	0	0	16	0	33	0	306	1142
3:15 PM	0	119	8	0	15	155	0	0	0	0	0	0	5	0	24	0	326	1194
3:30 PM	0	112	3	0	10	129	0	0	0	0	0	0	3	0	29	0	286	1195
3:45 PM	0	137	5	0	12	162	0	0	0	0	0	0	9	0	24	0	349	1267
4:00 PM	0	127	3	0	12	163	0	0	0	0	0	0	8	0	9	0	322	1283
4:15 PM	0	114	6	0	14	162	0	0	0	0	0	0	4	0	19	0	319	1276
4:30 PM	0	115	6	0	22	148	0	0	0	0	0	0	9	0	19	0	319	1309
4:45 PM	0	116	8	0	20	183	0	0	0	0	0	0	9	0	15	0	351	1311
5:00 PM	0	118	4	0	18	195	0	0	0	0	0	0	9	0	16	0	360	1349
5:15 PM	0	86	5	0	21	183	0	0	0	0	0	0	3	0	12	0	310	1340
5:30 PM	0	73	4	0	15	175	0	0	0	0	0	0	6	0	13	0	286	1307
5:45 PM	0	76	6	0	24	168	0	0	0	0	0	0	5	0	9	0	288	1244
6:00 PM	0	85	3	0	15	164	0	0	0	0	0	0	3	0	10	0	280	1164
6:15 PM	0	76	3	0	9	136	0	0	0	0	0	0	4	0	27	0	255	1109
6:30 PM	0	72	3	0	9	126	0	0	0	0	0	0	7	0	15	0	232	1055
6:45 PM	0	51	1	0	7	105	0	0	0	0	0	0	1	0	8	0	173	940
7:00 PM	0	41	5	0	10	94	0	0	0	0	0	0	3	0	6	0	159	819
7:15 PM	0	36	3	0	8	87	0	0	0	0	0	0	7	0	13	0	154	718
7:30 PM	0	44	3	0	6	74	0	0	0	0	0	0	4	0	12	0	143	629
7:45 PM	0	34	1	0	16	83	0	0	0	0	0	0	2	0	12	0	148	604
8:00 PM	0	34	2	0	9	72	0	0	0	0	0	0	5	0	20	0	142	587
8:15 PM	0	35	2	0	11	84	0	0	0	0	0	0	5	0	16	0	153	586
8:30 PM	0	23	2	0	10	70	0	0	0	0	0	0	4	0	14	0	123	566
8:45 PM	0	22	1	0	5	53	0	0	0	0	0	0	3	0	5	0	89	507
9:00 PM	0	22	1	0	9	39	0	0	0	0	0	0	4	0	4	0	79	444
9:15 PM	0	18	0	0	4	45	0	0	0	0	0	0	4	0	3	0	74	365
9:30 PM	0	19	0	0	4	45	0	0	0	0	0	0	2	0	5	0	75	317
9:45 PM	0	20	3	0	4	33	0	0	0	0	0	0	1	0	2	0	63	291
10:00 PM	0	16	1	0	1	29	0	0	0	0	0	0	1	0	6	0	54	266
10:15 PM	0	7	1	0	5	33	0	0	0	0	0	0	2	0	0	0	48	240
10:30 PM	0	9	0	0	1	25	0	0	0	0	0	0	0	0	1	0	36	201
10:45 PM	0	2	0	0	1	25	0	0	0	0	0	0	0	0	0	0	28	166
11:00 PM	0	7	0	0	0	23	0	0	0	0	0	0	0	0	0	0	30	142
11:15 PM	0	5	0	0	0	8	0	0	0	0	0	0	0	0	1	0	14	108
11:30 PM	0	3	0	0	1	12	0	0	0	0	0	0	0	0	0	0	16	88
11:45 PM	0	8	0	0	2	9	0	0	0	0	0	0	0	0	0	0	19	79










Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	
All Vehicles	0	660	192	0	208	324	0	0	0	0	0	0	20	0	48	0	1452
Heavy Trucks	0	4	0	0	0	16	0	0	0	0	0	0	0	0	0	0	20
Pedestrians	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Railroad																	
Stopped Buses																	

Comments:

LOCATION: Kuakini Hwy -- YWAM Driveway
CITY/STATE: Kailua, HI

QC JOB #: 15036059
DATE: Tue, Oct 1 2019

Peak-Hour: 4:15 PM -- 5:15 PM
Peak 15-Min: 5:00 PM -- 5:15 PM











15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				YWAM Driveway (Eastbound)				YWAM Driveway (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
12:00 AM	0	6	0	0	0	11	0	0	0	0	0	0	0	0	0	0	17	
12:15 AM	0	4	0	0	0	8	0	0	0	0	0	0	0	0	0	0	12	
12:30 AM	0	1	0	0	0	6	0	0	0	0	0	0	0	0	0	0	7	
12:45 AM	0	5	0	0	0	7	0	0	0	0	0	0	0	0	0	0	12	48
1:00 AM	0	1	0	0	0	7	0	0	0	0	0	0	0	0	0	0	8	39
1:15 AM	0	3	0	0	0	4	0	1	0	0	0	0	0	0	0	0	8	35
1:30 AM	0	2	0	0	0	8	0	0	0	0	0	0	0	0	0	0	10	38
1:45 AM	0	2	0	0	1	2	0	0	0	0	0	0	1	0	0	0	6	32
2:00 AM	0	5	0	0	0	6	0	0	0	0	0	0	0	0	0	0	11	35
2:15 AM	0	2	0	0	0	2	0	0	0	0	0	0	0	0	0	0	4	31
2:30 AM	0	3	0	0	0	11	0	0	0	0	0	0	0	0	0	0	14	35
2:45 AM	0	3	0	0	0	6	0	0	0	0	0	0	0	0	1	0	10	39
3:00 AM	0	1	0	0	0	4	0	0	0	0	0	0	0	0	0	0	5	33
3:15 AM	0	4	0	0	1	1	0	0	0	0	0	0	0	0	0	0	6	35
3:30 AM	0	7	1	0	0	3	0	0	0	0	0	0	0	0	0	0	11	32
3:45 AM	0	5	0	0	0	2	0	0	0	0	0	0	0	0	0	0	7	29
4:00 AM	0	7	0	0	0	4	0	0	0	0	0	0	0	0	0	0	12	36
4:15 AM	0	9	0	0	0	3	0	0	0	0	0	0	0	0	1	0	13	43
4:30 AM	0	7	0	0	0	1	0	0	0	0	0	0	0	0	0	0	8	40
4:45 AM	0	17	0	0	2	4	0	1	0	0	0	0	0	0	0	0	24	57
5:00 AM	0	14	1	0	1	7	0	0	0	0	0	0	0	0	0	0	23	68
5:15 AM	0	18	3	0	7	4	0	0	0	0	0	0	0	0	1	0	33	88
5:30 AM	0	39	5	0	1	8	0	0	0	0	0	0	0	0	1	0	54	134
5:45 AM	0	57	1	0	5	13	0	0	0	0	0	0	0	0	0	0	76	186
6:00 AM	0	39	1	0	2	24	0	0	0	0	0	0	0	0	1	0	67	230
6:15 AM	0	77	3	0	3	22	0	0	0	0	0	0	0	0	2	0	107	304
6:30 AM	0	86	4	0	5	39	0	0	0	0	0	0	1	0	1	0	136	386
6:45 AM	0	104	4	0	5	60	0	0	0	0	0	0	2	0	3	0	178	488
7:00 AM	0	115	2	0	5	56	0	0	0	0	0	0	2	0	11	0	191	612
7:15 AM	0	146	5	0	10	83	0	0	0	0	0	0	0	0	3	0	247	752
7:30 AM	0	148	7	0	16	66	0	0	0	0	0	0	2	0	11	0	250	866
7:45 AM	0	165	48	0	52	81	0	0	0	0	0	0	5	0	12	0	363	1051
8:00 AM	0	161	17	0	29	74	0	0	0	0	0	0	3	0	28	0	312	1172
8:15 AM	0	156	8	0	15	70	0	0	0	0	0	0	5	0	11	1	266	1191
8:30 AM	0	117	3	0	18	107	0	0	0	0	0	0	0	0	6	0	251	1192
8:45 AM	0	101	6	0	18	85	0	0	0	0	0	0	4	0	13	0	227	1056
9:00 AM	0	122	3	1	12	70	0	0	0	0	0	0	6	0	10	0	224	968
9:15 AM	0	96	3	0	10	75	0	0	0	0	0	0	7	0	14	0	205	907
9:30 AM	0	111	3	0	8	100	0	0	0	0	0	0	2	0	8	0	232	888

15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				YWAM Driveway (Eastbound)				YWAM Driveway (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
9:45 AM	0	119	6	0	6	80	0	0	0	0	0	0	2	0	9	0	222	883
10:00 AM	0	101	2	1	15	80	0	0	0	0	0	0	1	0	17	0	217	876
10:15 AM	0	95	0	0	6	96	0	0	0	0	0	0	2	0	9	0	208	879
10:30 AM	0	94	1	0	10	76	0	0	0	0	0	0	1	0	4	0	186	833
10:45 AM	0	125	3	0	10	94	0	1	0	0	0	0	5	0	8	0	246	857
11:00 AM	0	100	3	0	9	100	0	0	0	0	0	0	1	0	9	0	222	862
11:15 AM	0	101	3	0	12	112	0	0	0	0	0	0	0	0	14	0	242	896
11:30 AM	0	102	4	0	12	102	0	0	0	0	0	0	3	0	5	0	228	938
11:45 AM	0	93	10	0	15	105	0	0	0	0	0	0	2	0	7	0	232	924
12:00 PM	0	104	6	0	9	118	0	0	0	0	0	0	5	0	17	0	259	961
12:15 PM	0	97	4	0	8	125	0	0	0	0	0	0	4	0	30	0	268	987
12:30 PM	0	98	5	0	10	109	0	0	0	0	0	0	7	0	21	0	250	1009
12:45 PM	0	112	7	0	18	123	0	0	0	0	0	0	7	0	10	0	277	1054
1:00 PM	0	88	5	0	16	104	0	0	0	0	0	0	3	0	9	0	225	1020
1:15 PM	0	83	7	0	20	98	0	0	0	0	0	0	5	0	22	0	235	987
1:30 PM	0	110	6	0	9	124	0	0	0	0	0	0	5	0	15	0	269	1006
1:45 PM	0	103	5	0	10	122	0	0	0	0	0	0	2	0	17	0	259	988
2:00 PM	0	86	2	0	8	124	0	0	0	0	0	0	5	0	21	0	246	1009
2:15 PM	0	114	2	0	15	125	0	0	0	0	0	0	2	0	16	0	274	1048
2:30 PM	0	112	11	0	16	123	0	0	0	0	0	0	7	0	16	0	285	1064
2:45 PM	0	101	9	0	15	125	0	0	0	0	0	0	6	0	21	0	277	1082
3:00 PM	0	103	5	0	15	134	0	0	0	0	0	0	16	0	33	0	306	1142
3:15 PM	0	119	8	0	15	155	0	0	0	0	0	0	5	0	24	0	326	1194
3:30 PM	0	112	3	0	10	129	0	0	0	0	0	0	3	0	29	0	286	1195
3:45 PM	0	137	5	0	12	162	0	0	0	0	0	0	9	0	24	0	349	1267
4:00 PM	0	127	3	0	12	163	0	0	0	0	0	0	8	0	9	0	322	1283
4:15 PM	0	114	6	0	14	162	0	0	0	0	0	0	4	0	19	0	319	1276
4:30 PM	0	115	6	0	22	148	0	0	0	0	0	0	9	0	19	0	319	1309
4:45 PM	0	116	8	0	20	183	0	0	0	0	0	0	9	0	15	0	351	1311
5:00 PM	0	118	4	0	18	195	0	0	0	0	0	0	9	0	16	0	360	1349
5:15 PM	0	86	5	0	21	183	0	0	0	0	0	0	3	0	12	0	310	1340
5:30 PM	0	73	4	0	15	175	0	0	0	0	0	0	6	0	13	0	286	1307
5:45 PM	0	76	6	0	24	168	0	0	0	0	0	0	5	0	9	0	288	1244
6:00 PM	0	85	3	0	15	164	0	0	0	0	0	0	3	0	10	0	280	1164
6:15 PM	0	76	3	0	9	136	0	0	0	0	0	0	4	0	27	0	255	1109
6:30 PM	0	72	3	0	9	126	0	0	0	0	0	0	7	0	15	0	232	1055
6:45 PM	0	51	1	0	7	105	0	0	0	0	0	0	1	0	8	0	173	940
7:00 PM	0	41	5	0	10	94	0	0	0	0	0	0	3	0	6	0	159	819
7:15 PM	0	36	3	0	8	87	0	0	0	0	0	0	7	0	13	0	154	718
7:30 PM	0	44	3	0	6	74	0	0	0	0	0	0	4	0	12	0	143	629
7:45 PM	0	34	1	0	16	83	0	0	0	0	0	0	2	0	12	0	148	604
8:00 PM	0	34	2	0	9	72	0	0	0	0	0	0	5	0	20	0	142	587
8:15 PM	0	35	2	0	11	84	0	0	0	0	0	0	5	0	16	0	153	586
8:30 PM	0	23	2	0	10	70	0	0	0	0	0	0	4	0	14	0	123	566
8:45 PM	0	22	1	0	5	53	0	0	0	0	0	0	3	0	5	0	89	507
9:00 PM	0	22	1	0	9	39	0	0	0	0	0	0	4	0	4	0	79	444
9:15 PM	0	18	0	0	4	45	0	0	0	0	0	0	4	0	3	0	74	365
9:30 PM	0	19	0	0	4	45	0	0	0	0	0	0	2	0	5	0	75	317
9:45 PM	0	20	3	0	4	33	0	0	0	0	0	0	1	0	2	0	63	291
10:00 PM	0	16	1	0	1	29	0	0	0	0	0	0	1	0	6	0	54	266
10:15 PM	0	7	1	0	5	33	0	0	0	0	0	0	2	0	0	0	48	240
10:30 PM	0	9	0	0	1	25	0	0	0	0	0	0	0	0	1	0	36	201
10:45 PM	0	2	0	0	1	25	0	0	0	0	0	0	0	0	0	0	28	166
11:00 PM	0	7	0	0	0	23	0	0	0	0	0	0	0	0	0	0	30	142
11:15 PM	0	5	0	0	0	8	0	0	0	0	0	0	0	0	1	0	14	108
11:30 PM	0	3	0	0	1	12	0	0	0	0	0	0	0	0	0	0	16	88
11:45 PM	0	8	0	0	2	9	0	0	0	0	0	0	0	0	0	0	19	79
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	0	472	16	0	72	780	0	0	0	0	0	0	36	0	64	0	1440	
Heavy Trucks	0	4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4	
Pedestrians	0	0	0	0	0	0	0	0	0	0	0	0	0	4	0	0	4	
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Railroad																		
Stopped Buses																		
<i>Comments:</i>																		

LOCATION: Kuakini Hwy -- YWAM Driveway
CITY/STATE: Kailua, HI

QC JOB #: 15036057
DATE: Wed, Oct 2 2019

Peak-Hour: 7:15 AM -- 8:15 AM
Peak 15-Min: 7:45 AM -- 8:00 AM



15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				YWAM Driveway (Eastbound)				YWAM Driveway (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
12:00 AM	0	4	0	0	0	14	0	1	0	0	0	0	0	0	0	0	19	
12:15 AM	0	8	0	0	1	11	0	0	0	0	0	0	0	0	1	0	21	
12:30 AM	0	1	0	0	0	7	0	0	0	0	0	0	0	0	0	0	8	
12:45 AM	0	3	0	0	0	6	0	0	0	0	0	0	0	0	0	0	9	57
1:00 AM	0	0	0	0	0	6	0	0	0	0	0	0	0	0	0	0	6	44
1:15 AM	0	3	0	0	0	4	0	0	0	0	0	0	0	0	0	0	7	30
1:30 AM	0	4	0	0	0	6	0	0	0	0	0	0	0	0	0	0	10	32
1:45 AM	0	6	0	0	0	6	0	1	0	0	0	0	0	0	0	0	13	36
2:00 AM	0	6	1	0	1	9	0	0	0	0	0	0	1	0	0	0	18	48
2:15 AM	0	3	0	0	0	3	0	0	0	0	0	0	0	1	0	0	7	48
2:30 AM	0	3	0	0	0	3	0	0	0	0	0	0	0	0	0	0	6	44
2:45 AM	0	0	0	0	0	5	0	0	0	0	0	0	0	0	0	0	5	36
3:00 AM	0	3	0	0	0	1	0	0	0	0	0	0	0	0	0	0	4	22
3:15 AM	0	8	1	0	0	1	0	1	0	0	0	0	0	0	0	0	11	26
3:30 AM	0	3	0	0	0	1	0	0	0	0	0	0	0	0	0	0	4	24
3:45 AM	0	8	0	0	0	4	0	1	0	0	0	0	0	0	0	0	13	32
4:00 AM	0	6	0	0	0	3	0	0	0	0	0	0	0	0	0	0	9	37
4:15 AM	0	8	0	0	2	1	0	0	0	0	0	0	0	0	0	0	11	37
4:30 AM	0	15	0	0	0	3	0	0	0	0	0	0	0	0	0	0	18	51
4:45 AM	0	14	3	0	1	6	0	0	0	0	0	0	0	0	0	0	24	62
5:00 AM	0	13	1	0	0	1	0	0	0	0	0	0	0	0	0	0	15	68
5:15 AM	0	24	2	0	1	11	0	0	0	0	0	0	0	1	0	0	39	96
5:30 AM	0	33	1	0	4	5	0	0	0	0	0	0	0	3	0	0	46	124
5:45 AM	0	70	5	0	5	15	0	0	0	0	0	0	0	2	0	0	97	197
6:00 AM	0	53	0	0	2	20	0	0	0	0	0	0	0	0	0	0	75	257
6:15 AM	0	71	0	0	13	26	0	0	0	0	0	0	1	0	2	0	113	331
6:30 AM	0	89	2	0	4	43	0	0	0	0	0	0	3	0	3	0	144	429
6:45 AM	0	103	4	0	4	46	0	0	0	0	0	0	1	0	5	0	163	495
7:00 AM	0	106	3	0	6	69	0	0	0	0	0	0	2	0	11	0	197	617
7:15 AM	0	132	2	0	13	75	0	0	0	0	0	0	0	0	6	0	228	732
7:30 AM	0	143	9	0	24	64	0	0	0	0	0	0	3	0	7	0	250	838
7:45 AM	0	173	34	0	46	79	0	0	0	0	0	0	0	0	15	0	347	1022
8:00 AM	0	172	28	0	28	71	0	0	0	0	0	0	6	0	17	0	322	1147
8:15 AM	0	116	9	0	18	79	0	0	0	0	0	0	9	0	3	0	234	1153
8:30 AM	0	124	1	0	17	80	0	0	0	0	0	0	8	0	2	0	232	1135
8:45 AM	0	134	7	0	17	81	0	0	0	0	0	0	10	0	5	0	254	1042
9:00 AM	0	126	11	0	7	70	0	0	0	0	0	0	13	0	3	0	230	950
9:15 AM	0	115	5	1	12	81	0	0	0	0	0	0	12	0	2	2	230	946









15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				YWAM Driveway (Eastbound)				YWAM Driveway (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
9:30 AM	0	94	2	0	10	76	0	0	0	0	0	0	12	0	0	0	194	908
9:45 AM	0	127	1	0	6	88	0	0	0	0	0	0	15	0	2	0	234	888
10:00 AM	0	107	6	0	15	88	0	0	0	0	0	0	10	0	1	0	232	890
10:15 AM	0	111	2	0	5	99	0	0	0	0	0	0	6	0	2	0	225	885
10:30 AM	0	117	2	0	4	89	0	2	0	0	0	0	10	0	2	0	226	917
10:45 AM	0	107	3	0	3	97	0	0	0	0	0	0	3	0	0	2	215	898
11:00 AM	0	100	1	0	10	117	0	0	0	0	0	0	5	0	1	0	234	900
11:15 AM	0	88	2	0	12	98	0	0	0	0	0	0	6	0	0	0	206	881
11:30 AM	0	92	2	0	17	94	0	1	0	0	0	0	7	0	4	0	217	872
11:45 AM	0	94	4	0	18	71	0	0	0	0	0	0	15	0	4	0	206	863
12:00 PM	0	77	3	0	15	109	0	0	0	0	0	0	7	0	22	0	233	862
12:15 PM	0	94	8	0	12	132	0	0	0	0	0	0	6	0	19	0	271	927
12:30 PM	0	94	6	0	12	111	0	0	0	0	0	0	13	0	14	0	250	960
12:45 PM	0	104	4	0	16	101	0	0	0	0	0	0	2	0	15	0	242	996
1:00 PM	0	110	2	0	20	116	0	0	0	0	0	0	1	0	21	0	270	1033
1:15 PM	0	124	5	0	20	109	0	0	0	0	0	0	5	0	13	0	276	1038
1:30 PM	0	103	5	0	17	127	0	0	0	0	0	0	1	0	22	0	275	1063
1:45 PM	0	123	3	0	8	113	0	0	0	0	0	0	4	0	9	0	260	1081
2:00 PM	0	102	4	0	12	119	0	0	0	0	0	0	2	0	19	0	258	1069
2:15 PM	0	76	3	0	12	141	0	0	0	0	0	0	1	0	13	0	246	1039
2:30 PM	0	104	4	0	19	119	0	0	0	0	0	0	1	0	9	0	256	1020
2:45 PM	0	101	12	0	31	141	0	0	0	0	0	0	6	0	11	0	302	1062
3:00 PM	0	74	5	1	12	143	0	0	0	0	0	0	8	0	14	0	257	1061
3:15 PM	0	119	1	0	12	153	0	0	0	0	0	0	9	0	12	0	306	1121
3:30 PM	0	103	2	0	7	141	0	0	0	0	0	0	7	0	11	0	271	1136
3:45 PM	0	107	3	0	15	165	0	0	0	0	0	0	4	0	15	0	309	1143
4:00 PM	0	115	3	0	9	154	0	0	0	0	0	0	8	0	15	0	304	1190
4:15 PM	0	118	4	0	15	176	0	0	0	0	0	0	2	0	15	0	330	1214
4:30 PM	0	131	5	0	6	180	0	0	0	0	0	0	10	0	17	0	349	1292
4:45 PM	0	95	6	0	13	193	0	0	0	0	0	0	5	0	15	0	327	1310
5:00 PM	0	89	7	0	19	181	0	0	0	0	0	0	10	0	33	0	339	1345
5:15 PM	0	95	9	0	15	189	0	0	0	0	0	0	8	0	23	0	339	1354
5:30 PM	0	79	5	0	16	161	0	0	0	0	0	0	6	0	16	0	283	1288
5:45 PM	0	79	7	0	13	165	0	0	0	0	0	0	6	0	15	0	285	1246
6:00 PM	0	83	1	0	10	156	0	0	0	0	0	0	2	0	14	0	266	1173
6:15 PM	0	79	12	0	13	156	0	0	0	0	0	0	3	0	6	0	269	1103
6:30 PM	0	60	5	0	12	101	0	0	0	0	0	0	7	0	12	0	197	1017
6:45 PM	0	47	4	0	7	101	0	0	0	0	0	0	3	0	14	0	176	908
7:00 PM	0	52	1	0	15	89	0	0	0	0	0	0	4	0	10	0	171	813
7:15 PM	0	50	2	0	9	79	0	0	0	0	0	0	4	0	6	0	150	694
7:30 PM	0	40	1	0	12	82	0	0	0	0	0	0	9	0	13	0	157	654
7:45 PM	0	36	2	0	7	83	0	0	0	0	0	0	5	0	20	0	153	631
8:00 PM	0	34	3	0	7	80	0	0	0	0	0	0	3	0	14	0	141	601
8:15 PM	0	32	7	0	9	76	0	0	0	0	0	0	5	0	6	0	135	586
8:30 PM	0	30	1	0	4	71	0	0	0	0	0	0	3	0	4	0	113	542
8:45 PM	0	33	4	0	5	52	0	0	0	0	0	0	0	0	5	0	99	488
9:00 PM	0	18	4	0	5	41	0	0	0	0	0	0	4	0	6	0	78	425
9:15 PM	0	23	1	0	7	58	0	0	0	0	0	0	2	0	3	0	94	384
9:30 PM	0	25	1	0	9	51	0	0	0	0	0	0	5	0	4	0	95	366
9:45 PM	0	15	2	0	5	34	0	0	0	0	0	0	3	0	2	0	61	328
10:00 PM	0	20	1	0	2	37	0	0	0	0	0	0	1	0	1	0	62	312
10:15 PM	0	14	1	0	1	32	0	0	0	0	0	0	4	0	2	0	54	272
10:30 PM	0	13	0	0	3	36	0	0	0	0	0	0	0	0	1	0	53	230
10:45 PM	0	7	0	0	0	22	0	0	0	0	0	0	0	0	2	0	31	200
11:00 PM	0	13	0	0	0	22	0	0	0	0	0	0	0	0	1	0	36	174
11:15 PM	0	6	0	0	0	17	0	0	0	0	0	0	1	0	0	0	24	144
11:30 PM	0	8	0	0	0	18	0	0	0	0	0	0	0	0	0	0	26	117
11:45 PM	0	10	0	0	0	8	0	0	0	0	0	0	0	0	0	0	18	104
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	0	692	136	0	184	316	0	0	0	0	0	0	0	0	60	0	1388	
Heavy Trucks	0	8	0	0	0	4	0	0	0	0	0	0	0	0	4	0	16	
Pedestrians	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Railroad																		
Stopped Buses																		

Comments:

LOCATION: Kuakini Hwy -- YWAM Driveway
CITY/STATE: Kailua, HI

QC JOB #: 15036057
DATE: Wed, Oct 2 2019

Peak-Hour: 4:30 PM -- 5:30 PM
Peak 15-Min: 4:30 PM -- 4:45 PM



15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				YWAM Driveway (Eastbound)				YWAM Driveway (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
12:00 AM	0	4	0	0	0	14	0	1	0	0	0	0	0	0	0	0	19	
12:15 AM	0	8	0	0	1	11	0	0	0	0	0	0	0	0	1	0	21	
12:30 AM	0	1	0	0	0	7	0	0	0	0	0	0	0	0	0	0	8	
12:45 AM	0	3	0	0	0	6	0	0	0	0	0	0	0	0	0	0	9	57
1:00 AM	0	0	0	0	0	6	0	0	0	0	0	0	0	0	0	0	6	44
1:15 AM	0	3	0	0	0	4	0	0	0	0	0	0	0	0	0	0	7	30
1:30 AM	0	4	0	0	0	6	0	0	0	0	0	0	0	0	0	0	10	32
1:45 AM	0	6	0	0	0	6	0	1	0	0	0	0	0	0	0	0	13	36
2:00 AM	0	6	1	0	1	9	0	0	0	0	0	0	1	0	0	0	18	48
2:15 AM	0	3	0	0	0	3	0	0	0	0	0	0	0	1	0	0	7	48
2:30 AM	0	3	0	0	0	3	0	0	0	0	0	0	0	0	0	0	6	44
2:45 AM	0	0	0	0	0	5	0	0	0	0	0	0	0	0	0	0	5	36
3:00 AM	0	3	0	0	0	1	0	0	0	0	0	0	0	0	0	0	4	22
3:15 AM	0	8	1	0	0	1	0	1	0	0	0	0	0	0	0	0	11	26
3:30 AM	0	3	0	0	0	1	0	0	0	0	0	0	0	0	0	0	4	24
3:45 AM	0	8	0	0	0	4	0	1	0	0	0	0	0	0	0	0	13	32
4:00 AM	0	6	0	0	0	3	0	0	0	0	0	0	0	0	0	0	9	37
4:15 AM	0	8	0	0	2	1	0	0	0	0	0	0	0	0	0	0	11	37
4:30 AM	0	15	0	0	0	3	0	0	0	0	0	0	0	0	0	0	18	51
4:45 AM	0	14	3	0	1	6	0	0	0	0	0	0	0	0	0	0	24	62
5:00 AM	0	13	1	0	0	1	0	0	0	0	0	0	0	0	0	0	15	68
5:15 AM	0	24	2	0	1	11	0	0	0	0	0	0	1	0	0	39	96	
5:30 AM	0	33	1	0	4	5	0	0	0	0	0	0	3	0	0	46	124	
5:45 AM	0	70	5	0	5	15	0	0	0	0	0	0	2	0	0	97	197	
6:00 AM	0	53	0	0	2	20	0	0	0	0	0	0	0	0	0	75	257	
6:15 AM	0	71	0	0	13	26	0	0	0	0	0	1	0	2	0	113	331	
6:30 AM	0	89	2	0	4	43	0	0	0	0	0	3	0	3	0	144	429	
6:45 AM	0	103	4	0	4	46	0	0	0	0	0	1	0	5	0	163	495	
7:00 AM	0	106	3	0	6	69	0	0	0	0	0	2	0	11	0	197	617	
7:15 AM	0	132	2	0	13	75	0	0	0	0	0	0	0	6	0	228	732	
7:30 AM	0	143	9	0	24	64	0	0	0	0	0	3	0	7	0	250	838	
7:45 AM	0	173	34	0	46	79	0	0	0	0	0	0	0	15	0	347	1022	
8:00 AM	0	172	28	0	28	71	0	0	0	0	0	6	0	17	0	322	1147	
8:15 AM	0	116	9	0	18	79	0	0	0	0	0	9	0	3	0	234	1153	
8:30 AM	0	124	1	0	17	80	0	0	0	0	0	8	0	2	0	232	1135	
8:45 AM	0	134	7	0	17	81	0	0	0	0	0	10	0	5	0	254	1042	
9:00 AM	0	126	11	0	7	70	0	0	0	0	0	13	0	3	0	230	950	
9:15 AM	0	115	5	1	12	81	0	0	0	0	0	12	0	2	2	230	946	
9:30 AM	0	94	2	0	10	76	0	0	0	0	0	12	0	0	0	194	908	









15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				YWAM Driveway (Eastbound)				YWAM Driveway (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
9:45 AM	0	127	1	0	6	88	0	0	0	0	0	0	10	0	2	0	234	888
10:00 AM	0	107	6	0	15	88	0	0	0	0	0	0	15	0	1	0	232	890
10:15 AM	0	111	2	0	5	99	0	0	0	0	0	0	6	0	2	0	225	885
10:30 AM	0	117	2	0	4	89	0	2	0	0	0	0	10	0	2	0	226	917
10:45 AM	0	107	3	0	3	97	0	0	0	0	0	0	3	0	0	2	215	898
11:00 AM	0	100	1	0	10	117	0	0	0	0	0	0	5	0	1	0	234	900
11:15 AM	0	88	2	0	12	98	0	0	0	0	0	0	6	0	0	0	206	881
11:30 AM	0	92	2	0	17	94	0	1	0	0	0	0	7	0	4	0	217	872
11:45 AM	0	94	4	0	18	71	0	0	0	0	0	0	15	0	4	0	206	863
12:00 PM	0	77	3	0	15	109	0	0	0	0	0	0	7	0	22	0	233	862
12:15 PM	0	94	8	0	12	132	0	0	0	0	0	0	6	0	19	0	271	927
12:30 PM	0	94	6	0	12	111	0	0	0	0	0	0	13	0	14	0	250	960
12:45 PM	0	104	4	0	16	101	0	0	0	0	0	0	2	0	15	0	242	996
1:00 PM	0	110	2	0	20	116	0	0	0	0	0	0	1	0	21	0	270	1033
1:15 PM	0	124	5	0	20	109	0	0	0	0	0	0	5	0	13	0	276	1038
1:30 PM	0	103	5	0	17	127	0	0	0	0	0	0	1	0	22	0	275	1063
1:45 PM	0	123	3	0	8	113	0	0	0	0	0	0	4	0	9	0	260	1081
2:00 PM	0	102	4	0	12	119	0	0	0	0	0	0	2	0	19	0	258	1069
2:15 PM	0	76	3	0	12	141	0	0	0	0	0	0	1	0	13	0	246	1039
2:30 PM	0	104	4	0	19	119	0	0	0	0	0	0	1	0	9	0	256	1020
2:45 PM	0	101	12	0	31	141	0	0	0	0	0	0	6	0	11	0	302	1062
3:00 PM	0	74	5	1	12	143	0	0	0	0	0	0	8	0	14	0	257	1061
3:15 PM	0	119	1	0	12	153	0	0	0	0	0	0	9	0	12	0	306	1121
3:30 PM	0	103	2	0	7	141	0	0	0	0	0	0	7	0	11	0	271	1136
3:45 PM	0	107	3	0	15	165	0	0	0	0	0	0	4	0	15	0	309	1143
4:00 PM	0	115	3	0	9	154	0	0	0	0	0	0	8	0	15	0	304	1190
4:15 PM	0	118	4	0	15	176	0	0	0	0	0	0	2	0	15	0	330	1214
4:30 PM	0	131	5	0	6	180	0	0	0	0	0	0	10	0	17	0	349	1292
4:45 PM	0	95	6	0	13	193	0	0	0	0	0	0	5	0	15	0	327	1310
5:00 PM	0	89	7	0	19	181	0	0	0	0	0	0	10	0	33	0	339	1345
5:15 PM	0	95	9	0	15	189	0	0	0	0	0	0	8	0	23	0	339	1354
5:30 PM	0	79	5	0	16	161	0	0	0	0	0	0	6	0	16	0	283	1288
5:45 PM	0	79	7	0	13	165	0	0	0	0	0	0	6	0	15	0	285	1246
6:00 PM	0	83	1	0	10	156	0	0	0	0	0	0	2	0	14	0	266	1173
6:15 PM	0	79	12	0	13	156	0	0	0	0	0	0	3	0	6	0	269	1103
6:30 PM	0	60	5	0	12	101	0	0	0	0	0	0	7	0	12	0	197	1017
6:45 PM	0	47	4	0	7	101	0	0	0	0	0	0	3	0	14	0	176	908
7:00 PM	0	52	1	0	15	89	0	0	0	0	0	0	4	0	10	0	171	813
7:15 PM	0	50	2	0	9	79	0	0	0	0	0	0	4	0	6	0	150	694
7:30 PM	0	40	1	0	12	82	0	0	0	0	0	0	9	0	13	0	157	654
7:45 PM	0	36	2	0	7	83	0	0	0	0	0	0	5	0	20	0	153	631
8:00 PM	0	34	3	0	7	80	0	0	0	0	0	0	3	0	14	0	141	601
8:15 PM	0	32	7	0	9	76	0	0	0	0	0	0	5	0	6	0	135	586
8:30 PM	0	30	1	0	4	71	0	0	0	0	0	0	3	0	4	0	113	542
8:45 PM	0	33	4	0	5	52	0	0	0	0	0	0	0	0	5	0	99	488
9:00 PM	0	18	4	0	5	41	0	0	0	0	0	0	4	0	6	0	78	425
9:15 PM	0	23	1	0	7	58	0	0	0	0	0	0	2	0	3	0	94	384
9:30 PM	0	25	1	0	9	51	0	0	0	0	0	0	5	0	4	0	95	366
9:45 PM	0	15	2	0	5	34	0	0	0	0	0	0	3	0	2	0	61	328
10:00 PM	0	20	1	0	2	37	0	0	0	0	0	0	1	0	1	0	62	312
10:15 PM	0	14	1	0	1	32	0	0	0	0	0	0	4	0	2	0	54	272
10:30 PM	0	13	0	0	3	36	0	0	0	0	0	0	0	0	1	0	53	230
10:45 PM	0	7	0	0	0	22	0	0	0	0	0	0	0	0	2	0	31	200
11:00 PM	0	13	0	0	0	22	0	0	0	0	0	0	0	0	1	0	36	174
11:15 PM	0	6	0	0	0	17	0	0	0	0	0	0	1	0	0	0	24	144
11:30 PM	0	8	0	0	0	18	0	0	0	0	0	0	0	0	0	0	26	117
11:45 PM	0	10	0	0	0	8	0	0	0	0	0	0	0	0	0	0	18	104
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	0	524	20	0	24	720	0	0	0	0	0	0	40	0	68	0	1396	
Heavy Trucks	0	4	0	0	0	12	0	0	0	0	0	0	0	0	4	0	20	
Pedestrians	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Bicycles	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	
Railroad																		
Stopped Buses																		

Comments:

LOCATION: Kuakini Hwy -- YWAM Driveway
CITY/STATE: Kailua, HI

QC JOB #: 15036058
DATE: Thu, Oct 3 2019

Peak-Hour: 7:15 AM -- 8:15 AM
Peak 15-Min: 7:45 AM -- 8:00 AM











15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				YWAM Driveway (Eastbound)				YWAM Driveway (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
12:00 AM	0	6	0	0	0	18	0	0	0	0	0	0	0	0	0	0	24	
12:15 AM	0	7	1	0	0	8	0	0	0	0	0	0	0	0	0	0	16	
12:30 AM	0	2	0	0	0	9	0	0	0	0	0	0	0	0	0	0	11	
12:45 AM	0	1	0	0	0	6	0	0	0	0	0	0	0	0	0	0	7	58
1:00 AM	0	2	0	0	0	3	0	0	0	0	0	0	0	0	0	0	5	39
1:15 AM	0	2	0	0	1	7	0	0	0	0	0	0	0	0	0	0	10	33
1:30 AM	0	2	0	0	0	5	0	0	0	0	0	0	0	0	0	0	7	29
1:45 AM	0	5	0	0	0	3	0	0	0	0	0	0	0	0	0	0	8	30
2:00 AM	0	1	0	0	0	4	0	0	0	0	0	0	0	0	0	0	5	30
2:15 AM	0	2	0	0	0	4	0	0	0	0	0	0	0	0	0	0	6	26
2:30 AM	0	1	1	0	0	4	0	0	0	0	0	0	0	1	0	0	7	26
2:45 AM	0	2	0	0	0	5	0	0	0	0	0	0	0	0	0	0	7	25
3:00 AM	0	4	0	0	0	2	0	0	0	0	0	0	0	1	0	0	7	27
3:15 AM	0	10	1	0	1	1	0	0	0	0	0	0	0	1	0	0	14	35
3:30 AM	0	3	0	0	1	0	0	0	0	0	0	0	0	0	0	0	4	32
3:45 AM	0	3	0	0	0	3	0	0	0	0	0	0	0	0	0	0	6	31
4:00 AM	0	5	0	0	0	3	0	0	0	0	0	0	0	0	0	0	8	32
4:15 AM	0	6	0	0	0	2	0	0	0	0	0	0	0	0	0	0	8	26
4:30 AM	0	12	0	0	0	4	0	0	0	0	0	0	0	0	0	0	16	38
4:45 AM	0	18	1	0	3	5	0	0	0	0	0	0	0	0	0	0	27	59
5:00 AM	0	15	1	0	1	5	0	0	0	0	0	0	0	1	0	0	23	74
5:15 AM	0	18	0	0	0	8	0	0	0	0	0	0	0	0	0	0	26	92
5:30 AM	0	31	1	0	1	8	0	0	0	0	0	0	0	0	0	0	41	117
5:45 AM	0	67	3	0	4	15	0	0	0	0	0	0	0	0	0	0	89	179
6:00 AM	0	43	0	0	1	19	0	0	0	0	0	1	0	1	0	0	65	221
6:15 AM	0	63	4	0	8	23	0	0	0	0	0	0	0	4	0	0	102	297
6:30 AM	0	89	7	0	3	41	0	0	0	0	0	0	0	2	0	0	142	398
6:45 AM	0	94	2	0	8	58	0	0	0	0	0	0	0	6	0	0	168	477
7:00 AM	0	107	3	0	8	68	0	0	0	0	0	2	0	10	0	0	198	610
7:15 AM	0	127	5	0	8	82	0	0	0	0	0	0	0	7	0	0	229	737
7:30 AM	0	148	12	0	28	67	0	0	0	0	0	1	0	5	0	0	261	856
7:45 AM	0	182	43	0	50	84	0	1	0	0	0	2	0	19	0	0	381	1069
8:00 AM	0	168	13	0	20	68	0	0	0	0	0	10	0	20	0	0	299	1170
8:15 AM	0	126	8	0	15	71	0	0	0	0	0	4	0	11	0	0	235	1176
8:30 AM	0	143	4	0	15	70	0	0	0	0	0	1	0	10	0	0	243	1158
8:45 AM	0	124	11	0	19	96	0	1	0	0	0	3	0	5	0	0	259	1036
9:00 AM	0	108	3	0	11	80	0	0	0	0	0	6	0	29	0	0	237	974
9:15 AM	0	105	6	0	6	84	0	1	0	0	0	4	0	12	0	0	218	957

15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				YWAM Driveway (Eastbound)				YWAM Driveway (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
9:30 AM	0	118	4	0	14	86	0	0	0	0	0	0	2	0	9	0	233	947
9:45 AM	0	91	2	0	4	92	0	1	0	0	0	0	2	0	7	0	199	887
10:00 AM	0	111	3	0	4	98	0	0	0	0	0	0	2	0	8	0	226	876
10:15 AM	0	113	6	0	12	86	0	0	0	0	0	0	3	0	12	0	232	890
10:30 AM	0	104	0	0	4	96	0	0	0	0	0	0	0	0	10	0	214	871
10:45 AM	0	118	2	0	12	93	0	1	0	0	0	0	4	0	10	0	240	912
11:00 AM	0	107	6	0	6	108	0	0	0	0	0	0	0	0	5	0	232	918
11:15 AM	0	127	2	0	21	93	0	0	0	0	0	0	2	0	9	0	254	940
11:30 AM	0	106	5	0	18	104	0	0	0	0	0	0	4	0	12	0	249	975
11:45 AM	0	93	8	0	17	95	0	0	0	0	0	0	6	0	8	0	227	962
12:00 PM	0	97	3	0	12	115	0	0	0	0	0	0	5	0	31	0	263	993
12:15 PM	0	87	11	0	7	116	0	0	0	0	0	0	6	0	17	0	244	983
12:30 PM	0	109	5	0	20	101	0	0	0	0	0	0	2	0	21	0	258	992
12:45 PM	0	91	3	0	17	131	0	0	0	0	0	0	5	0	13	0	260	1025
1:00 PM	0	83	3	0	18	127	0	0	0	0	0	0	3	0	14	1	249	1011
1:15 PM	0	99	5	0	16	137	0	0	0	0	0	0	2	0	15	1	275	1042
1:30 PM	0	91	0	0	15	121	0	1	0	0	0	0	3	0	8	0	239	1023
1:45 PM	0	99	4	0	17	119	0	1	0	0	0	0	4	0	12	0	256	1019
2:00 PM	0	102	5	0	11	152	0	0	0	0	0	0	4	0	16	0	290	1060
2:15 PM	0	125	2	0	11	124	0	0	0	0	0	0	6	0	10	0	278	1063
2:30 PM	0	96	7	0	18	100	0	0	0	0	0	0	2	0	13	0	236	1060
2:45 PM	0	101	8	0	21	150	0	0	0	0	0	0	7	0	39	0	326	1130
3:00 PM	0	108	4	0	20	131	0	0	0	0	0	0	13	0	28	0	304	1144
3:15 PM	0	99	14	0	15	155	0	0	0	0	0	0	12	0	15	0	310	1176
3:30 PM	0	98	0	0	7	142	0	0	0	0	0	0	3	0	11	0	261	1201
3:45 PM	0	131	1	0	6	165	0	0	0	0	0	0	3	0	16	0	322	1197
4:00 PM	0	118	3	0	15	128	0	1	0	0	0	0	2	0	9	0	276	1169
4:15 PM	0	131	6	0	14	140	0	0	0	0	0	0	2	0	19	0	312	1171
4:30 PM	0	135	4	0	12	169	0	1	0	0	0	0	3	0	28	0	352	1262
4:45 PM	0	104	3	0	16	163	0	0	0	0	0	0	11	0	21	0	318	1258
5:00 PM	0	94	2	0	14	176	0	0	0	0	0	0	5	0	11	0	302	1284
5:15 PM	0	87	4	0	12	162	0	0	0	0	0	0	2	0	17	0	284	1256
5:30 PM	0	77	10	0	20	144	0	0	0	0	0	0	5	0	10	0	266	1170
5:45 PM	0	81	9	0	21	139	0	0	0	0	0	0	4	0	8	0	262	1114
6:00 PM	0	79	7	0	19	148	0	0	0	0	0	0	3	0	10	0	266	1078
6:15 PM	0	75	8	0	10	137	0	0	0	0	0	0	5	0	4	0	239	1033
6:30 PM	0	83	3	0	7	122	0	0	0	0	0	0	3	0	9	0	227	994
6:45 PM	0	73	5	0	6	121	0	0	0	0	0	0	4	0	5	0	214	946
7:00 PM	0	62	4	0	5	106	0	0	0	0	0	0	4	0	8	0	189	869
7:15 PM	0	67	1	0	4	94	0	0	0	0	0	0	1	0	11	0	178	808
7:30 PM	0	43	3	0	4	94	0	0	0	0	0	0	5	0	2	0	151	732
7:45 PM	0	37	0	0	9	81	0	0	0	0	0	0	7	0	10	0	144	662
8:00 PM	0	45	4	0	5	76	0	0	0	0	0	0	5	0	18	0	153	626
8:15 PM	0	33	3	0	4	75	0	0	0	0	0	0	16	0	30	0	161	609
8:30 PM	0	22	1	0	6	73	0	0	0	0	0	0	10	0	24	0	136	594
8:45 PM	0	24	2	0	11	60	0	0	0	0	0	0	5	0	16	0	118	568
9:00 PM	0	20	4	0	4	45	0	0	0	0	0	0	2	0	5	0	80	495
9:15 PM	0	27	1	0	8	48	0	0	0	0	0	0	3	0	5	0	92	426
9:30 PM	0	18	0	0	7	55	0	0	0	0	0	0	2	0	3	0	85	375
9:45 PM	0	20	3	0	4	38	0	0	0	0	0	0	2	0	10	0	77	334
10:00 PM	0	10	0	0	6	32	0	0	0	0	0	0	1	0	5	0	54	308
10:15 PM	0	17	0	0	4	36	0	0	0	0	0	0	0	0	3	0	60	276
10:30 PM	0	17	1	0	2	39	0	0	0	0	0	0	2	0	2	0	63	254
10:45 PM	0	8	0	0	3	27	0	0	0	0	0	0	2	0	1	0	41	218
11:00 PM	0	11	1	0	0	26	0	0	0	0	0	0	2	0	2	0	42	206
11:15 PM	0	11	0	0	0	19	0	0	0	0	0	0	0	0	1	0	31	177
11:30 PM	0	12	0	0	0	15	0	0	0	0	0	0	0	0	0	0	27	141
11:45 PM	0	9	1	0	0	16	0	0	0	0	0	0	0	0	0	0	26	126
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	0	728	172	0	200	336	0	4	0	0	0	0	8	0	76	0	1524	
Heavy Trucks	0	0	0		0	0	0		0	0	0		0	0	4		4	
Pedestrians		0				0				0				0			0	
Bicycles	0	5	0		2	0	0		0	0	0		0	0	1		8	
Railroad																		
Stopped Buses																		
<i>Comments:</i>																		

LOCATION: Kuakini Hwy -- YWAM Driveway
CITY/STATE: Kailua, HI

QC JOB #: 15036058
DATE: Thu, Oct 3 2019

Peak-Hour: 4:15 PM -- 5:15 PM
Peak 15-Min: 4:30 PM -- 4:45 PM




15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				YWAM Driveway (Eastbound)				YWAM Driveway (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
12:00 AM	0	6	0	0	0	18	0	0	0	0	0	0	0	0	0	0	24	
12:15 AM	0	7	1	0	0	8	0	0	0	0	0	0	0	0	0	0	16	
12:30 AM	0	2	0	0	0	9	0	0	0	0	0	0	0	0	0	0	11	
12:45 AM	0	1	0	0	0	6	0	0	0	0	0	0	0	0	0	0	7	58
1:00 AM	0	2	0	0	0	3	0	0	0	0	0	0	0	0	0	0	5	39
1:15 AM	0	2	0	0	1	7	0	0	0	0	0	0	0	0	0	0	10	33
1:30 AM	0	2	0	0	0	5	0	0	0	0	0	0	0	0	0	0	7	29
1:45 AM	0	5	0	0	0	3	0	0	0	0	0	0	0	0	0	0	8	30
2:00 AM	0	1	0	0	0	4	0	0	0	0	0	0	0	0	0	0	5	30
2:15 AM	0	2	0	0	0	4	0	0	0	0	0	0	0	0	0	0	6	26
2:30 AM	0	1	1	0	0	4	0	0	0	0	0	0	0	1	0	0	7	26
2:45 AM	0	2	0	0	0	5	0	0	0	0	0	0	0	0	0	0	7	25
3:00 AM	0	4	0	0	0	2	0	0	0	0	0	0	0	1	0	0	7	27
3:15 AM	0	10	1	0	1	1	0	0	0	0	0	0	0	1	0	0	14	35
3:30 AM	0	3	0	0	1	0	0	0	0	0	0	0	0	0	0	0	4	32
3:45 AM	0	3	0	0	0	3	0	0	0	0	0	0	0	0	0	0	6	31
4:00 AM	0	5	0	0	0	3	0	0	0	0	0	0	0	0	0	0	8	32
4:15 AM	0	6	0	0	0	2	0	0	0	0	0	0	0	0	0	0	8	26
4:30 AM	0	12	0	0	0	4	0	0	0	0	0	0	0	0	0	0	16	38
4:45 AM	0	18	1	0	3	5	0	0	0	0	0	0	0	0	0	0	27	59
5:00 AM	0	15	1	0	1	5	0	0	0	0	0	0	0	1	0	0	23	74
5:15 AM	0	18	0	0	0	8	0	0	0	0	0	0	0	0	0	0	26	92
5:30 AM	0	31	1	0	1	8	0	0	0	0	0	0	0	0	0	0	41	117
5:45 AM	0	67	3	0	4	15	0	0	0	0	0	0	0	0	0	0	89	179
6:00 AM	0	43	0	0	1	19	0	0	0	0	0	1	0	1	0	0	65	221
6:15 AM	0	63	4	0	8	23	0	0	0	0	0	0	0	4	0	0	102	297
6:30 AM	0	89	7	0	3	41	0	0	0	0	0	0	0	2	0	0	142	398
6:45 AM	0	94	2	0	8	58	0	0	0	0	0	0	0	6	0	0	168	477
7:00 AM	0	107	3	0	8	68	0	0	0	0	0	2	0	10	0	0	198	610
7:15 AM	0	127	5	0	8	82	0	0	0	0	0	0	0	7	0	0	229	737
7:30 AM	0	148	12	0	28	67	0	0	0	0	0	1	0	5	0	0	261	856
7:45 AM	0	182	43	0	50	84	0	1	0	0	0	2	0	19	0	0	381	1069
8:00 AM	0	168	13	0	20	68	0	0	0	0	0	10	0	20	0	0	299	1170
8:15 AM	0	126	8	0	15	71	0	0	0	0	0	4	0	11	0	0	235	1176
8:30 AM	0	143	4	0	15	70	0	0	0	0	0	1	0	10	0	0	243	1158
8:45 AM	0	124	11	0	19	96	0	1	0	0	0	3	0	5	0	0	259	1036
9:00 AM	0	108	3	0	11	80	0	0	0	0	0	6	0	29	0	0	237	974
9:15 AM	0	105	6	0	6	84	0	1	0	0	0	4	0	12	0	0	218	957
9:30 AM	0	118	4	0	14	86	0	0	0	0	0	2	0	9	0	0	233	947

15-Min Count Period Beginning At	Kuakini Hwy (Northbound)				Kuakini Hwy (Southbound)				YWAM Driveway (Eastbound)				YWAM Driveway (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
9:45 AM	0	91	2	0	4	92	0	1	0	0	0	0	2	0	7	0	199	887
10:00 AM	0	111	3	0	4	98	0	0	0	0	0	0	2	0	8	0	226	876
10:15 AM	0	113	6	0	12	86	0	0	0	0	0	0	3	0	12	0	232	890
10:30 AM	0	104	0	0	4	96	0	0	0	0	0	0	0	0	10	0	214	871
10:45 AM	0	118	2	0	12	93	0	1	0	0	0	0	4	0	10	0	240	912
11:00 AM	0	107	6	0	6	108	0	0	0	0	0	0	0	0	5	0	232	918
11:15 AM	0	127	2	0	21	93	0	0	0	0	0	0	2	0	9	0	254	940
11:30 AM	0	106	5	0	18	104	0	0	0	0	0	0	4	0	12	0	249	975
11:45 AM	0	93	8	0	17	95	0	0	0	0	0	0	6	0	8	0	227	962
12:00 PM	0	97	3	0	12	115	0	0	0	0	0	0	5	0	31	0	263	993
12:15 PM	0	87	11	0	7	116	0	0	0	0	0	0	6	0	17	0	244	983
12:30 PM	0	109	5	0	20	101	0	0	0	0	0	0	2	0	21	0	258	992
12:45 PM	0	91	3	0	17	131	0	0	0	0	0	0	5	0	13	0	260	1025
1:00 PM	0	83	3	0	18	127	0	0	0	0	0	0	3	0	14	1	249	1011
1:15 PM	0	99	5	0	16	137	0	0	0	0	0	0	2	0	15	1	275	1042
1:30 PM	0	91	0	0	15	121	0	1	0	0	0	0	3	0	8	0	239	1023
1:45 PM	0	99	4	0	17	119	0	1	0	0	0	0	4	0	12	0	256	1019
2:00 PM	0	102	5	0	11	152	0	0	0	0	0	0	4	0	16	0	290	1060
2:15 PM	0	125	2	0	11	124	0	0	0	0	0	0	6	0	10	0	278	1063
2:30 PM	0	96	7	0	18	100	0	0	0	0	0	0	2	0	13	0	236	1060
2:45 PM	0	101	8	0	21	150	0	0	0	0	0	0	7	0	39	0	326	1130
3:00 PM	0	108	4	0	20	131	0	0	0	0	0	0	13	0	28	0	304	1144
3:15 PM	0	99	14	0	15	155	0	0	0	0	0	0	12	0	15	0	310	1176
3:30 PM	0	98	0	0	7	142	0	0	0	0	0	0	3	0	11	0	261	1201
3:45 PM	0	131	1	0	6	165	0	0	0	0	0	0	3	0	16	0	322	1197
4:00 PM	0	118	3	0	15	128	0	1	0	0	0	0	2	0	9	0	276	1169
4:15 PM	0	131	6	0	14	140	0	0	0	0	0	0	2	0	19	0	312	1171
4:30 PM	0	135	4	0	12	169	0	1	0	0	0	0	3	0	28	0	352	1262
4:45 PM	0	104	3	0	16	163	0	0	0	0	0	0	11	0	21	0	318	1258
5:00 PM	0	94	2	0	14	176	0	0	0	0	0	0	5	0	11	0	302	1284
5:15 PM	0	87	4	0	12	162	0	0	0	0	0	0	2	0	17	0	284	1256
5:30 PM	0	77	10	0	20	144	0	0	0	0	0	0	5	0	10	0	266	1170
5:45 PM	0	81	9	0	21	139	0	0	0	0	0	0	4	0	8	0	262	1114
6:00 PM	0	79	7	0	19	148	0	0	0	0	0	0	3	0	10	0	266	1078
6:15 PM	0	75	8	0	10	137	0	0	0	0	0	0	5	0	4	0	239	1033
6:30 PM	0	83	3	0	7	122	0	0	0	0	0	0	3	0	9	0	227	994
6:45 PM	0	73	5	0	6	121	0	0	0	0	0	0	4	0	5	0	214	946
7:00 PM	0	62	4	0	5	106	0	0	0	0	0	0	4	0	8	0	189	869
7:15 PM	0	67	1	0	4	94	0	0	0	0	0	0	1	0	11	0	178	808
7:30 PM	0	43	3	0	4	94	0	0	0	0	0	0	5	0	2	0	151	732
7:45 PM	0	37	0	0	9	81	0	0	0	0	0	0	7	0	10	0	144	662
8:00 PM	0	45	4	0	5	76	0	0	0	0	0	0	5	0	18	0	153	626
8:15 PM	0	33	3	0	4	75	0	0	0	0	0	0	16	0	30	0	161	609
8:30 PM	0	22	1	0	6	73	0	0	0	0	0	0	10	0	24	0	136	594
8:45 PM	0	24	2	0	11	60	0	0	0	0	0	0	5	0	16	0	118	568
9:00 PM	0	20	4	0	4	45	0	0	0	0	0	0	2	0	5	0	80	495
9:15 PM	0	27	1	0	8	48	0	0	0	0	0	0	3	0	5	0	92	426
9:30 PM	0	18	0	0	7	55	0	0	0	0	0	0	2	0	3	0	85	375
9:45 PM	0	20	3	0	4	38	0	0	0	0	0	0	2	0	10	0	77	334
10:00 PM	0	10	0	0	6	32	0	0	0	0	0	0	1	0	5	0	54	308
10:15 PM	0	17	0	0	4	36	0	0	0	0	0	0	0	0	3	0	60	276
10:30 PM	0	17	1	0	2	39	0	0	0	0	0	0	2	0	2	0	63	254
10:45 PM	0	8	0	0	3	27	0	0	0	0	0	0	2	0	1	0	41	218
11:00 PM	0	11	1	0	0	26	0	0	0	0	0	0	2	0	2	0	42	206
11:15 PM	0	11	0	0	0	19	0	0	0	0	0	0	0	0	1	0	31	177
11:30 PM	0	12	0	0	0	15	0	0	0	0	0	0	0	0	0	0	27	141
11:45 PM	0	9	1	0	0	16	0	0	0	0	0	0	0	0	0	0	26	126
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	0	540	16	0	48	676	0	4	0	0	0	0	12	0	112	0	1408	
Heavy Trucks	0	8	0	0	0	4	0	0	0	0	0	0	0	0	0	0	12	
Pedestrians	0	0	0	0	0	0	0	0	0	0	0	0	0	4	0	0	4	
Bicycles	0	0	0	0	2	1	0	0	0	0	0	0	0	0	1	0	4	
Railroad																		
Stopped Buses																		
<i>Comments:</i>																		

Report generated on 10/14/2019 2:36 PM

SOURCE: Quality Counts, LLC (<http://www.qualitycounts.net>) 1-877-580-2212










AM and PM Peak Hour counts were manually collected at this intersection during field observation on 30 September 2019.



LOCATION: Queen Kaahumanu Hwy -- Nani Kailua Dr
CITY/STATE: Kailua, HI

QC JOB #: 15036001
DATE: Tue, Oct 1 2019

Peak-Hour: 7:15 AM -- 8:15 AM
Peak 15-Min: 7:30 AM -- 7:45 AM









15-Min Count Period Beginning At	Queen Kaahumanu Hwy (Northbound)				Queen Kaahumanu Hwy (Southbound)				Nani Kailua Dr (Eastbound)				Nani Kailua Dr (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
6:00 AM	2	173	0	0	2	77	2	0	7	0	4	0	6	4	17	0	294	
6:15 AM	3	253	4	0	4	112	2	0	8	2	0	0	5	8	22	0	423	
6:30 AM	2	247	1	0	10	132	6	0	7	2	0	0	7	7	28	0	449	
6:45 AM	3	243	6	0	13	167	8	0	12	1	2	0	16	7	31	1	510	1676
7:00 AM	2	264	5	0	12	188	10	0	8	2	2	0	12	6	27	0	538	1920
7:15 AM	5	256	7	0	13	189	14	0	11	2	6	0	17	6	44	0	570	2067
7:30 AM	6	235	5	0	12	177	21	0	14	5	5	0	22	20	53	0	575	2193
7:45 AM	12	235	13	0	16	160	20	0	9	9	3	0	9	14	56	0	556	2239
8:00 AM	1	226	7	0	28	145	15	0	20	4	3	0	6	8	51	0	514	2215
8:15 AM	2	242	8	0	24	179	17	0	16	1	4	0	4	7	26	0	530	2175
8:30 AM	0	243	6	0	26	156	15	0	14	2	2	0	6	14	29	0	513	2113
8:45 AM	5	257	5	0	9	170	19	0	11	10	3	0	6	8	36	0	539	2096
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	24	940	20	0	48	708	84	0	56	20	20	0	88	80	212	0	2300	
Heavy Trucks	0	16	4		0	36	4		0	0	0		0	0	4		64	
Pedestrians	0	0	0		0	0	0		0	0	0		0	0	0		0	
Bicycles	0	0	0		0	0	0		0	0	0		0	0	1		1	
Railroad																		
Stopped Buses																		

Comments: Conduct TMC on 10/1 and 2/2019

LOCATION: Queen Kaahumanu Hwy -- Nani Kailua Dr
CITY/STATE: Kailua, HI

QC JOB #: 15036002
DATE: Tue, Oct 1 2019

Peak-Hour: 3:15 PM -- 4:15 PM
Peak 15-Min: 3:30 PM -- 3:45 PM












15-Min Count Period Beginning At	Queen Kaahumanu Hwy (Northbound)				Queen Kaahumanu Hwy (Southbound)				Nani Kailua Dr (Eastbound)				Nani Kailua Dr (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
3:00 PM	8	248	14	0	35	226	32	0	16	17	9	0	9	10	31	0	655	
3:15 PM	6	194	8	0	36	241	16	0	16	12	3	0	8	16	23	0	579	
3:30 PM	6	239	7	0	38	248	15	0	15	12	0	0	5	6	19	0	610	
3:45 PM	12	223	9	0	28	237	21	0	14	13	0	0	13	10	22	0	602	2446
4:00 PM	7	210	14	0	24	238	16	0	24	13	9	0	4	8	26	0	593	2384
4:15 PM	9	198	0	0	23	200	17	0	16	15	3	0	10	8	30	0	529	2334
4:30 PM	7	212	10	0	24	237	19	0	14	7	4	0	8	7	27	0	576	2300
4:45 PM	6	189	9	0	33	238	22	0	14	16	4	0	12	7	13	0	563	2261
5:00 PM	4	160	5	0	42	224	12	0	13	16	2	0	5	9	30	1	523	2191
5:15 PM	4	173	8	0	29	241	19	0	11	18	2	0	5	6	21	0	537	2199
5:30 PM	2	152	6	0	34	224	20	0	14	12	2	0	9	6	32	0	513	2136
5:45 PM	4	161	12	0	28	232	12	0	7	13	4	0	5	8	23	0	509	2082
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	24	956	28	0	152	992	60	0	60	48	0	0	20	24	76	0	2440	
Heavy Trucks	0	24	0	0	4	12	0	0	4	0	0	0	0	0	0	0	44	
Pedestrians	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Bicycles	0	1	0	0	0	1	0	0	0	0	0	0	0	1	2	0	5	
Railroad																		
Stopped Buses																		

Comments: Conduct TMC on 10/1 and 2/2019

LOCATION: NW Loop -- Hualalai Rd
CITY/STATE: Kailua, HI

QC JOB #: 15036011
DATE: Tue, Oct 1 2019

Peak-Hour: 7:15 AM -- 8:15 AM
Peak 15-Min: 7:30 AM -- 7:45 AM











15-Min Count Period Beginning At	NW Loop (Northbound)				NW Loop (Southbound)				Hualalai Rd (Eastbound)				Hualalai Rd (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
6:00 AM	3	0	2	0	1	0	0	0	0	5	0	0	0	10	1	0	22	
6:15 AM	6	0	1	0	0	0	0	0	0	7	0	0	0	4	0	0	18	
6:30 AM	2	0	1	0	0	0	0	0	2	3	0	0	1	16	4	0	29	
6:45 AM	6	0	1	0	0	0	0	0	0	13	0	0	1	24	3	0	48	117
7:00 AM	3	0	0	0	0	0	1	0	0	13	4	0	1	16	2	0	40	135
7:15 AM	5	0	1	0	0	0	0	0	2	28	0	0	0	24	0	0	60	177
7:30 AM	14	0	1	0	0	0	2	0	0	24	2	0	4	51	1	0	99	247
7:45 AM	12	0	0	0	0	0	0	0	0	12	0	0	1	56	0	0	81	280
8:00 AM	10	0	3	0	0	0	1	0	0	11	6	0	1	35	2	0	69	309
8:15 AM	2	0	2	0	1	0	0	0	1	15	1	0	0	43	2	0	67	316
8:30 AM	3	0	1	0	0	0	2	0	0	11	1	0	1	41	1	0	61	278
8:45 AM	4	0	0	0	0	0	1	0	1	11	1	0	1	57	1	0	77	274
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	56	0	4	0	0	0	8	0	0	96	8	0	16	204	4	0	396	
Heavy Trucks	0	0	0		0	0	0		0	0	4		0	0	0		4	
Pedestrians	0	0	0		0	0	0		0	0	0		0	0	0		0	
Bicycles	0	0	0		0	0	0		0	0	0		0	1	0		1	
Railroad																		
Stopped Buses																		

Comments: Conduct TMC on 10/1 and 2/2019

LOCATION: NW Loop -- Hualalai Rd
CITY/STATE: Kailua, HI

QC JOB #: 15036012
DATE: Tue, Oct 1 2019

Peak-Hour: 3:15 PM -- 4:15 PM
Peak 15-Min: 4:00 PM -- 4:15 PM










15-Min Count Period Beginning At	NW Loop (Northbound)				NW Loop (Southbound)				Hualalai Rd (Eastbound)				Hualalai Rd (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
3:00 PM	2	0	0	0	1	0	1	0	1	23	6	0	3	27	0	0	64	
3:15 PM	3	0	0	0	1	0	0	0	1	22	5	0	1	15	0	0	48	
3:30 PM	2	0	1	0	0	0	1	0	1	21	5	0	2	28	0	0	61	
3:45 PM	3	0	0	0	1	0	1	0	0	27	2	0	3	31	3	0	71	244
4:00 PM	5	0	3	0	1	0	0	0	0	34	1	0	7	26	1	0	78	258
4:15 PM	3	0	1	0	0	0	2	0	0	22	6	0	2	27	0	1	64	274
4:30 PM	4	0	0	0	0	0	0	0	0	21	5	0	2	23	2	0	57	270
4:45 PM	6	0	2	0	1	0	1	0	0	27	0	0	4	13	0	0	54	253
5:00 PM	4	0	0	0	0	0	1	0	0	31	2	0	3	13	0	0	54	229
5:15 PM	2	0	1	0	0	0	1	0	1	14	7	0	2	7	0	0	35	200
5:30 PM	4	0	1	0	1	0	1	0	0	19	3	0	0	13	0	0	42	185
5:45 PM	5	0	1	0	0	0	1	0	0	15	4	0	3	7	0	0	36	167
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	20	0	12	0	4	0	0	0	0	136	4	0	28	104	4	0	312	
Heavy Trucks	0	0	0		0	0	0		0	0	0		0	4	0		4	
Pedestrians						4				0				0			4	
Bicycles	0	0	0		0	0	0		0	0	0		0	0	0		0	
Railroad																		
Stopped Buses																		

Comments: Conduct TMC on 10/1 and 2/2019

LOCATION: Queen Kaahumanu Hwy -- Hualalai Rd
CITY/STATE: Kailua, HI

QC JOB #: 15036007
DATE: Tue, Oct 1 2019

Peak-Hour: 7:15 AM -- 8:15 AM
Peak 15-Min: 7:15 AM -- 7:30 AM




15-Min Count Period Beginning At	Queen Kaahumanu Hwy (Northbound)				Queen Kaahumanu Hwy (Southbound)				Hualalai Rd (Eastbound)				Hualalai Rd (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
6:00 AM	10	169	0	0	0	90	0	0	0	0	6	0	0	0	0	0	275	
6:15 AM	4	246	0	0	0	111	0	0	2	0	7	0	0	0	0	0	370	
6:30 AM	20	249	0	0	0	127	5	0	3	0	6	0	0	0	0	0	410	
6:45 AM	29	254	0	0	0	184	4	0	1	0	10	0	0	0	0	0	482	1537
7:00 AM	19	282	0	0	0	190	6	0	4	0	9	0	0	0	0	0	510	1772
7:15 AM	27	283	0	0	0	214	10	0	14	0	16	0	0	0	0	0	564	1966
7:30 AM	49	256	0	0	0	206	11	0	15	0	9	0	0	0	0	0	546	2102
7:45 AM	56	240	0	0	0	176	2	0	4	0	11	0	0	0	0	0	489	2109
8:00 AM	36	254	0	0	0	150	1	0	0	0	14	0	0	0	0	0	455	2054
8:15 AM	37	262	0	0	0	192	2	0	0	0	17	0	0	0	0	0	510	2000
8:30 AM	36	255	0	0	0	178	2	0	0	0	9	0	0	0	0	0	480	1934
8:45 AM	53	263	0	0	0	184	1	0	1	0	11	0	0	0	0	0	513	1958
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	108	1132	0	0	0	856	40	0	56	0	64	0	0	0	0	0	2256	
Heavy Trucks	0	8	0	0	0	16	0	0	0	0	0	0	0	0	0	0	24	
Pedestrians	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Railroad																		
Stopped Buses																		

Comments: Conduct TMC on 10/1 and 2/2019

LOCATION: Queen Kaahumanu Hwy -- Hualalai Rd
CITY/STATE: Kailua, HI

QC JOB #: 15036008
DATE: Tue, Oct 1 2019










15-Min Count Period Beginning At	Queen Kaahumanu Hwy (Northbound)				Queen Kaahumanu Hwy (Southbound)				Hualalai Rd (Eastbound)				Hualalai Rd (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
3:00 PM	23	237	0	0	0	237	6	0	1	0	24	0	0	0	0	0	528	
3:15 PM	14	218	0	0	0	251	3	0	0	0	23	0	0	0	0	0	509	
3:30 PM	23	227	0	0	0	245	2	0	4	0	23	0	0	0	0	0	524	
3:45 PM	32	236	0	0	0	241	6	0	2	0	25	0	0	0	0	0	542	2103
4:00 PM	20	224	0	0	0	254	8	0	8	0	34	0	0	0	0	0	548	2123
4:15 PM	26	219	0	0	0	217	2	0	0	0	24	0	0	0	0	0	488	2102
4:30 PM	22	198	0	0	0	240	5	0	4	0	18	0	0	0	0	0	487	2065
4:45 PM	13	203	0	0	0	244	4	0	4	0	24	0	0	0	0	0	492	2015
5:00 PM	11	163	0	0	0	237	4	0	0	0	31	0	0	0	0	0	446	1913
5:15 PM	7	175	0	0	0	235	3	0	3	0	17	0	0	0	0	0	440	1865
5:30 PM	13	155	0	0	0	235	3	0	2	0	21	0	0	0	0	0	429	1807
5:45 PM	12	170	0	0	0	240	7	0	1	0	15	0	0	0	0	0	445	1760
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
All Vehicles	80	896	0	0	0	1016	32	0	32	0	136	0	0	0	0	0	2192	
Heavy Trucks	4	16	0	0	0	16	0	0	0	0	0	0	0	0	0	0	36	
Pedestrians	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Bicycles	0	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0	2	
Railroad																		
Stopped Buses																		

Comments: Conduct TMC on 10/1 and 2/2019

LOCATION: Queen Kaahumanu Hwy -- Kuakini Hwy
CITY/STATE: Honolulu, HI

QC JOB #: 15036049
DATE: Tue, Oct 1 2019

Peak-Hour: 7:15 AM -- 8:15 AM
Peak 15-Min: 7:15 AM -- 7:30 AM




15-Min Count Period Beginning At	Queen Kaahumanu Hwy (Northbound)				Queen Kaahumanu Hwy (Southbound)				Kuakini Hwy (Eastbound)				Kuakini Hwy (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
6:00 AM	38	171	0	0	0	90	0	0	0	0	0	0	0	0	0	0	299	
6:15 AM	49	189	0	0	0	117	0	0	0	0	0	0	0	0	0	0	355	
6:30 AM	60	230	0	0	0	121	1	0	2	0	0	0	0	0	0	0	414	
6:45 AM	71	254	0	0	0	167	1	0	1	0	0	0	0	0	0	0	494	1562
7:00 AM	71	234	0	0	0	184	5	0	3	0	0	0	0	0	0	0	497	1760
7:15 AM	74	248	0	0	0	198	13	0	1	0	0	0	0	0	0	0	534	1939
7:30 AM	110	216	0	0	0	182	23	0	0	0	0	0	0	0	0	0	531	2056
7:45 AM	159	161	0	0	0	173	28	0	0	0	0	0	0	0	0	0	521	2083
8:00 AM	132	199	0	0	0	137	10	0	1	0	0	0	0	0	0	0	479	2065
8:15 AM	89	236	0	0	0	176	9	0	0	0	0	0	0	0	0	0	510	2041
8:30 AM	74	244	0	0	0	151	6	0	0	0	0	1	0	0	0	0	476	1986
8:45 AM	63	228	0	0	0	173	11	0	1	0	0	0	0	0	0	0	476	1941
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
All Vehicles	296	992	0	0	0	792	52	0	4	0	0	0	0	0	0	0	2136	
Heavy Trucks	0	28	0	0	0	20	0	0	0	0	0	0	0	0	0	0	48	
Pedestrians	0	0	0	0	0	0	0	0	0	0	0	0	4	0	0	0	4	
Bicycles	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Railroad																		
Stopped Buses																		

Comments: Conduct TMC on 10/1 and 2/2019

LOCATION: Queen Kaahumanu Hwy -- Kuakini Hwy
CITY/STATE: Honolulu, HI

QC JOB #: 15036050
DATE: Tue, Oct 1 2019



15-Min Count Period Beginning At	Queen Kaahumanu Hwy (Northbound)				Queen Kaahumanu Hwy (Southbound)				Kuakini Hwy (Eastbound)				Kuakini Hwy (Westbound)				Total	Hourly Totals
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
3:00 PM	47	218	0	0	0	224	12	0	4	0	0	0	0	0	0	0	505	
3:15 PM	63	207	0	0	0	219	10	0	3	0	0	0	0	0	0	0	502	
3:30 PM	77	223	0	0	0	190	20	0	3	0	0	2	0	0	0	0	515	
3:45 PM	61	210	0	0	0	214	12	0	5	0	1	0	0	0	0	0	503	2025
4:00 PM	56	230	0	0	0	206	10	0	2	0	0	0	0	0	0	0	504	2024
4:15 PM	76	220	0	0	0	176	11	0	3	0	0	1	0	0	0	0	487	2009
4:30 PM	75	167	0	0	0	189	14	0	2	0	1	1	0	0	0	0	449	1943
4:45 PM	60	192	0	0	0	210	18	0	1	0	0	0	0	0	0	0	481	1921
5:00 PM	55	150	0	0	0	192	15	0	3	0	0	1	0	0	0	0	416	1833
5:15 PM	52	164	0	0	0	191	13	0	3	0	0	0	0	0	0	0	423	1769
5:30 PM	39	136	0	0	0	197	12	0	2	0	0	0	0	0	0	0	386	1706
5:45 PM	54	172	0	0	0	169	12	0	3	0	0	0	0	0	0	0	410	1635
Peak 15-Min Flowrates	Northbound				Southbound				Eastbound				Westbound				Total	
	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U	Left	Thru	Right	U		
All Vehicles	308	892	0	0	0	760	80	0	12	0	0	8	0	0	0	0	2060	
Heavy Trucks	0	40	0	0	0	16	0	0	0	0	0	0	0	0	0	0	56	
Pedestrians	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Bicycles	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	
Railroad																		
Stopped Buses																		

























Comments: Conduct TMC on 10/1 and 2/2019

APPENDIX B: LOS WORKSHEETS



HCM 6th Signalized Intersection Summary
1: Kuakini Hwy & Hualalai Rd

Existing Conditions
AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	184	41	15	63	34	198	19	606	50	131	362	163
Future Volume (veh/h)	184	41	15	63	34	198	19	606	50	131	362	163
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	0.98		0.99	0.99		0.94	0.99		1.00	1.00		0.99
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	211	47	8	72	39	79	22	697	0	151	416	72
Peak Hour Factor	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	534	412	70	514	105	213	343	1045		386	656	549
Arrive On Green	0.14	0.26	0.24	0.08	0.20	0.17	0.05	0.29	0.00	0.10	0.35	0.35
Sat Flow, veh/h	1781	1555	265	1781	528	1069	1781	3647	0	1781	1870	1567
Grp Volume(v), veh/h	211	0	55	72	0	118	22	697	0	151	416	72
Grp Sat Flow(s),veh/h/ln	1781	0	1819	1781	0	1597	1781	1777	0	1781	1870	1567
Q Serve(g_s), s	5.2	0.0	1.4	1.9	0.0	4.0	0.5	10.5	0.0	3.3	11.3	1.9
Cycle Q Clear(g_c), s	5.2	0.0	1.4	1.9	0.0	4.0	0.5	10.5	0.0	3.3	11.3	1.9
Prop In Lane	1.00		0.15	1.00		0.67	1.00		0.00	1.00		1.00
Lane Grp Cap(c), veh/h	534	0	482	514	0	318	343	1045		386	656	549
V/C Ratio(X)	0.40	0.00	0.11	0.14	0.00	0.37	0.06	0.67		0.39	0.63	0.13
Avail Cap(c_a), veh/h	1183	0	1222	989	0	811	875	3843		818	2022	1694
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
Uniform Delay (d), s/veh	14.1	0.0	17.1	16.9	0.0	21.6	14.2	18.9	0.0	12.9	16.6	13.5
Incr Delay (d2), s/veh	0.5	0.0	0.0	0.0	0.0	0.3	0.0	0.3	0.0	0.2	0.6	0.1
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	2.0	0.0	0.6	0.7	0.0	1.4	0.2	4.1	0.0	1.2	4.6	0.6
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	14.6	0.0	17.1	16.9	0.0	21.9	14.2	19.2	0.0	13.1	17.1	13.6
LnGrp LOS	B	A	B	B	A	C	B	B		B	B	B
Approach Vol, veh/h		266			190			719	A		639	
Approach Delay, s/veh		15.1			20.0			19.0			15.8	
Approach LOS		B			B			B			B	
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	6.8	25.4	12.7	16.1	10.2	22.0	8.7	20.2				
Change Period (Y+Rc), s	* 5.2	5.5	* 5.2	5.5	* 5.2	5.5	* 5.2	5.5				
Max Green Setting (Gmax), s	* 20	64.5	* 30	29.5	* 20	64.5	* 20	39.5				
Max Q Clear Time (g_c+1), s	2.5	13.3	7.2	6.0	5.3	12.5	3.9	3.4				
Green Ext Time (p_c), s	0.0	2.3	0.6	0.4	0.1	3.1	0.0	0.1				
Intersection Summary												
HCM 6th Ctrl Delay	17.4											
HCM 6th LOS	B											
Notes												
* HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.												
Unsignalized Delay for [NBR] is excluded from calculations of the approach delay and intersection delay.												

Intersection						
Int Delay, s/veh	2					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	↵	↵	↵	↵	↵	↵
Traffic Vol, veh/h	10	54	620	77	107	304
Future Vol, veh/h	10	54	620	77	107	304
Conflicting Peds, #/hr	1	1	0	1	1	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Stop	-	None	-	None
Storage Length	0	40	-	-	120	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	81	81	81	81	81	81
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	12	67	765	95	132	375

Major/Minor	Minor1	Major1	Major2	Major2	Major2
Conflicting Flow All	1454	815	0	0	861
Stage 1	814	-	-	-	-
Stage 2	640	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.12
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.218
Pot Cap-1 Maneuver	143	377	-	-	781
Stage 1	436	-	-	-	-
Stage 2	525	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	119	376	-	-	780
Mov Cap-2 Maneuver	119	-	-	-	-
Stage 1	436	-	-	-	-
Stage 2	436	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	20.1	0	2.7
HCM LOS	C		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	WBLn2	SBL	SBT
Capacity (veh/h)	-	-	119	376	780
HCM Lane V/C Ratio	-	-	0.104	0.177	0.169
HCM Control Delay (s)	-	-	38.7	16.6	10.6
HCM Lane LOS	-	-	E	C	B
HCM 95th %tile Q(veh)	-	-	0.3	0.6	0.6

Intersection						
Int Delay, s/veh	3.8					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations	↑	↑	↑	↑	↑	↑
Traffic Vol, veh/h	72	73	198	12	12	105
Future Vol, veh/h	72	73	198	12	12	105
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	120	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	78	79	215	13	13	114

























Major/Minor	Major1	Major2	Minor2		
Conflicting Flow All	228	0	-	0	457 222
Stage 1	-	-	-	-	222 -
Stage 2	-	-	-	-	235 -
Critical Hdwy	4.12	-	-	-	6.42 6.22
Critical Hdwy Stg 1	-	-	-	-	5.42 -
Critical Hdwy Stg 2	-	-	-	-	5.42 -
Follow-up Hdwy	2.218	-	-	-	3.518 3.318
Pot Cap-1 Maneuver	1340	-	-	-	562 818
Stage 1	-	-	-	-	815 -
Stage 2	-	-	-	-	804 -
Platoon blocked, %		-	-	-	
Mov Cap-1 Maneuver	1340	-	-	-	529 818
Mov Cap-2 Maneuver	-	-	-	-	529 -
Stage 1	-	-	-	-	768 -
Stage 2	-	-	-	-	804 -

Approach	EB	WB	SB
HCM Control Delay, s	3.9	0	10.6
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	1340	-	-	-	775
HCM Lane V/C Ratio	0.058	-	-	-	0.164
HCM Control Delay (s)	7.9	-	-	-	10.6
HCM Lane LOS	A	-	-	-	B
HCM 95th %tile Q(veh)	0.2	-	-	-	0.6

HCM 6th Signalized Intersection Summary
 4: Queen Kaahumanu Hwy & Nani Kailua Dr

Existing Conditions
 AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	54	20	17	54	48	204	24	952	32	69	671	70
Future Volume (veh/h)	54	20	17	54	48	204	24	952	32	69	671	70
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	0.99		1.00	0.99		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	56	21	0	56	50	0	25	992	0	72	699	0
Peak Hour Factor	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	221	58		165	82		522	1176		355	1228	
Arrive On Green	0.11	0.11	0.00	0.10	0.10	0.00	0.05	0.63	0.00	0.07	0.66	0.00
Sat Flow, veh/h	1121	518	1585	826	850	1585	1781	1870	1585	1781	1870	1585
Grp Volume(v), veh/h	77	0	0	106	0	0	25	992	0	72	699	0
Grp Sat Flow(s),veh/h/ln	1638	0	1585	1676	0	1585	1781	1870	1585	1781	1870	1585
Q Serve(g_s), s	0.0	0.0	0.0	1.2	0.0	0.0	0.3	27.2	0.0	0.8	13.3	0.0
Cycle Q Clear(g_c), s	2.6	0.0	0.0	3.8	0.0	0.0	0.3	27.2	0.0	0.8	13.3	0.0
Prop In Lane	0.73		1.00	0.53		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	280	0		247	0		522	1176		355	1228	
V/C Ratio(X)	0.28	0.00		0.43	0.00		0.05	0.84		0.20	0.57	
Avail Cap(c_a), veh/h	598	0		809	0		891	2648		675	2648	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	0.00	1.00	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	26.7	0.0	0.0	28.2	0.0	0.0	4.8	9.5	0.0	9.8	6.1	0.0
Incr Delay (d2), s/veh	0.5	0.0	0.0	1.2	0.0	0.0	0.0	1.7	0.0	0.3	0.4	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.1	0.0	0.0	1.6	0.0	0.0	0.1	7.2	0.0	0.4	3.1	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	27.3	0.0	0.0	29.3	0.0	0.0	4.8	11.3	0.0	10.1	6.5	0.0
LnGrp LOS	C	A		C	A		A	B		B	A	
Approach Vol, veh/h		77	A		106	A		1017	A		771	A
Approach Delay, s/veh		27.3			29.3			11.1			6.9	
Approach LOS		C			C			B			A	
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	7.0	46.7		11.3	8.8	44.8		11.3				
Change Period (Y+Rc), s	* 5.2	6.0		* 5.5	* 5.2	6.0		5.5				
Max Green Setting (Gmax), s	* 15	90.0		* 29	* 15	90.0		20.0				
Max Q Clear Time (g_c+11), s	2.3	15.3		5.8	2.8	29.2		4.6				
Green Ext Time (p_c), s	0.0	5.1		0.5	0.1	9.6		0.3				

Intersection Summary		
HCM 6th Ctrl Delay		11.1
HCM 6th LOS		B

Notes
 * HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.
 Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	2	75	8	6	166	3	41	0	5	0	0	3
Future Vol, veh/h	2	75	8	6	166	3	41	0	5	0	0	3
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	120	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	78	78	78	78	78	78	78	78	78	78	78	78
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	3	96	10	8	213	4	53	0	6	0	0	4

Major/Minor	Major1		Major2		Minor1		Minor2					
Conflicting Flow All	217	0	0	106	0	0	340	340	101	341	343	215
Stage 1	-	-	-	-	-	-	107	107	-	231	231	-
Stage 2	-	-	-	-	-	-	233	233	-	110	112	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1353	-	-	1485	-	-	614	582	954	613	579	825
Stage 1	-	-	-	-	-	-	898	807	-	772	713	-
Stage 2	-	-	-	-	-	-	770	712	-	895	803	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1353	-	-	1485	-	-	608	578	954	606	575	825
Mov Cap-2 Maneuver	-	-	-	-	-	-	608	578	-	606	575	-
Stage 1	-	-	-	-	-	-	896	805	-	770	709	-
Stage 2	-	-	-	-	-	-	762	708	-	887	801	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	0.2	0.3	11.3	9.4
HCM LOS			B	A

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	633	1353	-	-	1485	-	-	825
HCM Lane V/C Ratio	0.093	0.002	-	-	0.005	-	-	0.005
HCM Control Delay (s)	11.3	7.7	0	-	7.4	-	-	9.4
HCM Lane LOS	B	A	A	-	A	-	-	A
HCM 95th %tile Q(veh)	0.3	0	-	-	0	-	-	0

Intersection						
Int Delay, s/veh	1.4					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↘	↗	↘	↗	↗	↘
Traffic Vol, veh/h	33	50	168	1033	746	24
Future Vol, veh/h	33	50	168	1033	746	24
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Free	-	None	-	Yield
Storage Length	130	0	420	-	-	500
Veh in Median Storage, #	2	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	91	91	91	91	91	91
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	36	55	185	1135	820	26

Major/Minor	Minor2	Major1	Major2		
Conflicting Flow All	2325	-	820	0	-
Stage 1	820	-	-	-	-
Stage 2	1505	-	-	-	-
Critical Hdwy	6.42	-	4.12	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	-	2.218	-	-
Pot Cap-1 Maneuver	41	0	809	-	-
Stage 1	433	0	-	-	-
Stage 2	203	0	-	-	-
Platoon blocked, %				-	-
Mov Cap-1 Maneuver	~ 32	-	809	-	-
Mov Cap-2 Maneuver	165	-	-	-	-
Stage 1	334	-	-	-	-
Stage 2	203	-	-	-	-

Approach	EB	NB	SB
HCM Control Delay, s	32.9	1.5	0
HCM LOS	D		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	EBLn2	SBT	SBR
Capacity (veh/h)	809	-	165	-	-	-
HCM Lane V/C Ratio	0.228	-	0.22	-	-	-
HCM Control Delay (s)	10.8	-	32.9	0	-	-
HCM Lane LOS	B	-	D	A	-	-
HCM 95th %tile Q(veh)	0.9	-	0.8	-	-	-

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Intersection						
Int Delay, s/veh	3.2					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↙		↙	↗	↗	↙
Traffic Vol, veh/h	2	0	475	824	690	74
Future Vol, veh/h	2	0	475	824	690	74
Conflicting Peds, #/hr	1	1	1	0	0	1
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Free	-	None	-	Yield
Storage Length	-	-	450	-	-	500
Veh in Median Storage, #	2	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	2	0	490	849	711	76

























Major/Minor	Minor2	Major1	Major2		
Conflicting Flow All	2542	-	712	0	-
Stage 1	712	-	-	-	-
Stage 2	1830	-	-	-	-
Critical Hdwy	6.42	-	4.12	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	-	2.218	-	-
Pot Cap-1 Maneuver	30	0	888	-	-
Stage 1	486	0	-	-	-
Stage 2	140	0	-	-	-
Platoon blocked, %				-	-
Mov Cap-1 Maneuver	13	-	887	-	-
Mov Cap-2 Maneuver	110	-	-	-	-
Stage 1	218	-	-	-	-
Stage 2	140	-	-	-	-

Approach	EB	NB	SB
HCM Control Delay, s	38.4	5.1	0
HCM LOS	E		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	887	-	110	-	-
HCM Lane V/C Ratio	0.552	-	0.019	-	-
HCM Control Delay (s)	13.9	-	38.4	-	-
HCM Lane LOS	B	-	E	-	-
HCM 95th %tile Q(veh)	3.5	-	0.1	-	-

HCM 6th Signalized Intersection Summary
1: Kuakini Hwy & Hualalai Rd

Existing Conditions
PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	205	43	50	69	43	217	28	568	89	179	632	313
Future Volume (veh/h)	205	43	50	69	43	217	28	568	89	179	632	313
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	0.99		0.99	0.98		0.97	1.00		1.00	0.99		0.95
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	218	46	27	73	46	113	30	604	0	190	672	221
Peak Hour Factor	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	440	266	156	432	79	194	245	1323		474	801	647
Arrive On Green	0.14	0.24	0.22	0.07	0.17	0.15	0.05	0.37	0.00	0.10	0.43	0.43
Sat Flow, veh/h	1781	1099	645	1781	471	1156	1781	3647	0	1781	1870	1512
Grp Volume(v), veh/h	218	0	73	73	0	159	30	604	0	190	672	221
Grp Sat Flow(s),veh/h/ln	1781	0	1744	1781	0	1627	1781	1777	0	1781	1870	1512
Q Serve(g_s), s	6.9	0.0	2.5	2.4	0.0	6.8	0.7	9.6	0.0	4.5	23.9	7.3
Cycle Q Clear(g_c), s	6.9	0.0	2.5	2.4	0.0	6.8	0.7	9.6	0.0	4.5	23.9	7.3
Prop In Lane	1.00		0.37	1.00		0.71	1.00		0.00	1.00		1.00
Lane Grp Cap(c), veh/h	440	0	422	432	0	273	245	1323		474	801	647
V/C Ratio(X)	0.50	0.00	0.17	0.17	0.00	0.58	0.12	0.46		0.40	0.84	0.34
Avail Cap(c_a), veh/h	926	0	958	812	0	676	662	3143		792	1654	1337
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
Uniform Delay (d), s/veh	19.5	0.0	22.6	22.9	0.0	29.2	15.7	17.7	0.0	11.7	19.0	14.3
Incr Delay (d2), s/veh	0.9	0.0	0.1	0.1	0.0	0.7	0.1	0.1	0.0	0.2	1.3	0.2
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	2.9	0.0	1.0	1.0	0.0	2.7	0.3	3.8	0.0	1.7	9.9	2.4
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	20.4	0.0	22.7	23.0	0.0	29.9	15.8	17.8	0.0	11.9	20.4	14.5
LnGrp LOS	C	A	C	C	A	C	B	B		B	C	B
Approach Vol, veh/h		291			232			634	A		1083	
Approach Delay, s/veh		21.0			27.7			17.7			17.7	
Approach LOS		C			C			B			B	
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	7.5	35.9	14.6	16.5	11.7	31.8	9.1	22.1				
Change Period (Y+Rc), s	* 5.2	5.5	* 5.2	5.5	* 5.2	5.5	* 5.2	5.5				
Max Green Setting (Gmax), s	* 20	64.5	* 30	29.5	* 20	64.5	* 20	39.5				
Max Q Clear Time (g_c+I1), s	2.7	25.9	8.9	8.8	6.5	11.6	4.4	4.5				
Green Ext Time (p_c), s	0.0	4.5	0.6	0.5	0.1	2.6	0.0	0.2				
Intersection Summary												
HCM 6th Ctrl Delay			19.2									
HCM 6th LOS			B									
Notes												
* HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.												
Unsignalized Delay for [NBR] is excluded from calculations of the approach delay and intersection delay.												

Intersection						
Int Delay, s/veh	1.9					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	↵	↵	↵	↵	↵	↵
Traffic Vol, veh/h	33	88	410	27	53	743
Future Vol, veh/h	33	88	410	27	53	743
Conflicting Peds, #/hr	6	5	0	6	5	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Stop	-	None	-	None
Storage Length	0	40	-	-	120	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	34	91	423	28	55	766

Major/Minor	Minor1	Major1	Major2	Major2	Major2
Conflicting Flow All	1325	448	0	0	457
Stage 1	443	-	-	-	-
Stage 2	882	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.12
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.218
Pot Cap-1 Maneuver	172	611	-	-	1104
Stage 1	647	-	-	-	-
Stage 2	405	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	162	605	-	-	1098
Mov Cap-2 Maneuver	162	-	-	-	-
Stage 1	643	-	-	-	-
Stage 2	383	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	17.7	0	0.6
HCM LOS	C		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	WBLn2	SBL	SBT
Capacity (veh/h)	-	-	162	605	1098
HCM Lane V/C Ratio	-	-	0.21	0.15	0.05
HCM Control Delay (s)	-	-	33	12	8.4
HCM Lane LOS	-	-	D	B	A
HCM 95th %tile Q(veh)	-	-	0.8	0.5	0.2

Intersection						
Int Delay, s/veh	5.4					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations	↑	↑	↑	↑	↑	↑
Traffic Vol, veh/h	123	98	106	9	21	147
Future Vol, veh/h	123	98	106	9	21	147
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	120	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	134	107	115	10	23	160

























Major/Minor	Major1	Major2	Minor2		
Conflicting Flow All	125	0	-	0	495 120
Stage 1	-	-	-	-	120 -
Stage 2	-	-	-	-	375 -
Critical Hdwy	4.12	-	-	-	6.42 6.22
Critical Hdwy Stg 1	-	-	-	-	5.42 -
Critical Hdwy Stg 2	-	-	-	-	5.42 -
Follow-up Hdwy	2.218	-	-	-	3.518 3.318
Pot Cap-1 Maneuver	1462	-	-	-	534 931
Stage 1	-	-	-	-	905 -
Stage 2	-	-	-	-	695 -
Platoon blocked, %		-	-	-	
Mov Cap-1 Maneuver	1462	-	-	-	485 931
Mov Cap-2 Maneuver	-	-	-	-	485 -
Stage 1	-	-	-	-	822 -
Stage 2	-	-	-	-	695 -

Approach	EB	WB	SB
HCM Control Delay, s	4.3	0	10.5
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	1462	-	-	-	835
HCM Lane V/C Ratio	0.091	-	-	-	0.219
HCM Control Delay (s)	7.7	-	-	-	10.5
HCM Lane LOS	A	-	-	-	B
HCM 95th %tile Q(veh)	0.3	-	-	-	0.8

HCM 6th Signalized Intersection Summary
4: Queen Kaahumanu Hwy & Nani Kailua Dr

Existing Conditions
PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	69	50	12	30	40	90	31	866	38	126	964	68
Future Volume (veh/h)	69	50	12	30	40	90	31	866	38	126	964	68
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	70	51	0	31	41	0	32	884	0	129	984	0
Peak Hour Factor	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	203	84		145	120		332	1107		416	1179	
Arrive On Green	0.12	0.12	0.00	0.10	0.10	0.00	0.05	0.59	0.00	0.09	0.63	0.00
Sat Flow, veh/h	922	705	1585	591	1172	1585	1781	1870	1585	1781	1870	1585
Grp Volume(v), veh/h	121	0	0	72	0	0	32	884	0	129	984	0
Grp Sat Flow(s),veh/h/ln	1626	0	1585	1763	0	1585	1781	1870	1585	1781	1870	1585
Q Serve(g_s), s	1.9	0.0	0.0	0.0	0.0	0.0	0.4	22.3	0.0	1.5	25.1	0.0
Cycle Q Clear(g_c), s	4.1	0.0	0.0	2.2	0.0	0.0	0.4	22.3	0.0	1.5	25.1	0.0
Prop In Lane	0.58		1.00	0.43		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	287	0		265	0		332	1107		416	1179	
V/C Ratio(X)	0.42	0.00		0.27	0.00		0.10	0.80		0.31	0.83	
Avail Cap(c_a), veh/h	646	0		876	0		718	2817		733	2817	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	0.00	1.00	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	25.4	0.0	0.0	25.6	0.0	0.0	8.7	9.6	0.0	8.7	8.8	0.0
Incr Delay (d2), s/veh	1.0	0.0	0.0	0.5	0.0	0.0	0.1	1.4	0.0	0.4	1.6	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.7	0.0	0.0	1.0	0.0	0.0	0.1	6.1	0.0	0.5	6.2	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	26.4	0.0	0.0	26.1	0.0	0.0	8.8	11.0	0.0	9.1	10.4	0.0
LnGrp LOS	C	A		C	A		A	B		A	B	
Approach Vol, veh/h		121	A		72	A		916	A		1113	A
Approach Delay, s/veh		26.4			26.1			10.9			10.3	
Approach LOS		C			C			B			B	
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	7.3	42.5		11.3	9.6	40.2		11.3				
Change Period (Y+Rc), s	* 5.2	6.0		* 5.5	* 5.2	6.0		5.5				
Max Green Setting (Gmax), s	* 15	90.0		* 29	* 15	90.0		20.0				
Max Q Clear Time (g_c+11), s	2.4	27.1		4.2	3.5	24.3		6.1				
Green Ext Time (p_c), s	0.0	9.5		0.3	0.2	7.6		0.5				

Intersection Summary		
HCM 6th Ctrl Delay		11.9
HCM 6th LOS		B

Notes
* HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.
Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	1.3											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	2	104	13	13	100	4	13	0	4	3	0	2
Future Vol, veh/h	2	104	13	13	100	4	13	0	4	3	0	2
Conflicting Peds, #/hr	0	0	0	2	0	3	0	0	2	3	0	1
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	120	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	83	83	83	83	83	83	83	83	83	83	83	83
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	2	125	16	16	120	5	16	0	5	4	0	2

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	128	0	0	143	0	0	296	299	138	301	305	127
Stage 1	-	-	-	-	-	-	139	139	-	158	158	-
Stage 2	-	-	-	-	-	-	157	160	-	143	147	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1458	-	-	1440	-	-	656	613	910	651	608	923
Stage 1	-	-	-	-	-	-	864	782	-	844	767	-
Stage 2	-	-	-	-	-	-	845	766	-	860	775	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1454	-	-	1437	-	-	646	603	906	638	598	919
Mov Cap-2 Maneuver	-	-	-	-	-	-	646	603	-	638	598	-
Stage 1	-	-	-	-	-	-	861	780	-	841	756	-
Stage 2	-	-	-	-	-	-	833	755	-	852	773	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	0.1	0.8	10.4	10
HCM LOS			B	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	693	1454	-	-	1437	-	-	727
HCM Lane V/C Ratio	0.03	0.002	-	-	0.011	-	-	0.008
HCM Control Delay (s)	10.4	7.5	0	-	7.5	-	-	10
HCM Lane LOS	B	A	A	-	A	-	-	B
HCM 95th %tile Q(veh)	0.1	0	-	-	0	-	-	0

Intersection						
Int Delay, s/veh	0.7					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↙	↘	↙	↘	↘	↘
Traffic Vol, veh/h	14	105	89	905	991	19
Future Vol, veh/h	14	105	89	905	991	19
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Free	-	None	-	Yield
Storage Length	130	0	420	-	-	500
Veh in Median Storage, #	2	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	14	108	92	933	1022	20

Major/Minor	Minor2	Major1	Major2		
Conflicting Flow All	2139	-	1022	0	-
Stage 1	1022	-	-	-	-
Stage 2	1117	-	-	-	-
Critical Hdwy	6.42	-	4.12	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	-	2.218	-	-
Pot Cap-1 Maneuver	54	0	679	-	-
Stage 1	347	0	-	-	-
Stage 2	313	0	-	-	-
Platoon blocked, %				-	-
Mov Cap-1 Maneuver	47	-	679	-	-
Mov Cap-2 Maneuver	209	-	-	-	-
Stage 1	300	-	-	-	-
Stage 2	313	-	-	-	-

Approach	EB	NB	SB
HCM Control Delay, s	23.5	1	0
HCM LOS	C		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	EBLn2	SBT	SBR
Capacity (veh/h)	679	-	209	-	-	-
HCM Lane V/C Ratio	0.135	-	0.069	-	-	-
HCM Control Delay (s)	11.1	-	23.5	0	-	-
HCM Lane LOS	B	-	C	A	-	-
HCM 95th %tile Q(veh)	0.5	-	0.2	-	-	-

Intersection						
Int Delay, s/veh	1.7					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↘		↘	↗	↗	↘
Traffic Vol, veh/h	15	0	257	870	829	52
Future Vol, veh/h	15	0	257	870	829	52
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Free	-	None	-	Yield
Storage Length	-	-	450	-	-	500
Veh in Median Storage, #	2	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	98	98	98	98	98	98
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	15	0	262	888	846	53

























Major/Minor	Minor2	Major1	Major2		
Conflicting Flow All	2258	-	846	0	-
Stage 1	846	-	-	-	-
Stage 2	1412	-	-	-	-
Critical Hdwy	6.42	-	4.12	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	-	2.218	-	-
Pot Cap-1 Maneuver	45	0	791	-	-
Stage 1	421	0	-	-	-
Stage 2	225	0	-	-	-
Platoon blocked, %				-	-
Mov Cap-1 Maneuver	30	-	791	-	-
Mov Cap-2 Maneuver	167	-	-	-	-
Stage 1	282	-	-	-	-
Stage 2	225	-	-	-	-

Approach	EB	NB	SB
HCM Control Delay, s	28.7	2.7	0
HCM LOS	D		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	791	-	167	-	-
HCM Lane V/C Ratio	0.332	-	0.092	-	-
HCM Control Delay (s)	11.8	-	28.7	-	-
HCM Lane LOS	B	-	D	-	-
HCM 95th %tile Q(veh)	1.5	-	0.3	-	-

HCM 6th Signalized Intersection Summary
1: Kuakini Hwy & Hualalai Rd

Phase 1 No Project Conditions
AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	210	50	20	80	40	230	30	720	60	150	430	190
Future Volume (veh/h)	210	50	20	80	40	230	30	720	60	150	430	190
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	0.98		0.99	0.99		0.94	1.00		1.00	1.00		0.99
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	241	57	13	92	46	139	34	828	0	172	494	101
Peak Hour Factor	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	489	426	97	511	85	256	298	1109		348	682	572
Arrive On Green	0.15	0.29	0.27	0.07	0.22	0.20	0.05	0.31	0.00	0.10	0.36	0.36
Sat Flow, veh/h	1781	1471	335	1781	392	1184	1781	3647	0	1781	1870	1568
Grp Volume(v), veh/h	241	0	70	92	0	185	34	828	0	172	494	101
Grp Sat Flow(s),veh/h/ln	1781	0	1806	1781	0	1576	1781	1777	0	1781	1870	1568
Q Serve(g_s), s	7.0	0.0	2.1	2.8	0.0	7.7	0.9	15.2	0.0	4.4	16.6	3.2
Cycle Q Clear(g_c), s	7.0	0.0	2.1	2.8	0.0	7.7	0.9	15.2	0.0	4.4	16.6	3.2
Prop In Lane	1.00		0.19	1.00		0.75	1.00		0.00	1.00		1.00
Lane Grp Cap(c), veh/h	489	0	524	511	0	341	298	1109		348	682	572
V/C Ratio(X)	0.49	0.00	0.13	0.18	0.00	0.54	0.11	0.75		0.49	0.72	0.18
Avail Cap(c_a), veh/h	985	0	1019	893	0	672	722	3227		679	1699	1424
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
Uniform Delay (d), s/veh	16.6	0.0	19.2	19.5	0.0	25.8	16.4	22.4	0.0	15.5	19.9	15.7
Incr Delay (d2), s/veh	0.8	0.0	0.0	0.1	0.0	0.5	0.1	0.4	0.0	0.4	0.8	0.1
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	2.8	0.0	0.9	1.1	0.0	2.9	0.4	6.1	0.0	1.7	7.0	1.1
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	17.3	0.0	19.2	19.6	0.0	26.3	16.5	22.8	0.0	15.9	20.7	15.8
LnGrp LOS	B	A	B	B	A	C	B	C		B	C	B
Approach Vol, veh/h		311			277			862	A		767	
Approach Delay, s/veh		17.7			24.1			22.5			19.0	
Approach LOS		B			C			C			B	
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	7.7	30.5	14.8	19.7	11.5	26.7	9.4	25.1				
Change Period (Y+Rc), s	* 5.2	5.5	* 5.2	5.5	* 5.2	5.5	* 5.2	5.5				
Max Green Setting (Gmax), s	* 20	64.5	* 30	29.5	* 20	64.5	* 20	39.5				
Max Q Clear Time (g_c+1), s	2.9	18.6	9.0	9.7	6.4	17.2	4.8	4.1				
Green Ext Time (p_c), s	0.0	2.8	0.7	0.6	0.1	3.9	0.0	0.2				
Intersection Summary												
HCM 6th Ctrl Delay			20.8									
HCM 6th LOS			C									
Notes												
* HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.												
Unsignalized Delay for [NBR] is excluded from calculations of the approach delay and intersection delay.												

Intersection						
Int Delay, s/veh	2.1					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	↙	↘	↙	↘	↙	↘
Traffic Vol, veh/h	10	54	740	77	107	360
Future Vol, veh/h	10	54	740	77	107	360
Conflicting Peds, #/hr	1	1	0	1	1	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Stop	-	None	-	None
Storage Length	0	40	-	-	120	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	81	81	81	81	81	81
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	12	67	914	95	132	444

Major/Minor	Minor1	Major1	Major2	Major2	Major2
Conflicting Flow All	1672	964	0	0	1010
Stage 1	963	-	-	-	-
Stage 2	709	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.12
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.218
Pot Cap-1 Maneuver	105	310	-	-	686
Stage 1	370	-	-	-	-
Stage 2	488	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	85	309	-	-	685
Mov Cap-2 Maneuver	85	-	-	-	-
Stage 1	370	-	-	-	-
Stage 2	393	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	25.2	0	2.6
HCM LOS	D		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	WBLn2	SBL	SBT
Capacity (veh/h)	-	-	85	309	685
HCM Lane V/C Ratio	-	-	0.145	0.216	0.193
HCM Control Delay (s)	-	-	54.4	19.8	11.5
HCM Lane LOS	-	-	F	C	B
HCM 95th %tile Q(veh)	-	-	0.5	0.8	0.7

Intersection						
Int Delay, s/veh	4					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations	↑	↑	↑	↑	↑	↑
Traffic Vol, veh/h	90	100	230	20	20	120
Future Vol, veh/h	90	100	230	20	20	120
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	120	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	98	109	250	22	22	130

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	272	0	0 566 261
Stage 1	-	-	- 261 -
Stage 2	-	-	- 305 -
Critical Hdwy	4.12	-	- 6.42 6.22
Critical Hdwy Stg 1	-	-	- 5.42 -
Critical Hdwy Stg 2	-	-	- 5.42 -
Follow-up Hdwy	2.218	-	- 3.518 3.318
Pot Cap-1 Maneuver	1291	-	- 486 778
Stage 1	-	-	- 783 -
Stage 2	-	-	- 748 -
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1291	-	- 449 778
Mov Cap-2 Maneuver	-	-	- 449 -
Stage 1	-	-	- 723 -
Stage 2	-	-	- 748 -

























Approach	EB	WB	SB
HCM Control Delay, s	3.8	0	11.5
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	1291	-	-	-	704
HCM Lane V/C Ratio	0.076	-	-	-	0.216
HCM Control Delay (s)	8	-	-	-	11.5
HCM Lane LOS	A	-	-	-	B
HCM 95th %tile Q(veh)	0.2	-	-	-	0.8

HCM 6th Signalized Intersection Summary
4: Queen Kaahumanu Hwy & Nani Kailua Dr

Phase 1 No Project Conditions

AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	70	30	30	70	60	260	30	1250	40	90	890	90
Future Volume (veh/h)	70	30	30	70	60	260	30	1250	40	90	890	90
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	0.99		1.00	0.99		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	73	31	0	73	62	0	31	1302	0	94	927	0
Peak Hour Factor	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	162	54		138	85		417	1364		193	1389	
Arrive On Green	0.12	0.12	0.00	0.11	0.11	0.00	0.04	0.73	0.00	0.05	0.74	0.00
Sat Flow, veh/h	922	448	1585	821	758	1585	1781	1870	1585	1781	1870	1585
Grp Volume(v), veh/h	104	0	0	135	0	0	31	1302	0	94	927	0
Grp Sat Flow(s),veh/h/ln	1370	0	1585	1579	0	1585	1781	1870	1585	1781	1870	1585
Q Serve(g_s), s	0.0	0.0	0.0	1.0	0.0	0.0	0.5	74.1	0.0	1.5	30.2	0.0
Cycle Q Clear(g_c), s	8.9	0.0	0.0	9.9	0.0	0.0	0.5	74.1	0.0	1.5	30.2	0.0
Prop In Lane	0.70		1.00	0.54		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	216	0		223	0		417	1364		193	1389	
V/C Ratio(X)	0.48	0.00		0.61	0.00		0.07	0.95		0.49	0.67	
Avail Cap(c_a), veh/h	303	0		434	0		598	1440		350	1440	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	0.00	1.00	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	50.1	0.0	0.0	51.5	0.0	0.0	7.1	14.4	0.0	31.6	7.9	0.0
Incr Delay (d2), s/veh	1.7	0.0	0.0	2.6	0.0	0.0	0.1	14.0	0.0	1.9	1.1	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	3.1	0.0	0.0	4.1	0.0	0.0	0.2	28.6	0.0	2.0	9.6	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	51.7	0.0	0.0	54.1	0.0	0.0	7.2	28.3	0.0	33.5	9.0	0.0
LnGrp LOS	D	A		D	A		A	C		C	A	
Approach Vol, veh/h		104	A		135	A		1333	A		1021	A
Approach Delay, s/veh		51.7			54.1			27.9			11.2	
Approach LOS		D			D			C			B	
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	8.4	92.7		18.3	10.0	91.1		18.3				
Change Period (Y+Rc), s	* 5.2	6.0		* 5.5	* 5.2	6.0		5.5				
Max Green Setting (Gmax), s	* 15	90.0		* 29	* 15	90.0		20.0				
Max Q Clear Time (g_c+11), s	2.5	32.2		11.9	3.5	76.1		10.9				
Green Ext Time (p_c), s	0.0	8.3		0.6	0.1	9.1		0.3				

Intersection Summary		
HCM 6th Ctrl Delay		23.6
HCM 6th LOS		C

Notes
 * HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.
 Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	2.5											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	10	100	10	10	190	10	50	0	10	0	0	10
Future Vol, veh/h	10	100	10	10	190	10	50	0	10	0	0	10
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	120	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	78	78	78	78	78	78	78	78	78	78	78	78
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	13	128	13	13	244	13	64	0	13	0	0	13

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	257	0	0	141	0	0	444	444	135	444	444	251
Stage 1	-	-	-	-	-	-	161	161	-	277	277	-
Stage 2	-	-	-	-	-	-	283	283	-	167	167	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1308	-	-	1442	-	-	524	508	914	524	508	788
Stage 1	-	-	-	-	-	-	841	765	-	729	681	-
Stage 2	-	-	-	-	-	-	724	677	-	835	760	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1308	-	-	1442	-	-	508	498	914	509	498	788
Mov Cap-2 Maneuver	-	-	-	-	-	-	508	498	-	509	498	-
Stage 1	-	-	-	-	-	-	832	757	-	721	675	-
Stage 2	-	-	-	-	-	-	706	671	-	814	752	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	0.6	0.4	12.6	9.6
HCM LOS			B	A

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	549	1308	-	-	1442	-	-	788
HCM Lane V/C Ratio	0.14	0.01	-	-	0.009	-	-	0.016
HCM Control Delay (s)	12.6	7.8	0	-	7.5	-	-	9.6
HCM Lane LOS	B	A	A	-	A	-	-	A
HCM 95th %tile Q(veh)	0.5	0	-	-	0	-	-	0.1

Intersection						
Int Delay, s/veh	1.9					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↘	↗	↘	↗	↗	↘
Traffic Vol, veh/h	40	60	190	1360	980	30
Future Vol, veh/h	40	60	190	1360	980	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Free	-	None	-	Yield
Storage Length	130	0	420	-	-	500
Veh in Median Storage, #	2	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	91	91	91	91	91	91
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	44	66	209	1495	1077	33

Major/Minor	Minor2	Major1	Major2		
Conflicting Flow All	2990	-	1077	0	-
Stage 1	1077	-	-	-	-
Stage 2	1913	-	-	-	-
Critical Hdwy	6.42	-	4.12	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	-	2.218	-	-
Pot Cap-1 Maneuver	~ 15	0	647	-	-
Stage 1	327	0	-	-	-
Stage 2	127	0	-	-	-
Platoon blocked, %				-	-
Mov Cap-1 Maneuver	~ 10	-	647	-	-
Mov Cap-2 Maneuver	102	-	-	-	-
Stage 1	221	-	-	-	-
Stage 2	127	-	-	-	-

Approach	EB	NB	SB
HCM Control Delay, s	64.7	1.6	0
HCM LOS	F		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	EBLn2	SBT	SBR
Capacity (veh/h)	647	-	102	-	-	-
HCM Lane V/C Ratio	0.323	-	0.431	-	-	-
HCM Control Delay (s)	13.2	-	64.7	0	-	-
HCM Lane LOS	B	-	F	A	-	-
HCM 95th %tile Q(veh)	1.4	-	1.8	-	-	-

Notes
 ~: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon

Intersection						
Int Delay, s/veh	5.8					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↘		↘	↗	↗	↘
Traffic Vol, veh/h	10	0	560	1090	910	90
Future Vol, veh/h	10	0	560	1090	910	90
Conflicting Peds, #/hr	1	1	1	0	0	1
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Free	-	None	-	Yield
Storage Length	-	-	450	-	-	500
Veh in Median Storage, #	2	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	10	0	577	1124	938	93

Major/Minor	Minor2	Major1	Major2		
Conflicting Flow All	3218	-	939	0	-
Stage 1	939	-	-	-	-
Stage 2	2279	-	-	-	-
Critical Hdwy	6.42	-	4.12	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	-	2.218	-	-
Pot Cap-1 Maneuver	11	0	730	-	-
Stage 1	380	0	-	-	-
Stage 2	83	0	-	-	-
Platoon blocked, %				-	-
Mov Cap-1 Maneuver	~ 2	-	729	-	-
Mov Cap-2 Maneuver	52	-	-	-	-
Stage 1	79	-	-	-	-
Stage 2	83	-	-	-	-

























Approach	EB	NB	SB
HCM Control Delay, s	90.6	8.8	0
HCM LOS	F		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	729	-	52	-	-
HCM Lane V/C Ratio	0.792	-	0.198	-	-
HCM Control Delay (s)	26	-	90.6	-	-
HCM Lane LOS	D	-	F	-	-
HCM 95th %tile Q(veh)	8	-	0.7	-	-

Notes
 ~: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon

HCM 6th Signalized Intersection Summary
1: Kuakini Hwy & Hualalai Rd

Phase 1 No Project Conditions
PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	230	50	60	80	50	250	40	670	100	200	750	350
Future Volume (veh/h)	230	50	60	80	50	250	40	670	100	200	750	350
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		0.99	0.99		0.98	1.00		1.00	1.00		0.96
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	245	53	42	85	53	164	43	713	0	213	798	259
Peak Hour Factor	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	382	249	197	412	71	221	196	1517		445	890	722
Arrive On Green	0.14	0.26	0.24	0.06	0.18	0.17	0.05	0.43	0.00	0.09	0.48	0.48
Sat Flow, veh/h	1781	961	761	1781	395	1221	1781	3647	0	1781	1870	1516
Grp Volume(v), veh/h	245	0	95	85	0	217	43	713	0	213	798	259
Grp Sat Flow(s),veh/h/ln	1781	0	1722	1781	0	1615	1781	1777	0	1781	1870	1516
Q Serve(g_s), s	10.9	0.0	4.5	3.9	0.0	13.2	1.4	14.8	0.0	6.5	40.3	11.1
Cycle Q Clear(g_c), s	10.9	0.0	4.5	3.9	0.0	13.2	1.4	14.8	0.0	6.5	40.3	11.1
Prop In Lane	1.00		0.44	1.00		0.76	1.00		0.00	1.00		1.00
Lane Grp Cap(c), veh/h	382	0	446	412	0	292	196	1517		445	890	722
V/C Ratio(X)	0.64	0.00	0.21	0.21	0.00	0.74	0.22	0.47		0.48	0.90	0.36
Avail Cap(c_a), veh/h	663	0	684	660	0	485	477	2273		638	1196	970
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
Uniform Delay (d), s/veh	27.5	0.0	30.3	31.1	0.0	40.6	21.4	21.2	0.0	14.4	24.7	17.1
Incr Delay (d2), s/veh	1.8	0.0	0.1	0.1	0.0	1.4	0.2	0.1	0.0	0.3	6.3	0.2
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	4.8	0.0	1.9	1.7	0.0	5.4	0.6	6.2	0.0	2.6	18.8	3.9
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	29.3	0.0	30.4	31.2	0.0	42.0	21.6	21.3	0.0	14.7	31.1	17.3
LnGrp LOS	C	A	C	C	A	D	C	C		B	C	B
Approach Vol, veh/h		340			302			756	A		1270	
Approach Delay, s/veh		29.6			39.0			21.3			25.5	
Approach LOS		C			D			C			C	
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	8.7	53.1	18.7	22.6	13.8	48.0	10.6	30.7				
Change Period (Y+Rc), s	* 5.2	5.5	* 5.2	5.5	* 5.2	5.5	* 5.2	5.5				
Max Green Setting (Gmax), s	* 20	64.5	* 30	29.5	* 20	64.5	* 20	39.5				
Max Q Clear Time (g_c+I1), s	3.4	42.3	12.9	15.2	8.5	16.8	5.9	6.5				
Green Ext Time (p_c), s	0.0	5.4	0.6	0.7	0.1	3.2	0.0	0.3				

Intersection Summary												
HCM 6th Ctrl Delay			26.4									
HCM 6th LOS			C									

Notes
* HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.
Unsignalized Delay for [NBR] is excluded from calculations of the approach delay and intersection delay.

Intersection						
Int Delay, s/veh	2					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	↵	↵	↵	↵	↵	↵
Traffic Vol, veh/h	33	88	490	27	53	880
Future Vol, veh/h	33	88	490	27	53	880
Conflicting Peds, #/hr	6	5	0	6	5	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Stop	-	None	-	None
Storage Length	0	40	-	-	120	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	34	91	505	28	55	907

Major/Minor	Minor1	Major1	Major2	Major3	Major4
Conflicting Flow All	1548	530	0	0	539
Stage 1	525	-	-	-	-
Stage 2	1023	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.12
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.218
Pot Cap-1 Maneuver	126	549	-	-	1029
Stage 1	593	-	-	-	-
Stage 2	347	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	118	543	-	-	1023
Mov Cap-2 Maneuver	118	-	-	-	-
Stage 1	589	-	-	-	-
Stage 2	327	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	22.4	0	0.5
HCM LOS	C		

Minor Lane/Major Mvmt	NBT	NBR	WBLn1	WBLn2	SBL	SBT
Capacity (veh/h)	-	-	118	543	1023	-
HCM Lane V/C Ratio	-	-	0.288	0.167	0.053	-
HCM Control Delay (s)	-	-	47.4	13	8.7	-
HCM Lane LOS	-	-	E	B	A	-
HCM 95th %tile Q(veh)	-	-	1.1	0.6	0.2	-

Intersection						
Int Delay, s/veh	5.6					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations	↑	↑	↑	↑	↑	↑
Traffic Vol, veh/h	140	120	130	20	30	170
Future Vol, veh/h	140	120	130	20	30	170
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	120	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	152	130	141	22	33	185

























Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	163	0	0 586 152
Stage 1	-	-	- 152 -
Stage 2	-	-	- 434 -
Critical Hdwy	4.12	-	- 6.42 6.22
Critical Hdwy Stg 1	-	-	- 5.42 -
Critical Hdwy Stg 2	-	-	- 5.42 -
Follow-up Hdwy	2.218	-	- 3.518 3.318
Pot Cap-1 Maneuver	1416	-	- 473 894
Stage 1	-	-	- 876 -
Stage 2	-	-	- 653 -
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1416	-	- 422 894
Mov Cap-2 Maneuver	-	-	- 422 -
Stage 1	-	-	- 782 -
Stage 2	-	-	- 653 -

Approach	EB	WB	SB
HCM Control Delay, s	4.2	0	11.6
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	1416	-	-	-	766
HCM Lane V/C Ratio	0.107	-	-	-	0.284
HCM Control Delay (s)	7.8	-	-	-	11.6
HCM Lane LOS	A	-	-	-	B
HCM 95th %tile Q(veh)	0.4	-	-	-	1.2

HCM 6th Signalized Intersection Summary
 4: Queen Kaahumanu Hwy & Nani Kailua Dr

Phase 1 No Project Conditions
 PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	90	70	20	40	50	120	40	1140	50	160	1270	90
Future Volume (veh/h)	90	70	20	40	50	120	40	1140	50	160	1270	90
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	92	71	0	41	51	0	41	1163	0	163	1296	0
Peak Hour Factor	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	163	90		114	127		173	1333		266	1355	
Arrive On Green	0.14	0.14	0.00	0.13	0.13	0.00	0.04	0.71	0.00	0.05	0.72	0.00
Sat Flow, veh/h	857	667	1585	561	998	1585	1781	1870	1585	1781	1870	1585
Grp Volume(v), veh/h	163	0	0	92	0	0	41	1163	0	163	1296	0
Grp Sat Flow(s),veh/h/ln	1524	0	1585	1559	0	1585	1781	1870	1585	1781	1870	1585
Q Serve(g_s), s	6.2	0.0	0.0	0.0	0.0	0.0	0.7	57.2	0.0	2.9	75.2	0.0
Cycle Q Clear(g_c), s	12.6	0.0	0.0	6.3	0.0	0.0	0.7	57.2	0.0	2.9	75.2	0.0
Prop In Lane	0.56		1.00	0.45		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	253	0		241	0		173	1333		266	1355	
V/C Ratio(X)	0.64	0.00		0.38	0.00		0.24	0.87		0.61	0.96	
Avail Cap(c_a), veh/h	318	0		426	0		344	1423		415	1423	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(l)	1.00	0.00	0.00	1.00	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	50.7	0.0	0.0	48.7	0.0	0.0	28.8	13.2	0.0	24.2	14.9	0.0
Incr Delay (d2), s/veh	3.0	0.0	0.0	1.0	0.0	0.0	0.7	6.0	0.0	2.3	14.4	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	5.0	0.0	0.0	2.7	0.0	0.0	0.8	21.0	0.0	3.2	29.5	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	53.7	0.0	0.0	49.7	0.0	0.0	29.5	19.2	0.0	26.5	29.3	0.0
LnGrp LOS	D	A		D	A		C	B		C	C	
Approach Vol, veh/h		163	A		92	A		1204	A		1459	A
Approach Delay, s/veh		53.7			49.7			19.5			29.0	
Approach LOS		D			D			B			C	
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	8.9	91.6		20.4	10.4	90.2		20.4				
Change Period (Y+Rc), s	* 5.2	6.0		* 5.5	* 5.2	6.0		5.5				
Max Green Setting (Gmax), s	* 15	90.0		* 29	* 15	90.0		20.0				
Max Q Clear Time (g_c+11), s	2.7	77.2		8.3	4.9	59.2		14.6				
Green Ext Time (p_c), s	0.0	8.5		0.4	0.3	11.8		0.4				

Intersection Summary		
HCM 6th Ctrl Delay		27.1
HCM 6th LOS		C

Notes
 * HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.
 Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	2.2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	10	120	20	20	120	10	20	0	10	10	0	10
Future Vol, veh/h	10	120	20	20	120	10	20	0	10	10	0	10
Conflicting Peds, #/hr	0	0	0	2	0	3	0	0	2	3	0	1
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	120	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	83	83	83	83	83	83	83	83	83	83	83	83
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	12	145	24	24	145	12	24	0	12	12	0	12

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	160	0	0	171	0	0	389	391	162	392	397	155
Stage 1	-	-	-	-	-	-	183	183	-	202	202	-
Stage 2	-	-	-	-	-	-	206	208	-	190	195	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1419	-	-	1406	-	-	570	545	883	567	540	891
Stage 1	-	-	-	-	-	-	819	748	-	800	734	-
Stage 2	-	-	-	-	-	-	796	730	-	812	739	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1415	-	-	1403	-	-	549	528	879	545	523	888
Mov Cap-2 Maneuver	-	-	-	-	-	-	549	528	-	545	523	-
Stage 1	-	-	-	-	-	-	810	740	-	790	719	-
Stage 2	-	-	-	-	-	-	771	715	-	791	731	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	0.5	1	11.1	10.5
HCM LOS			B	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	628	1415	-	-	1403	-	-	675
HCM Lane V/C Ratio	0.058	0.009	-	-	0.017	-	-	0.036
HCM Control Delay (s)	11.1	7.6	0	-	7.6	-	-	10.5
HCM Lane LOS	B	A	A	-	A	-	-	B
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.1

Intersection						
Int Delay, s/veh	0.8					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↙	↘	↙	↘	↘	↘
Traffic Vol, veh/h	20	120	100	1190	1310	30
Future Vol, veh/h	20	120	100	1190	1310	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Free	-	None	-	Yield
Storage Length	130	0	420	-	-	500
Veh in Median Storage, #	2	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	21	124	103	1227	1351	31

Major/Minor	Minor2	Major1	Major2		
Conflicting Flow All	2784	-	1351	0	-
Stage 1	1351	-	-	-	-
Stage 2	1433	-	-	-	-
Critical Hdwy	6.42	-	4.12	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	-	2.218	-	-
Pot Cap-1 Maneuver	21	0	509	-	-
Stage 1	241	0	-	-	-
Stage 2	220	0	-	-	-
Platoon blocked, %				-	-
Mov Cap-1 Maneuver	~ 17	-	509	-	-
Mov Cap-2 Maneuver	135	-	-	-	-
Stage 1	192	-	-	-	-
Stage 2	220	-	-	-	-

Approach	EB	NB	SB
HCM Control Delay, s	36.4	1.1	0
HCM LOS	E		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	EBLn2	SBT	SBR
Capacity (veh/h)	509	-	135	-	-	-
HCM Lane V/C Ratio	0.203	-	0.153	-	-	-
HCM Control Delay (s)	13.9	-	36.4	0	-	-
HCM Lane LOS	B	-	E	A	-	-
HCM 95th %tile Q(veh)	0.8	-	0.5	-	-	-

Notes
 ~: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon

Intersection						
Int Delay, s/veh	2.3					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↙		↙	↕	↕	↙
Traffic Vol, veh/h	20	0	310	1150	1090	70
Future Vol, veh/h	20	0	310	1150	1090	70
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Free	-	None	-	Yield
Storage Length	-	-	450	-	-	500
Veh in Median Storage, #	2	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	98	98	98	98	98	98
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	20	0	316	1173	1112	71

Major/Minor	Minor2	Major1	Major2		
Conflicting Flow All	2917	-	1112	0	-
Stage 1	1112	-	-	-	-
Stage 2	1805	-	-	-	-
Critical Hdwy	6.42	-	4.12	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	-	2.218	-	-
Pot Cap-1 Maneuver	~ 17	0	628	-	-
Stage 1	315	0	-	-	-
Stage 2	144	0	-	-	-
Platoon blocked, %				-	-
Mov Cap-1 Maneuver	~ 8	-	628	-	-
Mov Cap-2 Maneuver	98	-	-	-	-
Stage 1	157	-	-	-	-
Stage 2	144	-	-	-	-

























Approach	EB	NB	SB
HCM Control Delay, s	51.1	3.5	0
HCM LOS	F		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	628	-	98	-	-
HCM Lane V/C Ratio	0.504	-	0.208	-	-
HCM Control Delay (s)	16.4	-	51.1	-	-
HCM Lane LOS	C	-	F	-	-
HCM 95th %tile Q(veh)	2.8	-	0.7	-	-

Notes
 ~: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon

HCM 6th Signalized Intersection Summary
1: Kuakini Hwy & Hualalai Rd

Phase 1 Plus Project Conditions
AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	210	50	25	74	40	230	32	747	58	150	496	190
Future Volume (veh/h)	210	50	25	74	40	230	32	747	58	150	496	190
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	0.98		0.99	0.99		0.94	1.00		1.00	1.00		0.99
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	241	57	16	85	46	120	37	859	0	172	570	123
Peak Hour Factor	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	495	398	112	495	91	237	261	1140		346	693	581
Arrive On Green	0.15	0.28	0.26	0.07	0.21	0.19	0.05	0.32	0.00	0.10	0.37	0.37
Sat Flow, veh/h	1781	1402	393	1781	439	1144	1781	3647	0	1781	1870	1568
Grp Volume(v), veh/h	241	0	73	85	0	166	37	859	0	172	570	123
Grp Sat Flow(s),veh/h/ln	1781	0	1795	1781	0	1583	1781	1777	0	1781	1870	1568
Q Serve(g_s), s	7.1	0.0	2.2	2.6	0.0	6.8	1.0	15.8	0.0	4.3	20.1	3.9
Cycle Q Clear(g_c), s	7.1	0.0	2.2	2.6	0.0	6.8	1.0	15.8	0.0	4.3	20.1	3.9
Prop In Lane	1.00		0.22	1.00		0.72	1.00		0.00	1.00		1.00
Lane Grp Cap(c), veh/h	495	0	509	495	0	328	261	1140		346	693	581
V/C Ratio(X)	0.49	0.00	0.14	0.17	0.00	0.51	0.14	0.75		0.50	0.82	0.21
Avail Cap(c_a), veh/h	989	0	1012	880	0	674	681	3224		677	1697	1422
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
Uniform Delay (d), s/veh	16.8	0.0	19.6	20.0	0.0	26.0	16.7	22.1	0.0	15.4	20.7	15.6
Incr Delay (d2), s/veh	0.7	0.0	0.0	0.1	0.0	0.4	0.1	0.4	0.0	0.4	1.4	0.1
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	2.8	0.0	0.9	1.1	0.0	2.6	0.4	6.3	0.0	1.7	8.5	1.4
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	17.6	0.0	19.6	20.1	0.0	26.5	16.8	22.5	0.0	15.8	22.1	15.7
LnGrp LOS	B	A	B	C	A	C	B	C		B	C	B
Approach Vol, veh/h		314			251			896	A		865	
Approach Delay, s/veh		18.1			24.3			22.3			19.9	
Approach LOS		B			C			C			B	
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	7.8	31.0	14.9	19.1	11.5	27.3	9.3	24.6				
Change Period (Y+Rc), s	* 5.2	5.5	* 5.2	5.5	* 5.2	5.5	* 5.2	5.5				
Max Green Setting (Gmax), s	* 20	64.5	* 30	29.5	* 20	64.5	* 20	39.5				
Max Q Clear Time (g_c+1), s	3.0	22.1	9.1	8.8	6.3	17.8	4.6	4.2				
Green Ext Time (p_c), s	0.0	3.4	0.7	0.6	0.1	4.0	0.0	0.2				

Intersection Summary												
HCM 6th Ctrl Delay				21.1								
HCM 6th LOS				C								

Notes
 * HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.
 Unsignalized Delay for [NBR] is excluded from calculations of the approach delay and intersection delay.

Intersection						
Int Delay, s/veh	3.1					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	↑	↑	↑	↑	↑	↑
Traffic Vol, veh/h	7	80	740	69	172	360
Future Vol, veh/h	7	80	740	69	172	360
Conflicting Peds, #/hr	1	1	0	1	1	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Stop	-	None	-	None
Storage Length	0	40	-	-	120	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	81	81	81	81	81	81
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	9	99	914	85	212	444

Major/Minor	Minor1	Major1	Major2	Major2	Major2
Conflicting Flow All	1827	959	0	0	1000
Stage 1	958	-	-	-	-
Stage 2	869	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.12
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.218
Pot Cap-1 Maneuver	84	312	-	-	692
Stage 1	373	-	-	-	-
Stage 2	410	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	58	311	-	-	691
Mov Cap-2 Maneuver	58	-	-	-	-
Stage 1	373	-	-	-	-
Stage 2	284	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	26.4	0	4
HCM LOS	D		

Minor Lane/Major Mvmt	NBT	NBRWBLn1WBLn2	SBL	SBT
Capacity (veh/h)	-	-	58	311
HCM Lane V/C Ratio	-	-	0.149	0.318
HCM Control Delay (s)	-	-	77.6	21.9
HCM Lane LOS	-	-	F	C
HCM 95th %tile Q(veh)	-	-	0.5	1.3

Intersection						
Int Delay, s/veh	4.7					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations	↑	↑	↑	↑	↑	↑
Traffic Vol, veh/h	88	100	230	34	55	114
Future Vol, veh/h	88	100	230	34	55	114
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	120	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	96	109	250	37	60	124

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	287	0	0
Stage 1	-	-	-
Stage 2	-	-	-
Critical Hdwy	4.12	-	-
Critical Hdwy Stg 1	-	-	-
Critical Hdwy Stg 2	-	-	-
Follow-up Hdwy	2.218	-	-
Pot Cap-1 Maneuver	1275	-	-
Stage 1	-	-	-
Stage 2	-	-	-
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1275	-	-
Mov Cap-2 Maneuver	-	-	-
Stage 1	-	-	-
Stage 2	-	-	-

























Approach	EB	WB	SB
HCM Control Delay, s	3.8	0	13.2
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	1275	-	-	-	623
HCM Lane V/C Ratio	0.075	-	-	-	0.295
HCM Control Delay (s)	8.1	-	-	-	13.2
HCM Lane LOS	A	-	-	-	B
HCM 95th %tile Q(veh)	0.2	-	-	-	1.2

HCM 6th Signalized Intersection Summary
4: Queen Kaahumanu Hwy & Nani Kailua Dr

Phase 1 Plus Project Conditions

AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	80	32	30	70	65	260	30	1250	40	90	890	114
Future Volume (veh/h)	80	32	30	70	65	260	30	1250	40	90	890	114
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	0.99		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	83	33	0	73	68	0	31	1302	0	94	927	0
Peak Hour Factor	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	166	48		136	92		414	1361		189	1385	
Arrive On Green	0.12	0.12	0.00	0.12	0.12	0.00	0.04	0.73	0.00	0.05	0.74	0.00
Sat Flow, veh/h	927	386	1585	784	799	1585	1781	1870	1585	1781	1870	1585
Grp Volume(v), veh/h	116	0	0	141	0	0	31	1302	0	94	927	0
Grp Sat Flow(s),veh/h/ln	1313	0	1585	1584	0	1585	1781	1870	1585	1781	1870	1585
Q Serve(g_s), s	0.3	0.0	0.0	0.0	0.0	0.0	0.5	75.4	0.0	1.5	30.8	0.0
Cycle Q Clear(g_c), s	10.7	0.0	0.0	10.4	0.0	0.0	0.5	75.4	0.0	1.5	30.8	0.0
Prop In Lane	0.72		1.00	0.52		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	213	0		228	0		414	1361		189	1385	
V/C Ratio(X)	0.54	0.00		0.62	0.00		0.07	0.96		0.50	0.67	
Avail Cap(c_a), veh/h	292	0		431	0		592	1426		344	1426	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	0.00	1.00	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	51.0	0.0	0.0	51.8	0.0	0.0	7.3	14.8	0.0	32.2	8.1	0.0
Incr Delay (d2), s/veh	2.1	0.0	0.0	2.7	0.0	0.0	0.1	14.5	0.0	2.0	1.2	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	3.5	0.0	0.0	4.3	0.0	0.0	0.2	29.4	0.0	2.0	9.9	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	53.2	0.0	0.0	54.5	0.0	0.0	7.4	29.3	0.0	34.2	9.2	0.0
LnGrp LOS	D	A		D	A		A	C		C	A	
Approach Vol, veh/h		116	A		141	A		1333	A		1021	A
Approach Delay, s/veh		53.2			54.5			28.8			11.5	
Approach LOS		D			D			C			B	
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	8.4	93.4		18.9	10.0	91.8		18.9				
Change Period (Y+Rc), s	* 5.2	6.0		* 5.5	* 5.2	6.0		5.5				
Max Green Setting (Gmax), s	* 15	90.0		* 29	* 15	90.0		20.0				
Max Q Clear Time (g_c+11), s	2.5	32.8		12.4	3.5	77.4		12.7				
Green Ext Time (p_c), s	0.0	8.3		0.6	0.1	8.4		0.3				

Intersection Summary		
HCM 6th Ctrl Delay		24.5
HCM 6th LOS		C

Notes
 * HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.
 Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	2.3											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	10	125	10	10	252	10	50	0	10	0	0	10
Future Vol, veh/h	10	125	10	10	252	10	50	0	10	0	0	10
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	120	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	78	78	78	78	78	78	78	78	78	78	78	78
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	13	160	13	13	323	13	64	0	13	0	0	13

Major/Minor	Major1	Major2			Minor1			Minor2				
Conflicting Flow All	336	0	0	173	0	0	555	555	167	555	555	330
Stage 1	-	-	-	-	-	-	193	193	-	356	356	-
Stage 2	-	-	-	-	-	-	362	362	-	199	199	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1223	-	-	1404	-	-	442	440	877	442	440	712
Stage 1	-	-	-	-	-	-	809	741	-	661	629	-
Stage 2	-	-	-	-	-	-	657	625	-	803	736	-
Platoon blocked, %		-	-	-	-	-						
Mov Cap-1 Maneuver	1223	-	-	1404	-	-	427	431	877	428	431	712
Mov Cap-2 Maneuver	-	-	-	-	-	-	427	431	-	428	431	-
Stage 1	-	-	-	-	-	-	799	732	-	653	623	-
Stage 2	-	-	-	-	-	-	639	619	-	782	727	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	0.5	0.3	14.2	10.1
HCM LOS			B	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	467	1223	-	-	1404	-	-	712
HCM Lane V/C Ratio	0.165	0.01	-	-	0.009	-	-	0.018
HCM Control Delay (s)	14.2	8	0	-	7.6	-	-	10.1
HCM Lane LOS	B	A	A	-	A	-	-	B
HCM 95th %tile Q(veh)	0.6	0	-	-	0	-	-	0.1

Intersection						
Int Delay, s/veh	2.7					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↘	↗	↘	↗	↗	↘
Traffic Vol, veh/h	40	85	252	1360	980	30
Future Vol, veh/h	40	85	252	1360	980	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Free	-	None	-	Yield
Storage Length	130	0	420	-	-	500
Veh in Median Storage, #	2	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	91	91	91	91	91	91
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	44	93	277	1495	1077	33

Major/Minor	Minor2	Major1	Major2		
Conflicting Flow All	3126	-	1077	0	-
Stage 1	1077	-	-	-	-
Stage 2	2049	-	-	-	-
Critical Hdwy	6.42	-	4.12	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	-	2.218	-	-
Pot Cap-1 Maneuver	~ 12	0	647	-	-
Stage 1	327	0	-	-	-
Stage 2	108	0	-	-	-
Platoon blocked, %				-	-
Mov Cap-1 Maneuver	~ 7	-	647	-	-
Mov Cap-2 Maneuver	86	-	-	-	-
Stage 1	187	-	-	-	-
Stage 2	108	-	-	-	-

Approach	EB	NB	SB
HCM Control Delay, s	84.3	2.3	0
HCM LOS	F		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	EBLn2	SBT	SBR
Capacity (veh/h)	647	-	86	-	-	-
HCM Lane V/C Ratio	0.428	-	0.511	-	-	-
HCM Control Delay (s)	14.7	-	84.3	0	-	-
HCM Lane LOS	B	-	F	A	-	-
HCM 95th %tile Q(veh)	2.1	-	2.2	-	-	-

Notes
 ~: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon

Intersection						
Int Delay, s/veh	5.7					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↘		↘	↗	↗	↘
Traffic Vol, veh/h	8	0	551	1145	932	86
Future Vol, veh/h	8	0	551	1145	932	86
Conflicting Peds, #/hr	1	1	1	0	0	1
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Free	-	None	-	Yield
Storage Length	-	-	450	-	-	500
Veh in Median Storage, #	2	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	8	0	568	1180	961	89

Major/Minor	Minor2	Major1	Major2		
Conflicting Flow All	3279	-	962	0	-
Stage 1	962	-	-	-	-
Stage 2	2317	-	-	-	-
Critical Hdwy	6.42	-	4.12	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	-	2.218	-	-
Pot Cap-1 Maneuver	10	0	715	-	-
Stage 1	371	0	-	-	-
Stage 2	79	0	-	-	-
Platoon blocked, %				-	-
Mov Cap-1 Maneuver	~ 2	-	714	-	-
Mov Cap-2 Maneuver	50	-	-	-	-
Stage 1	76	-	-	-	-
Stage 2	79	-	-	-	-

Approach	EB	NB	SB
HCM Control Delay, s	90.7	8.7	0
HCM LOS	F		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	714	-	50	-	-
HCM Lane V/C Ratio	0.796	-	0.165	-	-
HCM Control Delay (s)	26.7	-	90.7	-	-
HCM Lane LOS	D	-	F	-	-
HCM 95th %tile Q(veh)	8.1	-	0.5	-	-

Notes
 ~: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon

Intersection						
Int Delay, s/veh	1.7					
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Vol, veh/h	120	35	62	250	14	25
Future Vol, veh/h	120	35	62	250	14	25
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	130	38	67	272	15	27

























Major/Minor	Major1	Major2	Minor1	Minor2	Minor3
Conflicting Flow All	0	0	168	0	555 149
Stage 1	-	-	-	-	149 -
Stage 2	-	-	-	-	406 -
Critical Hdwy	-	-	4.12	-	6.42 6.22
Critical Hdwy Stg 1	-	-	-	-	5.42 -
Critical Hdwy Stg 2	-	-	-	-	5.42 -
Follow-up Hdwy	-	-	2.218	-	3.518 3.318
Pot Cap-1 Maneuver	-	-	1410	-	493 898
Stage 1	-	-	-	-	879 -
Stage 2	-	-	-	-	673 -
Platoon blocked, %	-	-	-	-	-
Mov Cap-1 Maneuver	-	-	1410	-	465 898
Mov Cap-2 Maneuver	-	-	-	-	465 -
Stage 1	-	-	-	-	879 -
Stage 2	-	-	-	-	635 -

Approach	EB	WB	NB
HCM Control Delay, s	0	1.5	10.7
HCM LOS			B

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	673	-	-	1410	-
HCM Lane V/C Ratio	0.063	-	-	0.048	-
HCM Control Delay (s)	10.7	-	-	7.7	0
HCM Lane LOS	B	-	-	A	A
HCM 95th %tile Q(veh)	0.2	-	-	0.1	-

HCM 6th Signalized Intersection Summary
1: Kuakini Hwy & Hualalai Rd

Phase 1 Plus Project Conditions
PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	230	50	62	78	50	250	43	712	96	200	778	350
Future Volume (veh/h)	230	50	62	78	50	250	43	712	96	200	778	350
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		0.99	0.98		0.98	1.00		1.00	1.00		0.96
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	245	53	37	83	53	146	46	757	0	213	828	278
Peak Hour Factor	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	382	254	178	395	73	201	192	1578		438	916	743
Arrive On Green	0.14	0.25	0.24	0.06	0.17	0.16	0.05	0.44	0.00	0.09	0.49	0.49
Sat Flow, veh/h	1781	1020	712	1781	432	1189	1781	3647	0	1781	1870	1517
Grp Volume(v), veh/h	245	0	90	83	0	199	46	757	0	213	828	278
Grp Sat Flow(s),veh/h/ln	1781	0	1731	1781	0	1621	1781	1777	0	1781	1870	1517
Q Serve(g_s), s	11.3	0.0	4.4	4.0	0.0	12.4	1.4	15.9	0.0	6.4	42.9	12.1
Cycle Q Clear(g_c), s	11.3	0.0	4.4	4.0	0.0	12.4	1.4	15.9	0.0	6.4	42.9	12.1
Prop In Lane	1.00		0.41	1.00		0.73	1.00		0.00	1.00		1.00
Lane Grp Cap(c), veh/h	382	0	432	395	0	275	192	1578		438	916	743
V/C Ratio(X)	0.64	0.00	0.21	0.21	0.00	0.72	0.24	0.48		0.49	0.90	0.37
Avail Cap(c_a), veh/h	648	0	670	635	0	474	463	2215		627	1166	946
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	1.00	0.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
Uniform Delay (d), s/veh	28.9	0.0	31.7	33.0	0.0	42.2	21.8	20.8	0.0	14.2	24.7	16.9
Incr Delay (d2), s/veh	1.8	0.0	0.1	0.1	0.0	1.4	0.2	0.1	0.0	0.3	7.6	0.2
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	5.0	0.0	1.9	1.7	0.0	5.1	0.6	6.6	0.0	2.6	20.3	4.2
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	30.7	0.0	31.8	33.0	0.0	43.5	22.0	20.9	0.0	14.5	32.4	17.0
LnGrp LOS	C	A	C	C	A	D	C	C		B	C	B
Approach Vol, veh/h		335			282			803	A		1319	
Approach Delay, s/veh		31.0			40.5			21.0			26.3	
Approach LOS		C			D			C			C	
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	8.9	55.9	19.2	21.9	13.8	51.0	10.7	30.4				
Change Period (Y+Rc), s	* 5.2	5.5	* 5.2	5.5	* 5.2	5.5	* 5.2	5.5				
Max Green Setting (Gmax), s	* 20	64.5	* 30	29.5	* 20	64.5	* 20	39.5				
Max Q Clear Time (g_c+1), s	3.4	44.9	13.3	14.4	8.4	17.9	6.0	6.4				
Green Ext Time (p_c), s	0.0	5.5	0.6	0.6	0.1	3.4	0.0	0.3				

Intersection Summary												
HCM 6th Ctrl Delay			26.7									
HCM 6th LOS			C									

Notes
 * HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.
 Unsignalized Delay for [NBR] is excluded from calculations of the approach delay and intersection delay.

Intersection						
Int Delay, s/veh	2.4					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	↵	↵	↵	↵	↵	↵
Traffic Vol, veh/h	28	129	490	23	80	880
Future Vol, veh/h	28	129	490	23	80	880
Conflicting Peds, #/hr	6	5	0	6	5	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Stop	-	None	-	None
Storage Length	0	40	-	-	120	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	29	133	505	24	82	907

Major/Minor	Minor1	Major1	Major2		
Conflicting Flow All	1600	528	0	0	535
Stage 1	523	-	-	-	-
Stage 2	1077	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.12
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.218
Pot Cap-1 Maneuver	117	550	-	-	1033
Stage 1	595	-	-	-	-
Stage 2	327	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	106	544	-	-	1027
Mov Cap-2 Maneuver	106	-	-	-	-
Stage 1	591	-	-	-	-
Stage 2	299	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	20.4	0	0.7
HCM LOS	C		

Minor Lane/Major Mvmt	NBT	NBR	WBLn1	WBLn2	SBL	SBT
Capacity (veh/h)	-	-	106	544	1027	-
HCM Lane V/C Ratio	-	-	0.272	0.244	0.08	-
HCM Control Delay (s)	-	-	51.2	13.7	8.8	-
HCM Lane LOS	-	-	F	B	A	-
HCM 95th %tile Q(veh)	-	-	1	1	0.3	-

Intersection						
Int Delay, s/veh	5.8					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations	↑	↑	↑	↑	↑	↑
Traffic Vol, veh/h	136	120	130	42	44	168
Future Vol, veh/h	136	120	130	42	44	168
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	120	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	148	130	141	46	48	183

























Major/Minor	Major1	Major2	Minor2		
Conflicting Flow All	187	0	-	0	590 164
Stage 1	-	-	-	-	164 -
Stage 2	-	-	-	-	426 -
Critical Hdwy	4.12	-	-	-	6.42 6.22
Critical Hdwy Stg 1	-	-	-	-	5.42 -
Critical Hdwy Stg 2	-	-	-	-	5.42 -
Follow-up Hdwy	2.218	-	-	-	3.518 3.318
Pot Cap-1 Maneuver	1387	-	-	-	470 881
Stage 1	-	-	-	-	865 -
Stage 2	-	-	-	-	659 -
Platoon blocked, %		-	-	-	
Mov Cap-1 Maneuver	1387	-	-	-	420 881
Mov Cap-2 Maneuver	-	-	-	-	420 -
Stage 1	-	-	-	-	772 -
Stage 2	-	-	-	-	659 -

Approach	EB	WB	SB
HCM Control Delay, s	4.2	0	12.4
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	1387	-	-	-	718
HCM Lane V/C Ratio	0.107	-	-	-	0.321
HCM Control Delay (s)	7.9	-	-	-	12.4
HCM Lane LOS	A	-	-	-	B
HCM 95th %tile Q(veh)	0.4	-	-	-	1.4

HCM 6th Signalized Intersection Summary
4: Queen Kaahumanu Hwy & Nani Kailua Dr

Phase 1 Plus Project Conditions
PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	105	73	20	40	52	120	40	1140	50	160	1270	100
Future Volume (veh/h)	105	73	20	40	52	120	40	1140	50	160	1270	100
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	107	74	0	41	53	0	41	1163	0	163	1296	0
Peak Hour Factor	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	176	90		119	139		159	1317		253	1341	
Arrive On Green	0.15	0.15	0.00	0.14	0.14	0.00	0.04	0.70	0.00	0.05	0.72	0.00
Sat Flow, veh/h	885	612	1585	557	995	1585	1781	1870	1585	1781	1870	1585
Grp Volume(v), veh/h	181	0	0	94	0	0	41	1163	0	163	1296	0
Grp Sat Flow(s),veh/h/ln	1498	0	1585	1552	0	1585	1781	1870	1585	1781	1870	1585
Q Serve(g_s), s	8.2	0.0	0.0	0.0	0.0	0.0	0.8	61.0	0.0	3.2	80.1	0.0
Cycle Q Clear(g_c), s	14.8	0.0	0.0	6.6	0.0	0.0	0.8	61.0	0.0	3.2	80.1	0.0
Prop In Lane	0.59		1.00	0.44		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	267	0		258	0		159	1317		253	1341	
V/C Ratio(X)	0.68	0.00		0.36	0.00		0.26	0.88		0.64	0.97	
Avail Cap(c_a), veh/h	303	0		410	0		322	1373		394	1373	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(l)	1.00	0.00	0.00	1.00	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	51.9	0.0	0.0	49.1	0.0	0.0	31.6	14.5	0.0	26.6	16.4	0.0
Incr Delay (d2), s/veh	5.1	0.0	0.0	0.9	0.0	0.0	0.9	7.0	0.0	2.7	16.8	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	5.9	0.0	0.0	2.8	0.0	0.0	0.9	23.3	0.0	3.5	32.9	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	57.0	0.0	0.0	49.9	0.0	0.0	32.5	21.5	0.0	29.3	33.2	0.0
LnGrp LOS	E	A		D	A		C	C		C	C	
Approach Vol, veh/h		181	A		94	A		1204	A		1459	A
Approach Delay, s/veh		57.0			49.9			21.9			32.7	
Approach LOS		E			D			C			C	
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	9.0	93.8		22.5	10.6	92.2		22.5				
Change Period (Y+Rc), s	* 5.2	6.0		* 5.5	* 5.2	6.0		5.5				
Max Green Setting (Gmax), s	* 15	90.0		* 29	* 15	90.0		20.0				
Max Q Clear Time (g_c+11), s	2.8	82.1		8.6	5.2	63.0		16.8				
Green Ext Time (p_c), s	0.0	5.7		0.4	0.3	11.2		0.3				

Intersection Summary		
HCM 6th Ctrl Delay		30.3
HCM 6th LOS		C

Notes
 * HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.
 Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	10	159	20	20	146	10	20	0	10	10	0	10
Future Vol, veh/h	10	159	20	20	146	10	20	0	10	10	0	10
Conflicting Peds, #/hr	0	0	0	2	0	3	0	0	2	3	0	1
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	120	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	83	83	83	83	83	83	83	83	83	83	83	83
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	12	192	24	24	176	12	24	0	12	12	0	12

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	191	0	0	218	0	0	467	469	209	470	475	186
Stage 1	-	-	-	-	-	-	230	230	-	233	233	-
Stage 2	-	-	-	-	-	-	237	239	-	237	242	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1383	-	-	1352	-	-	506	492	831	504	488	856
Stage 1	-	-	-	-	-	-	773	714	-	770	712	-
Stage 2	-	-	-	-	-	-	766	708	-	766	705	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1379	-	-	1349	-	-	487	476	827	483	472	853
Mov Cap-2 Maneuver	-	-	-	-	-	-	487	476	-	483	472	-
Stage 1	-	-	-	-	-	-	764	705	-	760	697	-
Stage 2	-	-	-	-	-	-	741	693	-	745	697	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	0.4	0.9	11.8	11.1
HCM LOS			B	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	564	1379	-	-	1349	-	-	617
HCM Lane V/C Ratio	0.064	0.009	-	-	0.018	-	-	0.039
HCM Control Delay (s)	11.8	7.6	0	-	7.7	-	-	11.1
HCM Lane LOS	B	A	A	-	A	-	-	B
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.1

Intersection						
Int Delay, s/veh	1					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↙	↘	↙	↘	↘	↘
Traffic Vol, veh/h	20	159	126	1190	1310	30
Future Vol, veh/h	20	159	126	1190	1310	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Free	-	None	-	Yield
Storage Length	130	0	420	-	-	500
Veh in Median Storage, #	2	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	21	164	130	1227	1351	31

Major/Minor	Minor2	Major1	Major2		
Conflicting Flow All	2838	-	1351	0	-
Stage 1	1351	-	-	-	-
Stage 2	1487	-	-	-	-
Critical Hdwy	6.42	-	4.12	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	-	2.218	-	-
Pot Cap-1 Maneuver	~ 19	0	509	-	-
Stage 1	241	0	-	-	-
Stage 2	207	0	-	-	-
Platoon blocked, %				-	-
Mov Cap-1 Maneuver	~ 14	-	509	-	-
Mov Cap-2 Maneuver	126	-	-	-	-
Stage 1	180	-	-	-	-
Stage 2	207	-	-	-	-

Approach	EB	NB	SB
HCM Control Delay, s	39.1	1.4	0
HCM LOS	E		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	EBLn2	SBT	SBR
Capacity (veh/h)	509	-	126	-	-	-
HCM Lane V/C Ratio	0.255	-	0.164	-	-	-
HCM Control Delay (s)	14.5	-	39.1	0	-	-
HCM Lane LOS	B	-	E	A	-	-
HCM 95th %tile Q(veh)	1	-	0.6	-	-	-

Notes
 ~: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon

Intersection						
Int Delay, s/veh	2.3					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	↘		↘	↗	↗	↘
Traffic Vol, veh/h	18	0	306	1173	1125	68
Future Vol, veh/h	18	0	306	1173	1125	68
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	Free	-	None	-	Yield
Storage Length	-	-	450	-	-	500
Veh in Median Storage, #	2	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	98	98	98	98	98	98
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	18	0	312	1197	1148	69

Major/Minor	Minor2	Major1	Major2		
Conflicting Flow All	2969	-	1148	0	-
Stage 1	1148	-	-	-	-
Stage 2	1821	-	-	-	-
Critical Hdwy	6.42	-	4.12	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	-	2.218	-	-
Pot Cap-1 Maneuver	~ 16	0	609	-	-
Stage 1	302	0	-	-	-
Stage 2	141	0	-	-	-
Platoon blocked, %				-	-
Mov Cap-1 Maneuver	~ 8	-	609	-	-
Mov Cap-2 Maneuver	94	-	-	-	-
Stage 1	147	-	-	-	-
Stage 2	141	-	-	-	-

Approach	EB	NB	SB
HCM Control Delay, s	52.4	3.5	0
HCM LOS	F		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	609	-	94	-	-
HCM Lane V/C Ratio	0.513	-	0.195	-	-
HCM Control Delay (s)	17	-	52.4	-	-
HCM Lane LOS	C	-	F	-	-
HCM 95th %tile Q(veh)	2.9	-	0.7	-	-

Notes
 ~: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon

Intersection						
Int Delay, s/veh	2					
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Vol, veh/h	150	14	26	150	22	39
Future Vol, veh/h	150	14	26	150	22	39
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	163	15	28	163	24	42

Major/Minor	Major1	Major2	Minor1	Minor2	Minor3
Conflicting Flow All	0	0	178	0	390
Stage 1	-	-	-	-	171
Stage 2	-	-	-	-	219
Critical Hdwy	-	-	4.12	-	6.42
Critical Hdwy Stg 1	-	-	-	-	5.42
Critical Hdwy Stg 2	-	-	-	-	5.42
Follow-up Hdwy	-	-	2.218	-	3.518
Pot Cap-1 Maneuver	-	-	1398	-	614
Stage 1	-	-	-	-	859
Stage 2	-	-	-	-	817
Platoon blocked, %	-	-	-	-	-
Mov Cap-1 Maneuver	-	-	1398	-	600
Mov Cap-2 Maneuver	-	-	-	-	600
Stage 1	-	-	-	-	859
Stage 2	-	-	-	-	799

Approach	EB	WB	NB
HCM Control Delay, s	0	1.1	10.3
HCM LOS			B

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	750	-	-	1398	-
HCM Lane V/C Ratio	0.088	-	-	0.02	-
HCM Control Delay (s)	10.3	-	-	7.6	0
HCM Lane LOS	B	-	-	A	A
HCM 95th %tile Q(veh)	0.3	-	-	0.1	-

APPENDIX C: 4-HOUR SIGNAL WARRANT WORKSHEETS





Major Street Kuakini Hwy
 Minor Street Project Driveway

Project 0
 Scenario Existing
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	0	242	0	110
Through	1,715	2,770	0	0
Right	83	0	0	276
Total	450	753	0	97

Major Street Direction

x North/South
 East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 2
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 38.7
 Approach with Worst Case Delay WB
 Total Vehicles on Approach 97

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Existing	1	97	1,299
Limiting Value	5	150	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Kuakini Hwy
 Minor Street Project Driveway

Project _____
 Scenario Existing
 Peak Hour AM+PM Peak Periods


Turn Movement Volumes

	NB	SB	EB	WB
Left	0	242	0	110
Through	1,715	2,770	0	0
Right	83	0	0	276
Total	450	753	0	97

Major Street Direction

x	North/South
	East/West

Warrant 3B, Peak Hour



* Note: 150 vph applies as the lower threshold volume for a minor-street approach with two or more lanes and 100 vph applies as the lower threshold volume for a minor-street approach with one lane.

Source: *California Manual on Uniform Traffic Control Devices*, Caltrans, 2014

	Major Street	Minor Street	Warrant Met
	Kuakini Hwy	Project Driveway	
Number of Approach Lanes	1	2	<u>NO</u>
Traffic Volume (VPH) *	1,203	97	
* Note: Traffic Volume for Major Street is Total Volume of Both Approches. Traffic Volume for Minor Street is the Volume of High Volume Approach.			



Major Street Queen Kaahumanu Hwy
 Minor Street Hualalai Rd

Project 0
 Scenario Existing
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	486	0	61	0
Through	3,857	3,419	0	0
Right	0	71	291	0
Total	1,086	873	88	0

Major Street Direction

x North/South
 East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 2
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 32.9
 Approach with Worst Case Delay EB
 Total Vehicles on Approach 88

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Existing	0.8	88	2,046
Limiting Value	5	150	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Queen Kaahumanu Hwy
 Minor Street Hualalai Rd


Project _____
 Scenario Existing
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	486	0	61	0
Through	3,857	3,419	0	0
Right	0	71	291	0
Total	1,086	873	88	0

Major Street Direction

x	North/South
	East/West



	Major Street	Minor Street	Warrant Met
	Queen Kaahumanu Hwy	Hualalai Rd	
Number of Approach Lanes	2	2	<u>NO</u>
Traffic Volume (VPH) *	1,958	88	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.



Major Street Queen Kaahumanu Hwy
 Minor Street Kuakini Hwy

Project 0
 Scenario Existing
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	1,295	0	29	0
Through	3,459	2,996	0	0
Right	0	202	2	0
Total	1,189	800	8	0

Major Street Direction

x North/South
 East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 1
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 38.4
 Approach with Worst Case Delay EB
 Total Vehicles on Approach 8

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Existing	0.1	8	1,996
Limiting Value	4	100	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Queen Kaahumanu Hwy
 Minor Street Kuakini Hwy


Project _____
 Scenario Existing
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	1,295	0	29	0
Through	3,459	2,996	0	0
Right	0	202	2	0
Total	1,189	800	8	0

Major Street Direction

x	North/South
	East/West



	Major Street	Minor Street	Warrant Met
	Queen Kaahumanu Hwy	Kuakini Hwy	
Number of Approach Lanes	2	1	<u>NO</u>
Traffic Volume (VPH) *	1,988	8	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.



Major Street Kuakini Hwy
 Minor Street Project Driveway

Project 0
 Scenario Phase 1
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	0	242	0	110
Through	2,030	3,270	0	0
Right	83	0	0	276
Total	528	878	0	97

Major Street Direction

x North/South
 East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 2
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 54.4
 Approach with Worst Case Delay WB
 Total Vehicles on Approach 97

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Baseline	1.5	97	1,503
Limiting Value	5	150	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Kuakini Hwy
 Minor Street Project Driveway

Project 0
 Scenario Phase 1
 Peak Hour AM+PM Peak Periods


Turn Movement Volumes

	NB	SB	EB	WB
Left	0	242	0	110
Through	2,030	3,270	0	0
Right	83	0	0	276
Total	528	878	0	97

Major Street Direction

x North/South
 East/West

Warrant 3B, Peak Hour



* Note: 150 vph applies as the lower threshold volume for a minor-street approach with two or more lanes and 100 vph applies as the lower threshold volume for a minor-street approach with one lane.

Source: *California Manual on Uniform Traffic Control Devices*, Caltrans, 2014

	Major Street	Minor Street	Warrant Met
	Kuakini Hwy	Project Driveway	
Number of Approach Lanes	1	2	<u>NO</u>
Traffic Volume (VPH) *	1,406	97	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.



Major Street Queen Kaahumanu Hwy
 Minor Street Hualalai Rd

Project 0
 Scenario Phase 1
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	550	0	70	0
Through	5,070	4,490	0	0
Right	0	80	330	0
Total	1,405	1,143	100	0

Major Street Direction

x North/South
 East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 2
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 64.7
 Approach with Worst Case Delay EB
 Total Vehicles on Approach 100

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Baseline	1.8	100	2,648
Limiting Value	5	150	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Queen Kaahumanu Hwy
 Minor Street Hualalai Rd


Project 0
 Scenario Phase 1
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	550	0	70	0
Through	5,070	4,490	0	0
Right	0	80	330	0
Total	1,405	1,143	100	0

Major Street Direction

x North/South
 East/West



	Major Street	Minor Street	Warrant Met
	Queen Kaahumanu Hwy	Hualalai Rd	
Number of Approach Lanes	2	2	<u>NO</u>
Traffic Volume (VPH) *	2,548	100	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.



Major Street Kuakini Hwy
 Minor Street Project Driveway

Project _____
 Scenario Phase 1 +P
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	0	427	0	93
Through	2,030	3,270	0	0
Right	59	0	0	411
Total	522	924	0	126

Major Street Direction

x	North/South
	East/West

Intersection Geometry

Number of Approach Lanes for Minor Street	2
Total Approaches	3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle)	77.6
Approach with Worst Case Delay	WB
Total Vehicles on Approach	126

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Baseline +P	2.7	126	1,572
Limiting Value	5	150	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Kuakini Hwy
 Minor Street Project Driveway

Project _____
 Scenario Phase 1 +P
 Peak Hour AM+PM Peak Periods


Turn Movement Volumes

	NB	SB	EB	WB
Left	0	427	0	93
Through	2,030	3,270	0	0
Right	59	0	0	411
Total	522	924	0	126

Major Street Direction

x North/South
 _____ East/West

Warrant 3B, Peak Hour



* Note: 150 vph applies as the lower threshold volume for a minor-street approach with two or more lanes and 100 vph applies as the lower threshold volume for a minor-street approach with one lane.

Source: *California Manual on Uniform Traffic Control Devices*, Caltrans, 2014

	Major Street	Minor Street	Warrant Met
	Kuakini Hwy	Project Driveway	
Number of Approach Lanes	1	2	<u>NO</u>
Traffic Volume (VPH) *	1,447	126	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.



Major Street Queen Kaahumanu Hwy
 Minor Street Hualalai Rd

Project _____
 Scenario Phase 1 +P
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	726	0	70	0
Through	5,070	4,490	0	0
Right	0	80	458	0
Total	1,449	1,143	132	0

Major Street Direction

x North/South
 _____ East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 2
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 89.3
 Approach with Worst Case Delay EB
 Total Vehicles on Approach 132

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Baseline +P	3.3	132	2,724
Limiting Value	5	150	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Queen Kaahumanu Hwy
 Minor Street Hualalai Rd


Project _____
 Scenario Phase 1 +P
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	726	0	70	0
Through	5,070	4,490	0	0
Right	0	80	458	0
Total	1,449	1,143	132	0

Major Street Direction

x	North/South
	East/West



	Major Street	Minor Street	Warrant Met
	Queen Kaahumanu Hwy	Hualalai Rd	
Number of Approach Lanes	2	2	<u>NO</u>
Traffic Volume (VPH) *	2,592	132	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.



Major Street Queen Kaahumanu Hwy
 Minor Street Kuakini Hwy

Project _____
 Scenario Phase 1 +P
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	1,504	0	32	0
Through	4,697	4,054	0	0
Right	0	229	10	0
Total	1,550	1,071	11	0

Major Street Direction

x North/South
 _____ East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 1
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 99.6
 Approach with Worst Case Delay EB
 Total Vehicles on Approach 11

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Baseline +P	0.3	11	2,631
Limiting Value	4	100	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Queen Kaahumanu Hwy
 Minor Street Kuakini Hwy

Project _____
 Scenario Phase 1 +P
 Peak Hour AM+PM Peak Periods


Turn Movement Volumes

	NB	SB	EB	WB
Left	1,504	0	32	0
Through	4,697	4,054	0	0
Right	0	229	10	0
Total	1,550	1,071	11	0

Major Street Direction

x	North/South
	East/West

Warrant 3B, Peak Hour



* Note: 150 vph applies as the lower threshold volume for a minor-street approach with two or more lanes and 100 vph applies as the lower threshold volume for a minor-street approach with one lane.

Source: *California Manual on Uniform Traffic Control Devices*, Caltrans, 2014

	Major Street	Minor Street	Warrant Met
	Queen Kaahumanu Hwy	Kuakini Hwy	
Number of Approach Lanes	2	1	NO
Traffic Volume (VPH) *	2,621	11	
* Note: Traffic Volume for Major Street is Total Volume of Both Approches. Traffic Volume for Minor Street is the Volume of High Volume Approach.			

APPENDIX D: 8-HOUR SIGNAL WARRANT WORKSHEETS





Major Street Kuakini Hwy
 Minor Street Project Driveway

Project 0
 Scenario Existing
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	0	530	0	209
Through	3,618	4,894	0	0
Right	219	0	0	595
Total	959	1,356	0	201

Major Street Direction

x North/South
 East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 2
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 38.7
 Approach with Worst Case Delay WB
 Total Vehicles on Approach 101

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Existing	1.1	201	2,516
Limiting Value	5	150	650
Condition Satisfied?	Not Met	Met	Met
Warrant Met	<u>NO</u>		



Major Street Kuakini Hwy
 Minor Street Project Driveway


Project _____
 Scenario Existing
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	0	530	0	209
Through	3,618	4,894	0	0
Right	219	0	0	595
Total	480	678	0	101

Major Street Direction

x	North/South
	East/West



	Major Street	Minor Street	Warrant Met
	Kuakini Hwy	Project Driveway	
Number of Approach Lanes	1	2	<u>NO</u>
Traffic Volume (VPH) *	1,158	101	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.



Major Street Queen Kaahumanu Hwy
 Minor Street Hualalai Rd

Project 0
 Scenario Existing
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	698	0	85	0
Through	7,019	6,337	0	0
Right	0	123	517	0
Total	965	808	75	0

Major Street Direction

x North/South
 East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 2
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 32.9
 Approach with Worst Case Delay EB
 Total Vehicles on Approach 75

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Existing	0.7	75	1,847
Limiting Value	5	150	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Queen Kaahumanu Hwy
 Minor Street Hualalai Rd


Project _____
 Scenario Existing
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	698	0	85	0
Through	7,019	6,337	0	0
Right	0	123	517	0
Total	965	808	75	0

Major Street Direction

x	North/South
	East/West



	Major Street	Minor Street	Warrant Met
	Queen Kaahumanu Hwy	Hualalai Rd	
Number of Approach Lanes	2	2	<u>NO</u>
Traffic Volume (VPH) *	1,772	75	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.



Major Street Queen Kaahumanu Hwy
 Minor Street Kuakini Hwy

Project 0
 Scenario Existing
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	2,123	0	57	0
Through	6,365	5,490	0	0
Right	0	320	2	0
Total	1,061	726	7	0

Major Street Direction

x North/South
 East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 1
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 38.4
 Approach with Worst Case Delay EB
 Total Vehicles on Approach 7

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Existing	0.1	7	1,795
Limiting Value	4	100	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Queen Kaahumanu Hwy
 Minor Street Kuakini Hwy

Project _____
 Scenario Existing
 Peak Hour AM+PM Peak Periods


Turn Movement Volumes

	NB	SB	EB	WB
Left	2,123	0	57	0
Through	6,365	5,490	0	0
Right	0	320	2	0
Total	1,061	726	7	0

Major Street Direction

x	North/South
	East/West

Warrant 3B, Peak Hour



* Note: 150 vph applies as the lower threshold volume for a minor-street approach with two or more lanes and 100 vph applies as the lower threshold volume for a minor-street approach with one lane.

Source: *California Manual on Uniform Traffic Control Devices*, Caltrans, 2014

	Major Street	Minor Street	Warrant Met
	Queen Kaahumanu Hwy	Kuakini Hwy	
Number of Approach Lanes	2	1	<u>NO</u>
Traffic Volume (VPH) *	1,787	7	
* Note: Traffic Volume for Major Street is Total Volume of Both Approches. Traffic Volume for Minor Street is the Volume of High Volume Approach.			



Major Street Kuakini Hwy
 Minor Street Project Driveway

Project 0
 Scenario Phase 1
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	0	530	0	209
Through	4,270	5,770	0	0
Right	219	0	0	595
Total	1,122	1,575	0	201

Major Street Direction

x North/South
 East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 2
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 54.4
 Approach with Worst Case Delay WB
 Total Vehicles on Approach 101

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Baseline	1.5	201	2,898
Limiting Value	5	150	650
Condition Satisfied?	Not Met	Met	Met
Warrant Met	<u>NO</u>		



Major Street Kuakini Hwy
 Minor Street Project Driveway

Project 0
 Scenario Phase 1
 Peak Hour AM+PM Peak Periods


Turn Movement Volumes

	NB	SB	EB	WB
Left	0	530	0	209
Through	4,270	5,770	0	0
Right	219	0	0	595
Total	561	788	0	101

Major Street Direction

x North/South
 East/West

Warrant 3B, Peak Hour



* Note: 150 vph applies as the lower threshold volume for a minor-street approach with two or more lanes and 100 vph applies as the lower threshold volume for a minor-street approach with one lane.

Source: *California Manual on Uniform Traffic Control Devices*, Caltrans, 2014

	Major Street	Minor Street	Warrant Met
	Kuakini Hwy	Project Driveway	
Number of Approach Lanes	1	2	<u>NO</u>
Traffic Volume (VPH) *	1,349	101	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.



Major Street Queen Kaahumanu Hwy
 Minor Street Hualalai Rd

Project 0
 Scenario Phase 1
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	780	0	100	0
Through	9,210	8,320	0	0
Right	0	140	580	0
Total	1,249	1,058	85	0

Major Street Direction

x North/South
 East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 2
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 64.7
 Approach with Worst Case Delay EB
 Total Vehicles on Approach 85

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Baseline	1.5	85	2,391
Limiting Value	5	150	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Queen Kaahumanu Hwy
 Minor Street Hualalai Rd


Project 0
 Scenario Phase 1
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	780	0	100	0
Through	9,210	8,320	0	0
Right	0	140	580	0
Total	1,249	1,058	85	0

Major Street Direction

x	North/South
	East/West



	Major Street	Minor Street	Warrant Met
	Queen Kaahumanu Hwy	Hualalai Rd	
Number of Approach Lanes	2	2	<u>NO</u>
Traffic Volume (VPH) *	2,306	85	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.



Major Street Kuakini Hwy
 Minor Street Project Driveway

Project _____
 Scenario Phase 1 +P
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	0	900	0	174
Through	4,270	5,770	0	0
Right	171	0	0	864
Total	1,110	1,667	0	260

Major Street Direction

x North/South
 _____ East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 2
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 77.6
 Approach with Worst Case Delay WB
 Total Vehicles on Approach 130

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Baseline +P	2.8	260	3,037
Limiting Value	5	150	650
Condition Satisfied?	Not Met	Met	Met
Warrant Met	<u>NO</u>		



Major Street Kuakini Hwy
 Minor Street Project Driveway

Project _____
 Scenario Phase 1 +P
 Peak Hour AM+PM Peak Periods


Turn Movement Volumes

	NB	SB	EB	WB
Left	0	900	0	174
Through	4,270	5,770	0	0
Right	171	0	0	864
Total	555	834	0	130

Major Street Direction

x North/South
 East/West

Warrant 3B, Peak Hour



* Note: 150 vph applies as the lower threshold volume for a minor-street approach with two or more lanes and 100 vph applies as the lower threshold volume for a minor-street approach with one lane.

Source: *California Manual on Uniform Traffic Control Devices*, Caltrans, 2014

	Major Street	Minor Street	Warrant Met
	Kuakini Hwy	Project Driveway	
Number of Approach Lanes	1	2	<u>NO</u>
Traffic Volume (VPH) *	1,389	130	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.



Major Street Queen Kaahumanu Hwy
 Minor Street Hualalai Rd

Project _____
 Scenario Phase 1 +P
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	1,133	0	100	0
Through	9,210	8,320	0	0
Right	0	140	837	0
Total	1,293	1,058	117	0

Major Street Direction

x North/South
 _____ East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 2
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 89.3
 Approach with Worst Case Delay EB
 Total Vehicles on Approach 117

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Baseline +P	2.9	117	2,467
Limiting Value	5	150	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Queen Kaahumanu Hwy
 Minor Street Hualalai Rd

Project _____
 Scenario Phase 1 +P
 Peak Hour AM+PM Peak Periods


Turn Movement Volumes

	NB	SB	EB	WB
Left	1,133	0	100	0
Through	9,210	8,320	0	0
Right	0	140	837	0
Total	1,293	1,058	117	0

Major Street Direction

x	North/South
	East/West

Warrant 3B, Peak Hour



* Note: 150 vph applies as the lower threshold volume for a minor-street approach with two or more lanes and 100 vph applies as the lower threshold volume for a minor-street approach with one lane.

Source: *California Manual on Uniform Traffic Control Devices*, Caltrans, 2014

	Major Street	Minor Street	Warrant Met
	Queen Kaahumanu Hwy	Hualalai Rd	
Number of Approach Lanes	2	2	<u>NO</u>
Traffic Volume (VPH) *	2,350	117	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.



Major Street Queen Kaahumanu Hwy
 Minor Street Kuakini Hwy

Project _____
 Scenario Phase 1 +P
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	2,458	0	54	0
Through	8,673	7,438	0	0
Right	0	358	10	0
Total	1,391	975	8	0

Major Street Direction

x North/South
 _____ East/West

Intersection Geometry

Number of Approach Lanes for Minor Street 1
 Total Approaches 3

Worst Case Delay for Minor Street

Stopped Delay (seconds per vehicle) 99.6
 Approach with Worst Case Delay EB
 Total Vehicles on Approach 8

Warrant 3A, Peak Hour			
	Peak Hour Delay on Minor Approach (vehicle-hours)	Peak Hour Volume on Minor Approach (vph)	Peak Hour Entering Volume Serviced (vph)
Phase1 +P	0.2	8	2,374
Limiting Value	4	100	650
Condition Satisfied?	Not Met	Not Met	Met
Warrant Met	<u>NO</u>		



Major Street Queen Kaahumanu Hwy
 Minor Street Kuakini Hwy


Project _____
 Scenario Phase 1 +P
 Peak Hour AM+PM Peak Periods

Turn Movement Volumes

	NB	SB	EB	WB
Left	2,458	0	54	0
Through	8,673	7,438	0	0
Right	0	358	10	0
Total	1,391	975	8	0

Major Street Direction

x	North/South
	East/West



	Major Street	Minor Street	Warrant Met
	Queen Kaahumanu Hwy	Kuakini Hwy	
Number of Approach Lanes	2	1	<u>NO</u>
Traffic Volume (VPH) *	2,366	8	

* Note: Traffic Volume for Major Street is Total Volume of Both Approches.
 Traffic Volume for Minor Street is the Volume of High Volume Approach.